

Use this number when searching for this item:

## 9005840008000

#### Center Drill, 0.8mm, HSS, Uncoated



#### >> Item Info

| EDP#              | 9005840008000 |
|-------------------|---------------|
| Series            | 584           |
| Order Code        | 0.800         |
| Coating           | Uncoated      |
| Coolant Through   | No            |
| Cutting Direction | LH            |
| Material          | HSS           |
| Point Angle       | 118°          |
| Shank             | Straight      |
| Туре              | Center Drill  |


### >> Features

- relieved cone
- correct positioning between lathe centres
- for centre holes acc. to DIN 332 part 1, form R
- d1 = 0.8 mm: not double ended

## >> Suggested Materials

- Aluminum
- Alloyed Steels
- Free Cutting Steels
- Tool Steels
- Stainless Steels
- Ti and Ti-alloys
- Cast Iron
- Brass
- Bronze
- Copper
- Magnesium
- Special Alloys
- Plastic
- Hardened Steels

# >> Technical Specs



|             |          | Cut Ø | Cut Ø  | Cut Ø | Cut Ø         | Shank Ø | OAL   | Flute Length | Drilling Depth | Drilling Depth |            |        |
|-------------|----------|-------|--------|-------|---------------|---------|-------|--------------|----------------|----------------|------------|--------|
| EDP#        | Code No. | d1    | d1     | d1    | d1            | d2      | I1    | 12           | tmax           | tmax           | Shank Type | Flutes |
|             |          | mm    | inch   | frac. | wire / letter | mm      | mm    | mm           | mm             | inch           |            |        |
| 90058400080 | 0.800    | 0.800 | 0.0315 |       |               | 3.150   | 25.00 | 7.00         | 5.80           | 0.228          | Straight   | 2      |

<sup>\*\*\*</sup> **DISCLAIMER:** Data on this PDF is subject to change at any time without notice.