

Use this number when searching for this item:

9006090095000

Drill, 9.5mm 5xD 3Flt, GS 200 U, Carbide, TiN



>> Item Info

| | |
|-------------------|---------------|
| EDP # | 9006090095000 |
| Series | 609 |
| Order Code | 9.500 |
| Coating | TiN |
| Coolant Through | No |
| Cutting Direction | RH |
| Drilling Depth | 5xD |
| Material | Carbide |
| Point Angle | 150° |
| Shank | Straight |
| Type | GS 200 U |
| Tolerance | h7 |

>> Features

>> Suggested Materials

- Aluminum
- Alloyed Steels
- Free Cutting Steels
- Tool Steels
- Stainless Steels
- Ti and Ti-alloys
- Cast Iron
- Brass
- Bronze
- Copper
- Magnesium
- Special Alloys
- Plastic
- Hardened Steels

>> Technical Specs



| EDP # | Code No. | Cut Ø | Cut Ø | Cut Ø | Cut Ø | Shank Ø | OAL | Flute Length | Drilling Depth | Drilling Depth | Shank Type | Flutes |
|---------------|----------|-------|--------|-------|---------------|---------|-------|--------------|----------------|----------------|------------|--------|
| | | d1 | d1 | d1 | d1 | d2 | l1 | l2 | tmax | tmax | | |
| | | mm | inch | frac. | wire / letter | mm | mm | mm | mm | inch | | |
| 9006090095000 | 9.500 | 9.500 | 0.3740 | | | 9.500 | 84.00 | 52.00 | 37.75 | 1.486 | Straight | 3 |



WARNING:
This product contains Cobalt, a chemical known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

*** **DISCLAIMER:** Data on this PDF is subject to change at any time without notice.