

Use this number when searching for this item:

# **9014520160000** Drill, 16mm 5xD 3Flt, GS 200 U, Carbide, Uncoated



#### >> Item Info

EDP #	9014520160000
Series	1452
Order Code	16.000
Coating	Uncoated
Coolant Through	No
Cutting Direction	RH
Drilling Depth	5xD
Material	Carbide
Point Angle	150°
Shank	Straight

## >> Features


# >> Suggested Materials

- Aluminum
- Free Cutting Steels
- Cast Iron
- Brass

Туре	GS 200 U
Tolerance	h7

## >> Technical Specs

 $t_{max} = I_2 - 1,5 \times d_1$ 



		Cut Ø	Cut Ø	Cut Ø	Cut Ø	Shank Ø	OAL	Flute Length	Drilling Depth	Drilling Depth		
EDP #	Code No.	d1	d1	d1	d1	d2	11	12	tmax	tmax	Shank Type	Flutes
		mm	inch	frac.	wire / letter	mm	mm	mm	mm	inch		
90145201600 00	16.000	16.000	0.6299			16.000	115.00	73.00	49.00	1.929	Straight	3



\*\*\* **DISCLAIMER:** Data on this PDF is subject to change at any time without notice.

WARNING:

This product contains Cobalt, a chemical known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov