

Use this number when searching for this item:

9016620119100

Drill, 15/32 5xD, RT 100 F, Carbide, TiN, Coolant through



>> Item Info

EDP #	9016620119100
Series	1662
Order Code	11.910
Coating	TiN
Coolant Through	Yes
Cutting Direction	RH
Drilling Depth	5xD
Material	Carbide
Point Angle	140°
Shank	HA
Type	RT 100 F
Tolerance	m7


>> Features

- relieved cone
- main cutting edge form concave
- optimized cutting geometry
- sharp cutting edges

>> Suggested Materials

- Aluminum
- Free Cutting Steels
- Tool Steels
- Stainless Steels
- Ti and Ti-alloys
- Cast Iron
- Brass
- Bronze
- Copper
- Magnesium
- Special Alloys
- Hardened Steels

>> Technical Specs



EDP #	Code No.	Cut Ø	Cut Ø	Cut Ø	Cut Ø	Shank Ø	OAL	Flute Length	Drilling Depth	Drilling Depth	Shank Length	Shank Type	Flutes
		d1	d1	d1	d1	d2	l1	l2	tmax	tmax	l3		
		mm	inch	frac.	wire / letter	mm	mm	mm	mm	inch	mm		
9016620119100	11.910	11.910	0.4689	15/32		12.00	118.00	71.00	53.14	2.092	45.00	Straight	2



WARNING:
This product contains Cobalt, a chemical known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

*** **DISCLAIMER:** Data on this PDF is subject to change at any time without notice.