


METRIC




Series 3924
Standard ANSI
Tool Material HSS-E (Cobalt)
Spiral Point Straight flute
Chamfer Form B • 3.5 - 5
Class of Fit ISO 2(6H)




Through holes **Bright Finish** **External cooling**

d1 - P	D Limits	Tap Drill Range mm	Number of Flutes	d2 inch	SW inch	l1 inch	l3 inch	Order Code	EDP Number	Stock
M3 X 0.50	D2/D3	2.459 - 2.599	3	0.141	0.110	1.941	0.709	3.000	9039240030000	●
M4 X 0.70	D3/D4	3.242 - 3.422	3	0.168	0.131	2.130	0.827	4.000	9039240040000	●
M5 X 0.80	D3/D4	4.134 - 4.334	3	0.194	0.152	2.382	0.945	5.000	9039240050000	●
M6 X 1.00	D4/D5	4.917 - 5.153	3	0.255	0.191	2.500	1.181	6.000	9039240060000	●
M8 X 1.25	D4/D5	6.647 - 6.912	3	0.318	0.238	2.721	1.377	8.000	9039240080000	●
M10 X 1.50	D4/D5	8.376 - 8.676	3	0.381	0.286	2.941	1.456	10.000	9039240100000	●
M12 X 1.75	D5/D6	10.106 - 10.441	3	0.367	0.275	3.382	N/A	12.000	9039240120000	●
M14 X 2.00	D5/D6	11.835 - 12.210	3	0.429	0.322	3.591	N/A	14.000	9039240140000	●
M16 X 2.00	D6/D7	13.835 - 14.210	3	0.480	0.360	3.811	N/A	16.000	9039240160000	●

METRIC



Series 3930
Standard ANSI
Tool Material HSS-E (Cobalt)
Spiral Flute 45° Helix
Chamfer Form C • 2-3
Class of Fit ISO 2(6H)



Blind holes **Bright finish** **External cooling**

d1 - P	D Limits	Tap Drill Range mm	Number of Flutes	d2 inch	SW inch	l1 inch	l3 inch	Order Code	EDP Number	Stock
M3 X 0.50	D2/D3	2.459 - 2.599	2	0.141	0.110	1.941	0.709	3.000	9039300030000	●
M4 X 0.70	D3/D4	3.242 - 3.422	2	0.168	0.131	2.130	0.827	4.000	9039300040000	●
M5 X 0.80	D3/D4	4.134 - 4.334	2	0.194	0.152	2.382	0.945	5.000	9039300050000	●
M6 X 1.00	D4/D5	4.917 - 5.153	2	0.255	0.191	2.500	1.181	6.000	9039300060000	●
M8 X 1.25	D4/D5	6.647 - 6.912	2	0.318	0.238	2.721	1.377	8.000	9039300080000	●
M10 X 1.50	D4/D5	8.376 - 8.676	2	0.381	0.286	2.941	1.456	10.000	9039300100000	●
M12 X 1.75	D5/D6	10.106 - 10.441	2	0.367	0.275	3.382	N/A	12.000	9039300120000	●
M14 X 2.00	D5/D6	11.835 - 12.210	3	0.429	0.322	3.591	N/A	14.000	9039300140000	●
M16 X 2.00	D6/D7	13.835 - 14.210	3	0.480	0.360	3.811	N/A	16.000	9039300160000	●

"Tap drill Range" given is per the Class of Fit shown per Series #
 Additional Tap Drill sizes & percent of thread engagement can be found on pages 199 - 206.