

Use this number when searching for this item:

9056110177000

Drill, 17.7mm 5xD, RT 100 U, Carbide, nano-FIREX, Coolant through



>> Item Info

EDP#	9056110177000
Series	5611
Order Code	17.700
Coating	nano-FIREX
Coolant Through	Yes
Cutting Direction	RH
Drilling Depth	5xD
Material	Carbide
Point Angle	140°
Shank	HE
Туре	RT 100 U
Tolerance	m7

>> Features


- facet point grind


- main cutting edge form straight
- optimized cutting geometry

>> Suggested Materials

- Aluminum
- Alloyed Steels
- Free Cutting Steels
- Tool Steels
- Stainless Steels
- Ti and Ti-alloys
- Cast Iron
- Brass
- Bronze
- Copper
- Magnesium
- Special Alloys
- Hardened Steels

>> Technical Specs





		Cut Ø	Cut Ø	Cut Ø	Cut Ø	Shank Ø	OAL	Flute Length	Drilling Depth	Drilling Depth	Shank Length		
EDP#	Code No.	d1	d1	d1	d1	d2	I1	12	tmax	tmax	13	Shank Type	Flutes
		mm	inch	frac.	wire / letter	mm	mm	mm	mm	inch	mm		
9056110177 000	17.700	17.700	0.6969			18.00	143.00	93.00	66.45	2.616	48.00	whistle notch	2



*** **DISCLAIMER:** Data on this PDF is subject to change at any time without notice.