

Use this number when searching for this item:

### 9057440095200

#### Drill, 3/8 5xD, RT 100 US, Carbide, nano-A, Coolant through



#### >> Item Info

#### >> Features

## >> Suggested Materials

- Stainless Steels

EDP #9057440095200Series5744Order Code9.520Coatingnano-ACoolant ThroughYesCutting DirectionRHDrilling Depth5xDMaterialCarbidePoint Angle140°ShankHA		
Order Code9.520Coatingnano-ACoolant ThroughYesCutting DirectionRHDrilling Depth5xDMaterialCarbidePoint Angle140°ShankHA	EDP#	9057440095200
Coatingnano-ACoolant ThroughYesCutting DirectionRHDrilling Depth5xDMaterialCarbidePoint Angle140°ShankHA	Series	5744
Coolant ThroughYesCutting DirectionRHDrilling Depth5xDMaterialCarbidePoint Angle140°ShankHA	Order Code	9.520
Cutting DirectionRHDrilling Depth5xDMaterialCarbidePoint Angle140°ShankHA	Coating	nano-A
Drilling Depth5xDMaterialCarbidePoint Angle140°ShankHA	Coolant Through	Yes
Material Carbide  Point Angle 140°  Shank HA	<b>Cutting Direction</b>	RH
Point Angle 140° Shank HA	Drilling Depth	5xD
Shank HA	Material	Carbide
	Point Angle	140°
- DT 400 110	Shank	НА
RT 100 US	Туре	RT 100 US
Tolerance m7	Tolerance	m7

# >> Technical Specs



		Cut Ø	Cut Ø	Cut Ø	Cut Ø	Shank Ø	OAL	Flute Length	Drilling Depth	Drilling Depth	Shank Length		
EDP#	Code No.	d1	d1	d1	d1	d2	I1	12	tmax	tmax	13	Shank Type	Flutes
		mm	inch	frac.	wire / letter	mm	mm	mm	mm	inch	mm		
9057440095 200	9.520	9.520	0.3748	3/8		10.00	103.00	61.00	46.72	1.839	40.00	Straight	2

