



CEMENTED TUNGSTEN CARBIDE CUTTING TOOLS; UNCOATED OR ALTIN COATED; SDS GROUP 11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Date of Issue: 10/08/2019

Version: 1.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: CEMENTED TUNGSTEN CARBIDE CUTTING TOOLS; UNCOATED OR ALTIN COATED; SDS GROUP 11

This product covers solid metal blanks for manufacturing cutting tools, this SDS and the hazards and information described below apply to this product if the materials contained within the cutting tool(s) become available during processing conditions, including dusts and particulates.

1.2. Intended Use of the Product

Cutting Tools for manufacturing industries. When used as intended, this product is physiologically inert. Do not modify or resharpen product; return tools to Harvey Tool Company for alteration.

1.3. Name, Address, and Telephone of the Responsible Party

Company

Harvey Tool Company, LLC
428 Newburyport Turnpike
Rowley, MA 01969
800-645-5609

Harveysales@harveyperformance.com

1.4. Emergency Telephone Number

Emergency Number : Within USA and Canada: 1-800-424-9300 or +1-703-527-3887 (collect calls accepted)
For Chemical Emergency, Spill, Leak, Fire, Exposure, or Accident, call CHEMTREC – Day or Night

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US/CA Classification

Acute Tox. 4 (Oral)	H302
Resp. Sens. 1B	H334
Skin Sens. 1	H317
Carc. 1B	H350
Repr. 2	H361
Aquatic Chronic 4	H413

Full text of hazard classes and H-statements : see section 16

2.2. Label Elements

GHS-US/CA Labeling

Hazard Pictograms (GHS-US/CA)



Signal Word (GHS-US/CA)

: Danger

Hazard Statements (GHS-US/CA)

: H302 - Harmful if swallowed.
H317 - May cause an allergic skin reaction.
H334 - May cause an allergy or asthma symptoms or breathing difficulties if inhaled.
H350 - May cause cancer.
H361 - Suspected of damaging fertility or the unborn child.
H413 - May cause long lasting harmful effects to aquatic life.

Precautionary Statements (GHS-US/CA)

: P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P261 - Avoid breathing vapors, mist, or spray.
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

CEMENTED TUNGSTEN CARBIDE CUTTING TOOLS; UNCOATED OR ALTIM COATED; SDS GROUP 11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

P270 - Do not eat, drink or smoke when using this product.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, and eye protection.
P284 - [In case of inadequate ventilation] wear respiratory protection.
P301+P312 - IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P321 - Specific treatment (see section 4 on this SDS).
P330 - Rinse mouth.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P342+P311 - If experiencing respiratory symptoms: Call a POISON CENTER or doctor.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P405 - Store locked up.
P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions. Contains substances that are combustible dusts. If dried and allowed to accumulate, may form combustible dust concentrations in air that could ignite and cause an explosion. Take appropriate precautions.

Hazards Not Otherwise Classified (HNOC): Reacts violently with water

2.4. Unknown Acute Toxicity (GHS-US/CA)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Synonyms	Product Identifier	% *	GHS Ingredient Classification
Tungsten carbide	Tungsten carbide (WC) / Tungsten(IV) carbide	(CAS-No.) 12070-12-1	<= 96	Comb. Dust
Cobalt	Cobalt metal / Cobalt, elemental / C.I. 77320 / Cobalt metallic	(CAS-No.) 7440-48-4	<= 30	Acute Tox. 4 (Oral), H302 Resp. Sens. 1B, H334 Skin Sens. 1, H317 Carc. 1B, H350 Repr. 2, H361 Aquatic Chronic 4, H413
Tantalum carbide (TaC)	Tantalum carbide	(CAS-No.) 12070-06-3	<= 20	Not classified
Titanium carbide (TiC)	Titanium carbide	(CAS-No.) 12070-08-5	<= 20	Comb. Dust
Niobium carbide (NbC)	Niobium carbide	(CAS-No.) 12069-94-2	<= 20	Flam. Sol. 1, H228
Chromium	Chromium metal / Chromium, elemental / Chromium, metal / Chromium, metallic / Chrome, metal / Chrome	(CAS-No.) 7440-47-3	<= 5	Comb. Dust
Aluminum	Aluminium powder (stabilized) / Aluminium powder / Aluminum (metal) / CI 77000 / C.I. 77000 / Aluminum, metal / Aluminium, elemental / Aluminum metal / Aluminium, metal / Aluminium metal / Aluminium /	(CAS-No.) 7429-90-5	> 0.07	Flam. Sol. 1, H228 Water-react. 2, H261 Comb. Dust

CEMENTED TUNGSTEN CARBIDE CUTTING TOOLS; UNCOATED OR ALTiN COATED; SDS GROUP 11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

	Aluminium metal, powder / Aluminium powders / Aluminium powder (stabilised) / Pigment Metal 1 / Aluminum powder			
Titanium nitride	Titanium nitride (TiN) / BALINIT A	(CAS-No.) 25583-20-4	> 0.01	Not classified

Full text of H-phrases: see section 16

*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: Using proper respiratory protection, move the exposed person to fresh air at once. Encourage exposed person to cough, spit out, and blow nose to remove dust. Immediately call a poison center, physician, or emergency medical service.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: The health effects listed below are not likely to occur unless dust or fumes are generated by processing. Harmful if swallowed. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Skin sensitization. May cause cancer. Suspected of damaging fertility or the unborn child. Final product may have sharp edges.

Inhalation: Exposure may produce cough, mucous secretions, shortness of breath, chest tightness or other symptoms indicative of an allergic/sensitization reaction. Dust may be harmful or cause irritation.

Skin Contact: May cause an allergic skin reaction. Contact with hot, molten metal will cause thermal burns. Mechanical damage via flying particles and chipped slag is possible.

Eye Contact: During metal processing, dusts caused from milling and physical alteration will likely cause eye irritation. Fumes from thermal decomposition or molten material will likely be irritating to the eyes.

Ingestion: This material is harmful orally and can cause adverse health effects or death in significant amounts.

Chronic Symptoms: May cause cancer. Suspected of damaging fertility or the unborn child. Chronic exposure to cobalt-containing hard metal (dust or fume) can result in a serious lung disease called "hard metal lung disease", which is a type of pneumoconiosis (lung fibrosis). Repeated exposure to tantalum alloys may cause fibrosis, chronic rhinitis and "hard metal pneumoconiosis". . Chromium: Certain hexavalent chromium compounds have been demonstrated to be carcinogenic on the basis of epidemiological investigations on workers and experimental studies in animals. Increased incidences of respiratory cancer have been found in chromium (VI) workers. There is an increased incidence of lung cancer in industrial workers exposed to chromium (VI) compounds. Please refer to IARC volume 23 for a more detailed discussion. Aluminum: Inhalation of finely divided aluminum powder may cause pulmonary fibrosis.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Use Class D extinguishing agents on dusts, fines or molten metal. Use coarse water spray on chips and turnings.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Metallic dusts may ignite or explode.

Explosion Hazard: Dust explosion hazard in air. If excessive dust is generated from processing, it may present a dust explosion hazard when dispersed in air at sufficient quantities in the presence of an ignition source.

Reactivity: Hazardous reactions will not occur under normal conditions.

CEMENTED TUNGSTEN CARBIDE CUTTING TOOLS; UNCOATED OR ALTiN COATED; SDS GROUP 11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Metal oxides.

Other Information: Do not allow run-off from fire fighting to enter drains or water courses. Risk of dust explosion.

5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not breathe dust. Do not get in eyes, on skin, or on clothing. Avoid generating dust. Remove ignition sources. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain solid spills with appropriate barriers and prevent migration and entry into sewers or streams. Avoid generation of dust during clean-up of spills.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Use explosion proof vacuum during cleanup, with appropriate filter. Do not mix with other materials. Vacuum clean-up is preferred. If sweeping is required use a dust suppressant. Use only non-sparking tools. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: This product is physiologically inert in its massive form. However, user-generated dust and/or fumes may pose a physiological hazard if inhaled or ingested. Avoid inhalation of metal dusts and fumes. May cause an influenza-like illness. Avoid skin and eye contact with dusts to prevent mechanical irritation. User-generated dust is easily ignited and difficult to extinguish. Accumulation and dispersion of dust with an ignition source can cause a combustible dust explosion. Keep dust levels to a minimum and follow applicable regulations.

Precautions for Safe Handling: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid creating or spreading dust. Do not get in eyes, on skin, or on clothing. Do not breathe dust. Keep away from heat, sparks, open flames, hot surfaces. – No smoking. Handle empty containers with care because they may still present a hazard. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations. Avoid creating or spreading dust. Use explosion-proof electrical, ventilating, lighting equipment. Proper grounding procedures to avoid static electricity should be followed.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong acids. Strong oxidizers.

7.3. Specific End Use(s)

Cutting Tools for Manufacturing Industries.-----NA ONLY-----When used as intended, this product is physiologically inert. Do not modify or sharpen product; return tools to Harvey Tool Company for alteration.

CEMENTED TUNGSTEN CARBIDE CUTTING TOOLS; UNCOATED OR ALTIN COATED; SDS GROUP 11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

Chromium (7440-47-3)		
USA ACGIH	ACGIH TWA (mg/m ³)	0.5 mg/m ³ (inhalable particulate matter)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	1 mg/m ³
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	0.5 mg/m ³
USA IDLH	US IDLH (mg/m ³)	250 mg/m ³
Alberta	OEL TWA (mg/m ³)	0.5 mg/m ³
British Columbia	OEL TWA (mg/m ³)	0.5 mg/m ³ (total)
Manitoba	OEL TWA (mg/m ³)	0.5 mg/m ³ (inhalable particulate matter)
New Brunswick	OEL TWA (mg/m ³)	0.5 mg/m ³
Newfoundland & Labrador	OEL TWA (mg/m ³)	0.5 mg/m ³ (inhalable particulate matter)
Nova Scotia	OEL TWA (mg/m ³)	0.5 mg/m ³ (inhalable particulate matter)
Nunavut	OEL STEL (mg/m ³)	1.5 mg/m ³ (metal)
Nunavut	OEL TWA (mg/m ³)	0.5 mg/m ³ (metal)
Northwest Territories	OEL STEL (mg/m ³)	1.5 mg/m ³ (metal)
Northwest Territories	OEL TWA (mg/m ³)	0.5 mg/m ³ (metal)
Ontario	OEL TWA (mg/m ³)	0.5 mg/m ³
Prince Edward Island	OEL TWA (mg/m ³)	0.5 mg/m ³ (inhalable particulate matter)
Québec	VEMP (mg/m ³)	0.5 mg/m ³
Saskatchewan	OEL STEL (mg/m ³)	1.5 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	0.5 mg/m ³
Yukon	OEL STEL (mg/m ³)	3 mg/m ³
Yukon	OEL TWA (mg/m ³)	0.1 mg/m ³
Tungsten, insoluble compounds		
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	10 mg/m ³
Alberta	OEL STEL (mg/m ³)	10 mg/m ³
Alberta	OEL TWA (mg/m ³)	5 mg/m ³
British Columbia	OEL STEL (mg/m ³)	10 mg/m ³
British Columbia	OEL TWA (mg/m ³)	5 mg/m ³
New Brunswick	OEL STEL (mg/m ³)	10 mg/m ³
New Brunswick	OEL TWA (mg/m ³)	5 mg/m ³
Nunavut	OEL STEL (mg/m ³)	10 mg/m ³
Nunavut	OEL TWA (mg/m ³)	5 mg/m ³
Northwest Territories	OEL STEL (mg/m ³)	10 mg/m ³
Northwest Territories	OEL TWA (mg/m ³)	5 mg/m ³
Ontario	OEL STEL (mg/m ³)	10 mg/m ³
Ontario	OEL TWA (mg/m ³)	5 mg/m ³
Québec	VECD (mg/m ³)	10 mg/m ³
Québec	VEMP (mg/m ³)	5 mg/m ³
Saskatchewan	OEL STEL (mg/m ³)	10 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	5 mg/m ³
Yukon	OEL STEL (mg/m ³)	10 mg/m ³
Yukon	OEL TWA (mg/m ³)	5 mg/m ³
Tungsten compounds		

CEMENTED TUNGSTEN CARBIDE CUTTING TOOLS; UNCOATED OR ALTIM COATED; SDS GROUP 11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

USA ACGIH	ACGIH TWA (mg/m ³)	3 mg/m ³ (in the absence of cobalt-respirable particulate matter)
Manitoba	OEL TWA (mg/m ³)	3 mg/m ³ (in the absence of Cobalt-respirable particulate matter)
Newfoundland & Labrador	OEL TWA (mg/m ³)	3 mg/m ³ (in the absence of Cobalt-respirable particulate matter)
Nova Scotia	OEL TWA (mg/m ³)	3 mg/m ³ (in the absence of Cobalt-respirable particulate matter)
Prince Edward Island	OEL TWA (mg/m ³)	3 mg/m ³ (in the absence of Cobalt-respirable particulate matter)
Aluminum (7429-90-5)		
USA ACGIH	ACGIH TWA (mg/m ³)	1 mg/m ³ (respirable particulate matter)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)
Alberta	OEL TWA (mg/m ³)	10 mg/m ³ (dust)
British Columbia	OEL TWA (mg/m ³)	1 mg/m ³ (respirable)
Manitoba	OEL TWA (mg/m ³)	1 mg/m ³ (respirable particulate matter)
New Brunswick	OEL TWA (mg/m ³)	10 mg/m ³ (metal dust)
Newfoundland & Labrador	OEL TWA (mg/m ³)	1 mg/m ³ (respirable particulate matter)
Nova Scotia	OEL TWA (mg/m ³)	1 mg/m ³ (respirable particulate matter)
Nunavut	OEL STEL (mg/m ³)	20 mg/m ³ (metal-dust)
Nunavut	OEL TWA (mg/m ³)	10 mg/m ³ (metal-dust)
Northwest Territories	OEL STEL (mg/m ³)	20 mg/m ³ (metal-dust)
Northwest Territories	OEL TWA (mg/m ³)	10 mg/m ³ (metal-dust)
Ontario	OEL TWA (mg/m ³)	1 mg/m ³ (respirable)
Prince Edward Island	OEL TWA (mg/m ³)	1 mg/m ³ (respirable particulate matter)
Québec	VEMP (mg/m ³)	10 mg/m ³
Saskatchewan	OEL STEL (mg/m ³)	20 mg/m ³ (dust)
Saskatchewan	OEL TWA (mg/m ³)	10 mg/m ³ (dust)
Cobalt (7440-48-4)		
USA ACGIH	ACGIH TWA (mg/m ³)	0.02 mg/m ³ (inhalable particulate matter)
USA ACGIH	ACGIH chemical category	dermal sensitizer, Confirmed Animal Carcinogen with Unknown Relevance to Humans
USA ACGIH	Biological Exposure Indices (BEI)	15 µg/l Parameter: Cobalt - Medium: urine - Sampling time: end of shift at end of workweek (nonspecific)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	0.1 mg/m ³ (dust and fume)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	0.05 mg/m ³ (dust and fume)
USA IDLH	US IDLH (mg/m ³)	20 mg/m ³ (dust and fume)
Alberta	OEL TWA (mg/m ³)	0.02 mg/m ³
British Columbia	OEL TWA (mg/m ³)	0.02 mg/m ³
Manitoba	OEL TWA (mg/m ³)	0.02 mg/m ³ (inhalable particulate matter)
New Brunswick	OEL TWA (mg/m ³)	0.02 mg/m ³
Newfoundland & Labrador	OEL TWA (mg/m ³)	0.02 mg/m ³ (inhalable particulate matter)
Nova Scotia	OEL TWA (mg/m ³)	0.02 mg/m ³ (inhalable particulate matter)
Nunavut	OEL STEL (mg/m ³)	0.06 mg/m ³
Nunavut	OEL TWA (mg/m ³)	0.02 mg/m ³
Northwest Territories	OEL STEL (mg/m ³)	0.06 mg/m ³

CEMENTED TUNGSTEN CARBIDE CUTTING TOOLS; UNCOATED OR ALTiN COATED; SDS GROUP 11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Northwest Territories	OEL TWA (mg/m ³)	0.02 mg/m ³
Ontario	OEL TWA (mg/m ³)	0.02 mg/m ³
Prince Edward Island	OEL TWA (mg/m ³)	0.02 mg/m ³ (inhalable particulate matter)
Québec	VEMP (mg/m ³)	0.02 mg/m ³
Saskatchewan	OEL STEL (mg/m ³)	0.06 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	0.02 mg/m ³
Yukon	OEL STEL (mg/m ³)	0.15 mg/m ³ (dust and fume)
Yukon	OEL TWA (mg/m ³)	0.05 mg/m ³ (dust and fume)

8.2. Exposure Controls

Appropriate Engineering Controls: Suitable eye/body wash equipment should be available in the vicinity of any potential exposure. It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents or an explosion suppression system or an oxygen-deficient environment. Use local exhaust or general dilution ventilation or other suppression methods to maintain dust levels below exposure limits. Power equipment should be equipped with proper dust collection devices. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear protective gloves.

Eye and Face Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Solid
Appearance	: Grey, Grey With Dark Grey Coat
Odor	: Odorless
Odor Threshold	: Not available
pH	: Not available
Evaporation Rate	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: Not available
Flash Point	: Not available
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20°C	: Not available
Relative Density	: Not available
Density	: 15.7g/cm ³
Specific Gravity	: Not available

CEMENTED TUNGSTEN CARBIDE CUTTING TOOLS; UNCOATED OR ALTIN COATED; SDS GROUP 11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Solubility	: Insoluble
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: Not available

SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** Hazardous reactions will not occur under normal conditions.
- 10.2. Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).
- 10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, and incompatible materials. Sparks, heat, open flame and other sources of ignition. Dust accumulation (to minimize explosion hazard).
- 10.5. Incompatible Materials:** Strong acids. Strong oxidizers.
- 10.6. Hazardous Decomposition Products:** Not expected to decompose under ambient conditions. Thermal decomposition may produce : Metal oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity (Oral): Harmful if swallowed.

Acute Toxicity (Dermal): Not classified

Acute Toxicity (Inhalation): Not classified

LD50 and LC50 Data:

CEMENTED TUNGSTEN CARBIDE CUTTING TOOLS; UNCOATED OR ALTIN COATED; SDS GROUP 11	
ATE US/CA (oral)	719.67 mg/kg body weight

Skin Corrosion/Irritation: Not classified

Eye Damage/Irritation: Not classified

Respiratory or Skin Sensitization: May cause an allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Carcinogenicity: May cause cancer.

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Exposure may produce cough, mucous secretions, shortness of breath, chest tightness or other symptoms indicative of an allergic/sensitization reaction. Dust may be harmful or cause irritation.

Symptoms/Injuries After Skin Contact: May cause an allergic skin reaction. Contact with hot, molten metal will cause thermal burns. Mechanical damage via flying particles and chipped slag is possible.

Symptoms/Injuries After Eye Contact: During metal processing, dusts caused from milling and physical alteration will likely cause eye irritation. Fumes from thermal decomposition or molten material will likely be irritating to the eyes.

Symptoms/Injuries After Ingestion: This material is harmful orally and can cause adverse health effects or death in significant amounts.

Chronic Symptoms: May cause cancer. Suspected of damaging fertility or the unborn child. Chronic exposure to cobalt-containing hard metal (dust or fume) can result in a serious lung disease called "hard metal lung disease", which is a type of pneumoconiosis (lung fibrosis). Repeated exposure to tantalum alloys may cause fibrosis, chronic rhinitis and "hard metal pneumoconiosis". . Chromium: Certain hexavalent chromium compounds have been demonstrated to be carcinogenic on the basis of epidemiological investigations on workers and experimental studies in animals. Increased incidences of respiratory cancer have been found in chromium (VI) workers. There is an increased incidence of lung cancer in industrial workers exposed to chromium (VI) compounds. Please refer to IARC volume 23 for a more detailed discussion. Aluminum: Inhalation of finely divided aluminum powder may cause pulmonary fibrosis.

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Chromium (7440-47-3)

CEMENTED TUNGSTEN CARBIDE CUTTING TOOLS; UNCOATED OR ALTIN COATED; SDS GROUP 11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

LD50 Oral Rat	> 5000 mg/kg
LC50 Inhalation Rat	> 5.41 mg/l/4h
Cobalt (7440-48-4)	
LD50 Oral Rat	215.9 - 1140 mg/kg
LC50 Inhalation Rat	> 10 mg/l (Exposure time: 1 h)
LC50 Inhalation Rat	< 0.05 mg/l/4h
Chromium (7440-47-3)	
IARC Group	3
Cobalt compounds	
IARC Group	2B
National Toxicology Program (NTP) Status	Reasonably anticipated to be Human Carcinogen.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
Cobalt (7440-48-4)	
IARC Group	2B
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity, Reasonably anticipated to be Human Carcinogen.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General: May cause long lasting harmful effects to aquatic life.

Cobalt (7440-48-4)	
LC50 Fish 1	> 100 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])

12.2. Persistence and Degradability Not available

12.3. Bioaccumulative Potential

Cobalt (7440-48-4)	
BCF Fish 1	(no bioaccumulation)

12.4. Mobility in Soil Not available

12.5. Other Adverse Effects Not available

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Additional Information: Container may remain hazardous when empty. Continue to observe all precautions.

Ecology - Waste Materials: Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT Not regulated for transport

14.2. In Accordance with IMDG Not regulated for transport

14.3. In Accordance with IATA Not regulated for transport

14.4. In Accordance with TDG Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

CEMENTED TUNGSTEN CARBIDE CUTTING TOOLS; UNCOATED OR ALTIN COATED; SDS GROUP 11	
SARA Section 311/312 Hazard Classes	Health hazard - Acute toxicity (any route of exposure) Health hazard - Respiratory or skin sensitization Health hazard - Carcinogenicity Health hazard - Reproductive toxicity

CEMENTED TUNGSTEN CARBIDE CUTTING TOOLS; UNCOATED OR ALTIN COATED; SDS GROUP 11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Tungsten carbide (12070-12-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Tantalum carbide (TaC) (12070-06-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Titanium carbide (TiC) (12070-08-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Niobium carbide (NbC) (12069-94-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Chromium (7440-47-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	5000 lb no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is >100 µm
SARA Section 313 - Emission Reporting	1 %
Titanium nitride (25583-20-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Aluminum (7429-90-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
SARA Section 313 - Emission Reporting	1 % (dust or fume only)
Cobalt (7440-48-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
SARA Section 313 - Emission Reporting	0.1 %

15.2. US State Regulations

California Proposition 65



WARNING: This product can expose you to Cobalt, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Chemical Name (CAS No.)	Carcinogenicity	Developmental Toxicity	Female Reproductive Toxicity	Male Reproductive Toxicity
Cobalt (7440-48-4)	X			

Tungsten carbide (12070-12-1)
U.S. - New Jersey - Right to Know Hazardous Substance List
Chromium (7440-47-3)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances U.S. - Pennsylvania - RTK (Right to Know) List
Cobalt compounds
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List
Chromium compounds
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List
Aluminum (7429-90-5)

CEMENTED TUNGSTEN CARBIDE CUTTING TOOLS; UNCOATED OR ALTiN COATED; SDS GROUP 11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

U.S. - Massachusetts - Right To Know List
 U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
 U.S. - Pennsylvania - RTK (Right to Know) List

Cobalt (7440-48-4)

U.S. - Massachusetts - Right To Know List
 U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
 U.S. - Pennsylvania - RTK (Right to Know) List

15.3. Canadian Regulations

Tungsten carbide (12070-12-1)

Listed on the Canadian DSL (Domestic Substances List)

Tantalum carbide (TaC) (12070-06-3)

Listed on the Canadian DSL (Domestic Substances List)

Titanium carbide (TiC) (12070-08-5)

Listed on the Canadian DSL (Domestic Substances List)

Niobium carbide (NbC) (12069-94-2)

Listed on the Canadian DSL (Domestic Substances List)

Chromium (7440-47-3)

Listed on the Canadian DSL (Domestic Substances List)

Titanium nitride (25583-20-4)

Listed on the Canadian DSL (Domestic Substances List)

Aluminum (7429-90-5)

Listed on the Canadian DSL (Domestic Substances List)

Cobalt (7440-48-4)

Listed on the Canadian DSL (Domestic Substances List)

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest Revision : 10/08/2019

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

GHS Full Text Phrases:

Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Chronic 4	Hazardous to the aquatic environment - Chronic Hazard Category 4
Carc. 1B	Carcinogenicity Category 1B
Comb. Dust	Combustible Dust
Flam. Sol. 1	Flammable solids Category 1
Repr. 2	Reproductive toxicity Category 2
Resp. Sens. 1B	Respiratory sensitization, Category 1B
Skin Sens. 1	Skin sensitization, Category 1
Water-react. 2	Substances and mixtures which in contact with water emit flammable gases Category 2
H228	Flammable solid
H261	In contact with water releases flammable gas
H302	Harmful if swallowed
H317	May cause an allergic skin reaction
H334	May cause an allergy or asthma symptoms or breathing difficulties if inhaled
H350	May cause cancer

CEMENTED TUNGSTEN CARBIDE CUTTING TOOLS; UNCOATED OR ALTIN COATED; SDS GROUP 11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

H361	Suspected of damaging fertility or the unborn child
H413	May cause long lasting harmful effects to aquatic life

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS 2015 (Can, US)