

Achieve a perfect finish with the 3M top tier finishing systems.

3M[™] Trizact[™] Abrasives

3M™ Trizact™ Abrasives used in paint defect removal and refinement help reduce compounding and buffing time. They consist of precisely-shaped three-dimensional structures distributed uniformly over the substrate. As these structures wear, fresh, sharp mineral is constantly exposed to the workpiece, resulting in faster, more consistent performance cutting throughout the life of the discs.



3M™ Perfect-It™ EX Finishing System

Use the 3M™ Perfect-It™ EX system for optimal performance every time. Unique formulas quickly remove scratches and other surface defects. Additional wet time with these products allow technicians to use less material and easy clean up helps reduce process time.

3M™ Perfect-It™ Quick Connect Pads complement the Perfect-It™ EX system and help eliminate swirl marks on painted surfaces, even on difficult dark colored cars. The 3M™ Quick Connect Adaptor makes it easy to quickly switch between compound and polishing pads.





Tech Tips:

When removing dirt nibs or leveling excess clear coat, using a dry application abrasive, like the 3M™ Purple Finishing Film Hookit™ Disc, will allow you to see your work. Wet sanding is a messier process and requires additional time wiping dry to see if the defect is removed from the panel. Depending on the size of the defect, 3M recommends using grade P2000 Purple Finishing Film for the majority of applications. The cutting power is still there, but the finish is finer, saving you valuable process time. For heavy texture and large dirt nibs, grade P1500 Purple Finishing Film is still a viable option.

Using 3M™ Trizact™ Hookit™ Foam 3000 and 5000 Grade Discs will allow you to begin the polishing process with an abrasive. 3M™ Trizact™ Hookit™ Foam Discs begin the polishing process before you even touch the polisher. Since this is the case, the user will be able to utilize a 3M™ Perfect-It™ Quick Connect White Foam Compounding Pad to quickly remove any sand scratches left behind. Using a foam compounding pad instead of a wool compounding pad will decrease your process time and reduce the amount of swirls and dieback/comeback. This is very important for dark colored vehicles. A wool corpounding pad is more aggressive than foam and tends to leave a deeper swirl marks that the technician will need to remove later in the process. Abrasive polishing with 3M™ Trizact™ Hookit™ Foam 3000 and 5000 Grade Discs will eliminate the need for a wool compounding pad, making the job easier and faster!

Paint defect removal and refinement.

Defect removal.

P1200/P1500/P2000 — Remove dirt nibs and level excess surface texture over large or small areas:






- Use dry to highlight surface defects
- Sand out highlighted defects and match surface texture

		For Large Areas	
Product	Grade	Part No.	Size
	P1200	30668	6 in
3M™ Purple Finishing Film Hookit™ Disc	P1500	30667	6 in
	P2000	30666	6 in
3M™ Trizact™ Hookit™ Clear Coat Sanding Disc	P1500	02088	6 in
3M™ Paint Defect Removal Hand System Kit	Kit includes grades 1000, 1500, 2000, 2500, 3000		′

s	For Small	For Small Areas	
	Part No.	Size	
	30368	3 in	
	30367	3 in	
	30366	3 in	
	02094	3 in	
	33888	_	

Scratch refinement.

3000 — Refine the scratches left after defect removal to reduce compounding time:





		For Large Areas	
Product	Grade	Part No.	Size
3M™ Trizact™ Hookit™ Foam Disc	3000	02085	6 in


For Small Areas		
Part No.	Size	
02087	3 in	

Tech Tip 3M[™] Trizact[™] Hookit[™] Foam Discs are designed to be used damp. Using too much water will cause the abrasive to hydroplane, reducing cut rate. Using too little water will rapidly load the abrasive.

- Use to reduce compounding time
- Dampen disc and entire area to be sanded
- To thoroughly remove previous scratches, go over each area 5 times

Additional scratch refinement. (Optional)

5000 — Reduce buffing time with further scratch refinement:





- Use to further reduce compounding time
- Dampen disc and entire area to be sanded
- To thoroughly remove previous scratches, go over each area 5 times

		For Large	Areas
Product	Grade	Part No.	Size
3M™ Trizact™ Hookit™ Foam Disc	5000	30662	6 in

For Small Areas		
Part No.	Size	
30362	3 in	

Tech Tip Make sure to refine the 3M™ Trizact™ Hookit™ Foam 3000 Grade Disc area thoroughly with the 3M™ Trizact™ Hookit™ Foam 5000 Grade Disc.
Use a north, south, east, west sanding pattern to ensure proper refinement.

Finishing with 3M™ Perfect-It™ EX Finishing System.



- For fastest cut and less heat, use a 3M[™] Perfect-lt[™] 100% Wool Compounding Pad
- To reduce lint and achieve a better finish, use a 3M™ Perfect-It™ Low Lint Compounding Pad
- Eliminate lint and achieve the finest finish by using a 3M™ Perfect-It™ Foam Compounding Pad

Product	Part No.	Description
	36058	1/2 Pint
3M™ Perfect-It™ EX Rubbing Compound	36060	Quart
Rubbing Compound	36061	Gallon
	33287	6 in, 100% Wool
	33288	6 in, Low Lint 100% Wool
3M™ Perfect-It™	33284	6 in, White Foam
Compounding Pads*	05753	9 in, 100% Wool
	33279	9 in, Low Lint 100% Wool
	05706	9 in, White Foam

Tech Tip If during the scratch refinement process you used the 3M™ Trizact™ Hookit™ Foam 5000 Grade Disc, you can skip wool and go directly to the 3M™ Perfect-It™ Quick Connect White Foam Compounding Pad.



- Quickly and effectively removes compound swirl marks and produces an outstanding finish
- Stays wet longer, so you can use less
- Easier to use and clean up

Product	Part No.	Description
ONATM D. C. LLTM EXC	06093	1/2 Pint
3M™ Perfect-It™ EX Machine Polish	06094	Quart
IVIACIIIIIE FOIISII	06095	Gallon
3M™ Perfect-It™	33285	6 in, Grey Foam
Polishing Pads*	05707	8 in, Grey Foam

Tech Tip Our most advanced machine polish formulation allows for less material use per application.



- Eliminates fine swirl marks and produces a high gloss finish, even on the most difficult dark colored vehicles
- Great handling
- Easy clean up

Product	Part No.	Description
	06097	1/2 Pint
3M™ Perfect-It™ Ultrafine Machine	39062	Pint
Polish	06068	Quart
	06069	Gallon
3M™ Perfect-It™ Ultrafine Polishing	33286	6 in, Blue Ultrafine Foam
Pads*	05708	8 in, Blue Ultrafine Foam

Tech Tip When using 3M™ Perfect-It™ Ultrafine Machine Polish, do not buff dry. Make sure to wipe off excess material with a 3M™ Perfect-It™ III Auto Detailing Cloth.

^{*}Quick Connect, Double Sided

^{*}Quick Connect, Double Sided

^{*}Quick Connect, Double Sided

For Finishing Small Areas



3M™ Perfect-It™ 1 Finishing Material is a fast cutting finishing material designed to remove 5000 and finer scratches.

- Eliminate the use of traditional rubbing compounds
- Leaves a high gloss finish with minimum swirl marks

Product	Part No.	Description
ODATM D. C. LUTM 4	36066	1/2 Pint
3M™ Perfect-It™ 1 Finishing Material	36064	Quart
	36065	Gallon
3M™ Perfect-It™ 1	33292	6 in, Teal Foam
Finishing Pads**	33291	8 in, Teal Foam

Tech Tip

Use our 3M Perfect-It" Quick Connect 6 inch pads for small areas and easier control.

For a full list of available 3M Paint Finishing products, visit 3MCollision.com/PaintFinishing

Accessories

















Part No.	Description
05551	6 in
05777	6 in
05771	3 in
28703	6 in 3/16 in Orbit
28353	3 in 1/8 in Orbit
28737	1–1/4 in
28391	NA
05752	5/8 in Thread
	05551 05777 05771 28703 28353 28737















Product	Part No.	Description
3M™ Perfect-It™ Auto Detailing Cloth	06016	12 in x 14 in Yellow
3M™ Perfect-It™ Auto Detailing Cloth	06020	12 in x 14 in Blue
3M™ Hookit™ Clean Sanding Disc Pad Kit	20427	3 in x 1/2 in
3M™ Perfect-It™ Cleaner Clay	38070	200 g
3M™ Perfect-It™ Clean and Shine	06084	16 oz
3M™ Inspection Spray*	06082	Gallon
3M [™] Conditioning Brush	05761	Red
3M™ Perfect-It™ Buffing Apron	06059	Black

^{*}Requires chemical safe spray bottle

^{**}Use with 3M™ Perfect-It™ 1 Finishing Material

3M™ Perfect-It™ EX System:

The 3M™ Perfect-It™ EX System will provide technicians with optimal performance every time. The easy clean up and high performance will reduce process time and provide the perfect finish. The additional wet time with these products allow technicians to use less material.

3M[™] Perfect-It[™] EX System:

The 3M™ Perfect-It™ EX System will provide technicians with optimal performance every time. The easy clean up and high performance will reduce process time and provide the perfect finish. The additional wet time with these products allow technicians to use less material.

Introducing 3M™ Perfect-It™ EX Machine Polish


Now part of the 3M™ Perfect-It™ EX Finishing System

- Better finish, fast
- Stays wet longer, so you use less
- Easier to use and clean up

Learn more at 3MCollision.com/EX-Machine-Polish



PN 36060



Perfect-It™ EX de 3M™

Ahora parte del Sistema de Acabado Perfect-It™ EX de 3M™

• Mejor acabado, rápido

PN 06068

- Se mantiene mojado por más tiempo, entonces usted usa menos
- Más fácil de utilizar y limpiar

Aprenda más en 3MCollision.com/es/EX-Machine-Polish

Achieve a perfect finish with the 3M top tier finishing systems.

3M[™] Trizact[™] Abrasives

3M™ Trizact™ Abrasives used in paint defect removal and refinement help reduce compounding and buffing time. They consist of precisely-shaped three-dimensional structures distributed uniformly over the substrate. As these structures wear, fresh, sharp mineral is constantly exposed to the workpiece, resulting in faster, more consistent performance cutting throughout the life of the discs.



3M™ Perfect-It™ EX Finishing System

Use the 3M™ Perfect-It™ EX system for optimal performance every time. Unique formulas quickly remove scratches and other surface defects. Additional wet time with these products allow technicians to use less material and easy clean up helps reduce process time.

3M™ Perfect-It™ Quick Connect Pads complement the Perfect-It™ EX system and help eliminate swirl marks on painted surfaces, even on difficult dark colored cars. The 3M™ Quick Connect Adaptor makes it easy to quickly switch between compound and polishing pads.



Tech Tips:

When removing dirt nibs or leveling excess clear coat, using a dry application abrasive, like the 3M[™] Purple Finishing Film Hookit[™] Disc, will allow you to see your work. Wet sanding is a messier process and requires additional time wiping dry to see if the defect is removed from the panel. Depending on the size of the defect, 3M recommends using grade P2000 Purple Finishing Film for the majority of applications. The cutting power is still there, but the finish is finer, saving you valuable process time. For heavy texture and large dirt nibs, grade P1500 Purple Finishing Film is still a viable option.

Using 3M™ Trizact™ Hookit™ Foam 3000 and 5000 Grade Discs will allow you to begin the polishing process with an abrasive. 3M™ Trizact™ Hookit™ Foam Discs begin the polishing process before you even touch the polisher. Since this is the case, the user will be able to utilize a 3M™ Perfect-It™ Quick Connect White Foam Compounding Pad to quickly remove any sand scratches left behind. Using a foam compounding pad instead of a wool compounding pad will decrease your process time and reduce the amount of swirls and dieback/comeback. This is very important for dark colored vehicles. A wool compounding pad is more aggressive than foam and tends to leave a deeper swirl marks that the technician will need to remove later in the process. Abrasive polishing with 3M™ Trizact™ Hookit™ Foam 3000 and 5000 Grade Discs will eliminate the need for a wool compounding pad, making the job easier and faster!

Paint defect removal and refinement.

Defect removal.

P1200/P1500/P2000 — Remove dirt nibs and level excess surface texture over large or small areas:





- Use dry to highlight surface defects
- Sand out highlighted defects and match surface texture

		For Large	Areas
Product	Grade	Part No.	Size
ONATM D. I. E' . I .	P1200	30668	6 in
3M [™] Purple Finishing Film Hookit [™] Disc	P1500	30667	6 in
	P2000	30666	6 in
3M™ Trizact™ Hookit™ Clear Coat Sanding Disc	P1500	02088	6 in
3M [™] Paint Defect Removal Hand System Kit		es grades 10 00, 2500, 30	,

s	For Small Areas	
	Part No.	Size
	30368	3 in
	30367	3 in
	30366	3 in
	02094	3 in
	33888	_

Scratch refinement.

3000 — Refine the scratches left after defect removal to reduce compounding time:





		For Large Areas	
Product	Grade	Part No.	Size
3M™ Trizact™ Hookit™ Foam Disc	3000	02085	6 in


For Small Areas
Part No. Size
02087 3 in

- Tech Tip
- 3M[™] Trizact[™] Hookit[™] Foam Discs are designed to be used damp. Using too much water will cause the abrasive to hydroplane, reducing cut rate. Using too little water will rapidly load the abrasive.

- Use to reduce compounding time
- Dampen disc and entire area to be sanded
- To thoroughly remove previous scratches, go over each area 5 times

Additional scratch refinement. (Optional)

5000 — Reduce buffing time with further scratch refinement:





- Use to further reduce compounding time
- Dampen disc and entire area to be sanded
 To thoroughly remove previous scratches, go over each area 5 times

		For Large	Areas
Product	Grade	Part No.	Size
3M™ Trizact™ Hookit™ Foam Disc	5000	30662	6 in


For Small Areas		
Part No.	Size	
30362	3 in	

Tech Tip Make sure to refine the 3M™ Trizact™ Hookit™ Foam 3000 Grade Disc area thoroughly with the 3M™ Trizact™ Hookit™ Foam 5000 Grade Disc.
Use a north, south, east, west sanding pattern to ensure proper refinement.

Finishing with 3M™ Perfect-It™ EX Finishing System.

Compounding

Remove sand scratches completely





- For fastest cut and less heat, use a 3M[™] Perfect-It[™] 100% Wool Compounding Pad
- To reduce lint and achieve a better finish, use a $3M^{\mathsf{\tiny{M}}}$ Perfect-It[™] Low Lint Compounding Pad
- Eliminate lint and achieve the finest finish by using a 3M™ Perfect-It™ Foam Compounding Pad

Product	Part No.	Description
	36058	1/2 Pint
3M™ Perfect-It™ EX Rubbing Compound	36060	Quart
Rabbing Compound	36061	Gallon
	33287	6 in, 100% Wool
	33288	6 in, Low Lint 100% Wool
3M™ Perfect-It™	33284	6 in, White Foam
Compounding Pads*	05753	9 in, 100% Wool
	33279	9 in, Low Lint 100% Wool
	05706	9 in, White Foam

Tech Tip

If during the scratch refinement process you used the 3M™ Trizact™ Hookit[™] Foam 5000 Grade Disc, you can skip wool and go directly to the 3M™ Perfect-It™ Quick Connect White Foam Compounding Pad.

*Quick Connect, Double Sided



Polishing

Remove compound swirl marks:



- Quickly and effectively removes compound swirl marks and produces an outstanding finish
- Stays wet longer, so you can use less
- Easier to use and clean up

Product	Part No.	Description
	06093	1/2 Pint
3M™ Perfect-It™ EX Machine Polish	06094	Quart
Widefillie i Olisii	06095	Gallon
3M™ Perfect-It™	33285	6 in, Grey Foam
Polishing Pads*	05707	8 in, Grev Foam

Tech Tip

Our most advanced machine polish formulation allows for less material use per application.

*Quick Connect, Double Sided



Swirl Elimination

Permanently eliminate fine swirl marks



- Eliminates fine swirl marks and produces a high gloss finish, even on the most difficult dark colored vehicles
- Great handling
- Easy clean up

Product	Part No.	Description
	06097	1/2 Pint
3M [™] Perfect-It [™] Ultrafine Machine	39062	Pint
Polish	06068	Quart
	06069	Gallon
3M™ Perfect-It™ Ultrafine Polishing	33286	6 in, Blue Ultrafine Foam
Pads*	05708	8 in, Blue Ultrafine Foam

Tech Tip

When using 3M™ Perfect-It™ Ultrafine Machine Polish, do not buff dry. Make sure to wipe off excess material with a 3M™ Perfect-It™ III Auto Detailing Cloth.

^{*}Quick Connect, Double Sided

For Finishing Small Areas



3M™ Perfect-It™ 1 Finishing Material is a fast cutting finishing material designed to remove 5000 and finer scratches.

- Eliminate the use of traditional rubbing compounds
- Leaves a high gloss finish with minimum swirl marks

Product	Part No.	Description
	36066	1/2 Pint
3M™ Perfect-It™ 1 Finishing Material	36064	Quart
i illisilling waterial	36065	Gallon
3M™ Perfect-It™ 1	33292	6 in, Teal Foam
Finishing Pads**	33291	8 in, Teal Foam

Tech Tip

Use our 3M Perfect-It™ Quick Connect 6 inch pads for small areas and easier control.

For a full list of available 3M Paint Finishing products, visit 3MCollision.com/PaintFinishing

Accessories



















Product	Part No.	Description
3M [™] Perfect-It [™] Auto Detailing Cloth	06016	12 in x 14 in Yellow
3M [™] Perfect-It [™] Auto Detailing Cloth	06020	12 in x 14 in Blue
3M [™] Hookit [™] Clean Sanding Disc Pad Kit	20427	3 in x 1/2 in
3M [™] Perfect-It [™] Cleaner Clay	38070	200 g
3M™ Perfect-It™ Clean and Shine	06084	16 oz
3M [™] Inspection Spray*	06082	Gallon
3M [™] Conditioning Brush	05761	Red
3M™ Perfect-It™ Buffing Apron	06059	Black

^{*}Requires chemical safe spray bottle

^{**}Use with 3M™ Perfect-It™ 1 Finishing Material

Learn more at 3MCollision.com/PaintFinishing

Aprenda más en 3MCollision.com/es/PaintFinishing



Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application. Warranty, Limited Remedy and Disclaimer: Unless an additional warranty is specificable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

For health and safety information please refer to product labels and Safety Data Sheets.

Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of applicable. Limited Remedy and Disclaimer: Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

For health and safety information please refer to product labels and Safety Data Sheets



FOLLOW us on INSTAGRAM @3MCollision

FOLLOW us on INSTAGRAM
@3MCollision



LIKE us on FACEBOOK FACEBOOK.COM/3MCollision





FOLLOW us on TWITTER @3M Collision





SUBSCRIBE to our channel to watch comprehensive instructional videos YOUTUBE.COM/3Mautobodyrepair SUBSCRIBE to our channel to watch comprehensive instructional videos YOUTUBE.COM/3Mautobodyrepair



Automotive Aftermarket Division 3M Center, Building 223-6N-01 St. Paul, MN 55144 USA

Phone 1-877-666-2277
Web 3MCollision.com
3MCollision.com/es