

Dexterity with superb cut resistance for optimal productivity

- The HyFlex 11-625, 11-627 and 11-628 gloves deliver a perfect balance of comfort and sure handling with superior cut resistance
- The liners have an innovative yarn structure that contains an optimal rate of Dyneema® fibers. This offers high levels of cut resistance, for a safe use in controlling, handling and assembly applications involving contacts with sharp pieces
- The Lycra® material in the liners of both gloves, as well as the polyurethane coating, provides excellent flexibility and fit
- The three models are designed for use in dry, as well as slightly oily environment



Industries

- Automotive & Transportation
- Building & Construction
- Chemical
- Glass
- Machinery & Equipment
- Maintenance
- Metal Fabrication

Applications

- Glass manufacturing
- Aeronautics
- Assembly of white goods
- Plastics injection and moulding
- Assembling metal parts and components
- Handling of sharp-edged objects, pre-assembling, cutting of small dry or lightly oiled parts and maintenance.
- Finishing works

Performance Profile

- Perfect for a wide range of applications, the unique glove structure offers excellent abrasion resistance, cut protection, dexterity and comfort.
- Optimize workforce performance. Protect the hands of your workers and your productivity with the HyFlex 11-627 glove.
- The palm coating design improves worker grip, extends glove life in abrasive conditions and allows the back-of-hand to breathe.

Key Features

- The special formulation of the polyurethane coating gives the gloves flexibility and fit, as well as a secure grip on dry to slightly oily pieces for sure handling in a wide range of environments.
- Unique combination of Dyneema®, Nylon, Lycra®, and glass fiber.
- Ultra strong fibers provide extreme resistance to cuts and burrs.

Technologies



Performance Standards



Specifications

BRAND STYLE	DESCRIPTION	GAUGE	SIZE	LENGTH	COLOR	PACKAGE
HyFlex 11-625	Type: Palm coated Coating material: Polyurethane Liner material: Spandex Dyneema® Cuff style: Knitwrist	18	6-11	211-274 mm 8.30-10.78 inches	White	12 pairs/bag, 12 bags/carton
HyFlex 11-627	Type: Palm coated Coating material: Polyurethane Liner material: Spandex Dyneema® Cuff style: Knitwrist		5-11	195-276 7.67-10.86 inches	Grey	
HyFlex 11-628	Type: Palm coated Coating material: Polyurethane Liner material: Nylon Lycra® Dyneema® Cuff style: Knitwrist		6-11	270-320 mm 10.62-12.59 inches		

Europe, Middle East & Africa

Ansell Healthcare Europe NV
Riverside Business Park
Blvd International, 55
1070 Brussels, Belgium
+32 2 528 74 00
+32 2 528 74 01

North America

Ansell Protective Products Inc.
111 Wood Avenue South
Suite 210
Iselin, NJ 08830, USA
+1 800 800 0444
+1 800 800 0445

Australia

Ansell Limited
Level 3, 678 Victoria Street,
Richmond, Vic, 3121
Australia
+61 1800 337 041
+61 1800 803 578

Asia Pacific

Ansell Global Trading Center
(Malaysia) Sdn Bhd
Prima 6, Prima Avenue
Block 3512, Jalan Teknokrat 6
63000 Cyberjaya
Selangor, Malaysia
T: +60 3 83106688
F: +60 3 8318 6699

Latin America & Caribbean

Ansell Brazil Ltda.
Rua das Figueiras 474 - 4ª Andar
Bairro Jardim
SP 09080-300 Santo André
Brazil
CNPJ: 03.496.778/0001-21
+55 11 3356 3100

Russia

Анселл РУС
123610 Россия, Москва
Краснопресненская
Наб. 12, п.3, оф. 1304А
Тел. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates, except as noted. Dyneema® is a trademark of DSM. Use of this trademark is prohibited unless strictly authorized. Lycra® is a trademark owned by INVISTA. © 2016 Ansell Limited. All Rights Reserved

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.