CRC.

SAFETY DATA SHEET

1. Identification

Product identifier Ball & Roller Bearing Hi-Temp Industrial Grease

Other means of identification

Product code SL3630

Recommended use Ball & roller bearing grease

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.

Warminster, PA 18974 US

Telephone

General Information 215-674-4300 **Technical** 800-521-3168

Assistance

 Customer Service
 800-272-4620

 24-Hour Emergency
 800-424-9300 (US)

(CHEMTREC) 703-527-3887 (International)
Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Not classified.

Health hazardsSensitization, skinCategory 1Environmental hazardsHazardous to the aquatic environment,Category 2

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention Avoid breathing vapors. Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves. Avoid release to the environment.

Response If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Wash

contaminated clothing before reuse. Collect spillage.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), solvent-dewaxed heavy paraffinic		64742-65-0	20 - 30
Aluminum hydroxide benzoate stearate		54326-11-3	10 - 20

Material name: Ball & Roller Bearing Hi-Temp Industrial Grease SL3630 Version #: 01 Issue date: 08-06-2015

Chemical name	Common name and synonyms	CAS number	%
Molybdenum disulphide		1317-33-5	3 - 5
Tris(dipentyldithiocarbamato-S,S')a ntimony		15890-25-2	3 - 5
Calcium bis(dinonylnaphthalenesulphonate)		57855-77-3	< 1.5
Distillates (petroleum), Hydrotreated Light Naphthenic		64742-53-6	< 1.5

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. If ingestion of a large amount does occur, call a poison control center immediately.
Most important symptoms/effects, acute and delayed	May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
E Fire fighting measures	

5. Fire-fighting measures	
Suitable extinguishing media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	Move containers from fire area if you can do so without risk.
General fire hazards	No unusual fire or explosion hazards noted.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	The product is immiscible with water and will spread on the water surface. Stop the flow of material, if this is without risk. Prevent product from entering drains. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

7. Handling and storage

Precautions for safe handling	When using do not eat or drink. Avoid release to the environment. Wash contaminated clothing before reuse. Provide adequate ventilation. Avoid breathing vapor. Avoid contact with eyes, skin, and clothing. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. For product usage instructions, please see the product label.
Conditions for safe storage	Keen away from heat and sources of ignition. Store in a cool, dry place out of direct sunlight. Keen

Conditions for safe storage, Keep away from heat and sources of ignition. Store in a cool, dry place out of direct sunlight. Keep including any incompatibilities container tightly closed. Store away from incompatible materials (see Section 10 of the SDS).

cupational exposure limits			
US. OSHA Table Z-1 Limits for Air	Contaminants (29 CFR 1910.1000)		
Components	Туре	Value	Form
Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6)	PEL	5 mg/m3	Mist.
,		2000 mg/m3 500 ppm	
Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	PEL	5 mg/m3	Mist.
para (6/16 6 1/ 12 66 6)		2000 mg/m3 500 ppm	
Molybdenum disulphide (CAS 1317-33-5)	PEL	15 mg/m3	Total dust.
Tris(dipentyldithiocarbamat o-S,S')antimony (CAS 15890-25-2)	PEL	0.5 mg/m3	
US. ACGIH Threshold Limit Values			
Components	Туре	Value	Form
Aluminum hydroxide benzoate stearate (CAS 54326-11-3)	TWA	1 mg/m3	Respirable fraction
Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Inhalable fraction.
Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	TWA	5 mg/m3	Inhalable fraction.
Molybdenum disulphide (CAS 1317-33-5)	TWA	3 mg/m3	Respirable fraction
Tris(dipentyldithiocarbamat o-S,S')antimony (CAS 15890-25-2)	TWA	10 mg/m3 0.5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide to Chem	ical Hazards		
Components	Type	Value	Form
Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6)	Ceiling	1800 mg/m3	
•	STEL	10 mg/m3	Mist.
Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	Ceiling	1800 mg/m3	
	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Tris(dipentyldithiocarbamat	TWA	0.5 mg/m3	

15890-25-2) **Biological limit values Exposure guidelines**

No biological exposure limits noted for the ingredient(s).

Appropriate engineering

o-S,S')antimony (CAS

Occupational Exposure Limits are not relevant to the current physical form of the product.

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves such as: Rubber. Latex.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the

workplace.

9. Physical and chemical properties

Appearance

Physical stateSolid.FormGrease.ColorGray.

Odor Mild petroleum.

Odor threshold Not available.

PH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling

range

680 °F (360 °C) estimated

Flash point > 450 °F (> 232.2 °C) Cleveland Open Cup

Evaporation rate Slow.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

Not available.

Flammability limit - upper (%)

Vapor pressure Not available.
Vapor density Not available.

Relative density 0.9

Solubility (water) Insoluble.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature

500 °F (260 °C) estimated

Decomposition temperature Not available.

Viscosity (kinematic) $> 21.5 \text{ mm}^2/\text{s} (104 \text{ °F} (40 \text{ °C}))$

Percent volatile Not available.

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoidContact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition Carbon oxides. Nitrogen oxides (NOx). Sulfur oxides. Metal oxides.

products

11. Toxicological information

Information on likely routes of exposure

InhalationProlonged inhalation may be harmful.Skin contactMay cause an allergic skin reaction.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity May cause an allergic skin reaction.

Product Species Test Results

Ball & Roller Bearing Hi-Temp Industrial Grease

<u>Acute</u>

Dermal

LD50 Rabbit 3403 mg/kg estimated

Inhalation

LC50 Rat 65679 mg/m3, 4 hours estimated

Oral

LD50 Rat 6857 mg/kg estimated

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not available.

US. National Toxicology Program (NTP) Report on Carcinogens

Not available.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Product Species Test Results

Ball & Roller Bearing Hi-Temp Industrial Grease

Aquatic

Crustacea EC50 Daphnia 2000 mg/l, 48 hours estimated
Fish LC50 Fish 10000 mg/l, 96 hours estimated

Material name: Ball & Roller Bearing Hi-Temp Industrial Grease
SL3630 Version #: 01 Issue date: 08-06-2015

^{*} Estimates for product may be based on additional component data not shown.

Components Species Test Results

Tris(dipentyldithiocarbamato-S,S')antimony (CAS 15890-25-2)

Aquatic Chronic

Crustacea NOEC Water flea (Daphnia magna) 0.02 mg/l, 21 days

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal of waste from residues / unused products

This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33). Empty containers may be recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.

Hazardous waste code

Not regulated.

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Tris(dipentyldithiocarbamato-S,S')antimony (CAS 15890-25-2)

CERCLA Hazardous Substance List (40 CFR 302.4)

Tris(dipentyldithiocarbamato-S,S')antimony (CAS Listed.

15890-25-2)

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Tris(dipentyldithiocarbamato-S,S')antimony (CAS 15890-25-2)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Food and Drug Not regulated.

Administration (FDA)

^{*} Estimates for product may be based on additional component data not shown.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 Immediate Hazard - Yes
Hazard categories Delayed Hazard - No
Fire Hazard - No

Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Tris(dipentyldithiocarbamato-S,S')antimony (CAS 15890-25-2)

Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6)

Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed

US. New Jersey Worker and Community Right-to-Know Act

Tris(dipentyldithiocarbamato-S,S')antimony (CAS 15890-25-2)

Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6) Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)

US. Massachusetts RTK - Substance List

Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6)

Molybdenum disulphide (CAS 1317-33-5)

US. Pennsylvania Worker and Community Right-to-Know Law

Not listed.

US. Rhode Island RTK

Tris(dipentyldithiocarbamato-S,S')antimony (CAS 15890-25-2)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR

Not determined

51.100(s))

Consumer products (40 CFR 59, Subpt. C)

Not regulated

State

Consumer products Not regulated VOC content (CA) 0.3 % VOC content (OTC) 0.3 %

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

Material name: Ball & Roller Bearing Hi-Temp Industrial Grease SL3630 Version #: 01 Issue date: 08-06-2015

Country(s) or region Inventory name On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

08-06-2015 Issue date Allison Cho Prepared by

Version # 01

Further information Not available. Health: 1 **HMIS®** ratings

> Flammability: 1 Physical hazard: 0 Personal protection: B

Health: 1 NFPA ratings

Flammability: 1 Instability: 0

NFPA ratings



Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.

Material name: Ball & Roller Bearing Hi-Temp Industrial Grease

SDS US 8/8 SL3630 Version #: 01 Issue date: 08-06-2015