SAFETY DATA SHEET

1. Identification

Product number Product identifier Company information	1000024391 13.5 OZ PECO CONTACT CLEANER LB 12PK PECO FASTENERS & ELECTRICAL 1218-A SIX FLAGS RD AUSTELL, GA 30336-0483 United States
Company phone	General Assistance 1-770-745-1300
Emergency telephone US	1-866-836-8855
Version #	01
Recommended use	CLEANER
Recommended restrictions	None known.

2. Hazard(s) identification

Label elements

Physical hazards	Flammable aerosols	Category 1
Health hazards	Skin corrosion/irritation	Category 2
	Reproductive toxicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2
	Aspiration hazard	Category 1
OSHA defined hazards	Not classified.	



Signal word	Danger		
Hazard statement	Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.		
Precautionary statement			
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.		
Response	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. Collect spillage.		
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.		
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.		
Environmental hazards	Hazardous to the aquatic environment, acute Category 2 hazard		
	Hazardous to the aquatic environment, Category 2 long-term hazard		
Hazard(s) not otherwise classified (HNOC)	None known.		

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Naphtha, (Petroleum), Hydrotreated Light		64742-49-0	40 - 60
1,1-Difluoroethane		75-37-6	20 - 40
n-Hexane		110-54-3	20 - 40
Isopropyl Alcohol		67-63-0	2.5 - 10
Cyclohexane		110-82-7	0.1 - 1
Other components below reportable levels			0.01 - 0.1

Other components below reportable levels

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Foam. Powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.

6. Accidental release measures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear Personal precautions, appropriate protective equipment and clothing during clean-up. Do not breathe gas. Do not touch protective equipment and damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate emergency procedures closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
Environmental precautions	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe gas. Avoid contact with eyes, skin, and clothing. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.
Conditions for safe storage,	Level 3 Aerosol.
including any incompatibilities	Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
Cyclohexane (CAS 110-82-7)	PEL	1050 mg/m3	
,		300 ppm	
Isopropyl Alcohol (CAS 67-63-0)	PEL	980 mg/m3	
		400 ppm	
n-Hexane (CAS 110-54-3)	PEL	1800 mg/m3	
		500 ppm	
US. ACGIH Threshold Limit Value	S		
Components	Туре	Value	
Cyclohexane (CAS 110-82-7)	TWA	100 ppm	
Isopropyl Alcohol (CAS 67-63-0)	STEL	400 ppm	
	TWA	200 ppm	
n-Hexane (CAS 110-54-3)	TWA	50 ppm	
US. NIOSH: Pocket Guide to Cher	nical Hazards		
Components	Туре	Value	
Cyclohexane (CAS 110-82-7)	TWA	1050 mg/m3	
,		300 ppm	
Isopropyl Alcohol (CAS 67-63-0)	STEL	1225 mg/m3	
		500 ppm	
	TWA	980 mg/m3	
		400 ppm	
n-Hexane (CAS 110-54-3)	TWA	180 mg/m3	

US. NIOSH: Pocket Guide Components	to Chemical Hazards Typ		v	alue
			50	0 ppm
US. Workplace Environme Components	ental Exposure Level Typ		v	alue
1,1-Difluoroethane (CAS 75-37-6)	TW	4	2	700 mg/m3
10-01-0)			10	000 ppm
ological limit values				
ACGIH Biological Exposu Components	re Indices Value	Determinant	Specimen	Sampling Time
Isopropyl Alcohol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*
n-Hexane (CAS 110-54-3)	0.4 mg/l	2,5-Hexanedio n, without hydrolysis	Urine	*
* - For sampling details, plea	ase see the source doo	cument.		
posure guidelines				
US - California OELs: Skir	designation			
n-Hexane (CAS 110-54 US ACGIH Threshold Limi			absorbed thro	ugh the skin.
n-Hexane (CAS 110-54	-3)	Can be	absorbed thro	ugh the skin.
propriate engineering ntrols	should be matched or other engineerin exposure limits ha	d to conditions. If app ng controls to mainta ve not been establis	blicable, use pro in airborne leve hed, maintain a	hour) should be used. Ventilation rates occess enclosures, local exhaust ventilation els below recommended exposure limits. In irborne levels to an acceptable level. Eye ble when handling this product.
lividual protection measure	s, such as personal p	protective equipme	nt	
Eye/face protection	Wear safety glasse	es with side shields (or goggles).	
Skin protection Hand protection	Wear appropriate o supplier.	chemical resistant gl	oves. Suitable	gloves can be recommended by the glove
Other	Wear appropriate	chemical resistant cl	othing. Use of a	an impervious apron is recommended.
Respiratory protection	If permissible level air-supplied respiration		NIOSH mecha	nical filter / organic vapor cartridge or an
Thermal hazards	Wear appropriate t	hermal protective cl	othing, when ne	ecessary.
neral hygiene nsiderations	personal hygiene r	neasures, such as w	ashing after ha	n using do not smoke. Always observe go andling the material and before eating, ng and protective equipment to remove
Physical and chemica	l properties			
pearance	· ·			

9

Appearance	
Physical state	Gas.
Form	Aerosol.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling	Not available.
range	
Flash point	-58.0 °F (-50.0 °C) Propellant estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.

Upper/lower flammability or explosive limits

oppennewer naminability of exp	
Flammability limit - lower (%)	3.9 % estimated
Flammability limit - upper (%)	13.2 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	40 - 50 psig @70F estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	611.6 °F (322 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Specific gravity	0.673 - 0.693 estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Acids. Strong oxidizing agents. Isocyanates. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.
Skin contact	Causes skin irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity

May be fatal if swallowed and enters airways. Narcotic effects.

Product	Species	Test Results
13.5 OZ PECO CONTACT	CLEANER LB 12PK	
<u>Acute</u>		
Dermal		
LD50	Rat	7082 mg/kg
Inhalation		
LC50	Rat	806 mg/l/4h

Components	Species	Test Results
Cyclohexane (CAS 110-82-7)	
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
LC50	Rat	> 32880 mg/m3, 4 Hours
		> 5540 ppm, 4 Hours
Oral		
LD50	Rabbit	> 5000 mg/kg
	Rat	> 5000 mg/kg
sopropyl Alcohol (CAS 67-63	3-0)	
Acute		
Dermal		
LD50	Rabbit	16.4 ml/kg, 24 Hours
Inhalation		Ū.
LC50	Rat	> 10000 ppm, 6 Hours
Oral		
LD50	Rat	5.84 g/kg
		0.04 g/kg
	treated Light (CAS 64742-49-0)	
<u>Acute</u>		
Dermal	Cuince nig: Debbit	
LD50	Guinea pig; Rabbit	> 9.4 ml/kg, 24 Hours
	Rabbit	> 1900 mg/kg, 24 Hours
Inhalation		
LC50	Rat	> 5000 mg/m3, 4 Hours
		> 4980 mg/m3
		> 4980 mg/m3, 4 Hours
		> 4.96 mg/l, 4 Hours
		13700 ppm, 4 Hours
Oral		
LD50	Rat	4820 mg/kg
n-Hexane (CAS 110-54-3)		10_0 mg/kg
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 4 Hours
LDOU	Kabbit	
		> 5 ml/kg, 4 Hours
Inhalation		5000 0411
LC50	Rat	> 5000 ppm, 24 Hours
		> 31.86 mg/l
		73860 ppm, 4 Hours
Oral		
LD50	Rat	24 ml/kg
		24 g/kg
	Wistar rat	49 g/kg
* Estimates for product r	nay be based on additional component data r	not shown.
Skin corrosion/irritation	Causes skin irritation.	
	Direct contact with eyes may cause te	

Respiratory or skin sensitization			
Respiratory sensitization	Not a respiratory sensitizer.		
Skin sensitization	This product is not expected to cause skin sensitization.		
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.		
IARC Monographs. Overall Evaluation of Carcinogenicity Not listed. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Not regulated. US. National Toxicology Program (NTP) Report on Carcinogens			
Not listed.			
Reproductive toxicity	Suspected of damaging fertility or the unborn child.		
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.		
Specific target organ toxicity - repeated exposure	Respiratory system. Skin. Central nervous system. Eyes. Peripheral nervous system. May cause damage to organs through prolonged or repeated exposure.		
Aspiration hazard	May be fatal if swallowed and enters airways.		
Chronic effects	May cause damage to organs through prolonged or repeated exposure.		

12. Ecological information

Toxic to aquatic life with long lasting effects.

Product		Species	Test Results
13.5 OZ PECO CONTAC	T CLEANER LE	3 12PK	
Aquatic			
Algae	IC50	Algae	11111 mg/L, 72 Hours
Fish	LC50	Fish	10.2822 mg/L, 96 Hours
Components		Species	Test Results
Cyclohexane (CAS 110-8	32-7)		
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	23.03 - 42.07 mg/l, 96 hours
Isopropyl Alcohol (CAS 6	67-63-0)		
Aquatic			
Algae	IC50	Algae	1000.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	13299 mg/L, 48 Hours
Fish	LC50	Bluegill (Lepomis macrochirus)	> 1400 mg/l, 96 hours
n-Hexane (CAS 110-54-3	3)		
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	2.101 - 2.981 mg/l, 96 hours
•	•	additional component data not shown.	
sistence and degradabil	ity No data is	s available on the degradability of this product.	
accumulative potential			
Partition coefficient n-o	octanol / water (0.75	
Cyclohexane		3.44	
Isopropyl Alcohol		0.05	
n-Hexane		3.9	
bility in soil	No data a	vailable.	
er adverse effects		adverse environmental effects (e.g. ozone depl endocrine disruption, global warming potential)	

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

DOT	
UN number	UN1950
UN proper shipping name	Aerosols, flammable, (each not exceeding 1 L capacity)
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

ΙΑΤΑ

	UN number	UN1950
	UN proper shipping name	Aerosols, flammable
	Transport hazard class(es)	
	Class	2.1
	Subsidiary risk	-
	Label(s)	2.1
	Packing group	Not applicable.
	Environmental hazards	Yes
	ERG Code	10L
	Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
	Other information	
	Passenger and cargo aircraft	Allowed with restrictions.
	Cargo aircraft only	Allowed with restrictions.
	Packaging Exceptions	LTD QTY
IME)G	
	UN number	UN1950
	UN proper shipping name	AEROSOLS
	Transport hazard class(es)	
	Class	2.1
	Subsidiary risk	-
	Label(s)	2.1
	Packing group	Not applicable.

Environmental hazardsMarine pollutantYesEmSF-D, S-USpecial precautions for userRead safety instructions, SDS and emergency procedures before handling. Read safety
instructions, SDS and emergency procedures before handling. Read safetyPackaging ExceptionsLTD QTYTransport in bulk according to
Annex II of MARPOL 73/78 and
the IBC CodeNot applicable.

DOT FLAMMABLE GAS 2 IATA; IMDG

Marine pollutant



General information

IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.			
CERCLA Hazardous Substance List (40 CFR 302.4)			
Cyclohexane (CAS 110-82-7)	Listed.		
n-Hexane (CAS 110-54-3)	Listed.		
SARA 304 Emergency release notification			
Not regulated.			
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)			

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard	categories
nuzunu	categories

Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
n-Hexane	110-54-3	20 - 40
Cyclohexane	110-82-7	0.1 - 1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

n-Hexane (CAS 110-54-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

1,1-Difluoroethane (CAS 75-37-6)

Safe Drinking Water Act Not regulated. (SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100) Not listed.

- US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.
- (a))

Isopropyl Alcohol (CAS 67-63-0) Naphtha, (Petroleum), Hydrotreated Light (CAS 64742-49-0) n-Hexane (CAS 110-54-3)

US. Massachusetts RTK - Substance List

1,1-Difluoroethane (CAS 75-37-6) Cyclohexane (CAS 110-82-7) Isopropyl Alcohol (CAS 67-63-0) n-Hexane (CAS 110-54-3)

US. New Jersey Worker and Community Right-to-Know Act

1,1-Difluoroethane (CAS 75-37-6) Cyclohexane (CAS 110-82-7) Isopropyl Alcohol (CAS 67-63-0) n-Hexane (CAS 110-54-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Cyclohexane (CAS 110-82-7) Isopropyl Alcohol (CAS 67-63-0) n-Hexane (CAS 110-54-3)

US. Rhode Island RTK

1,1-Difluoroethane (CAS 75-37-6) Cyclohexane (CAS 110-82-7) Isopropyl Alcohol (CAS 67-63-0) n-Hexane (CAS 110-54-3)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

•••••••••••••••••••••••••••••••••••••••			
Benzene (CAS 71-43-2)	Listed: February 27, 1987		
US - California Proposition 65 - CRT: Listed date/Developmental toxin			
Benzene (CAS 71-43-2)	Listed: December 26, 1997		
Toluene (CAS 108-88-3)	Listed: January 1, 1991		
US - California Proposition 65 - CRT: Listed date/Male reproductive toxin			
Benzene (CAS 71-43-2)	Listed: December 26, 1997		

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date Version #	03-04-2016 01
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. We cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.
Revision information	Product and Company Identification: Alternate Trade Names