

## PRODUCT DATA SHEET

Extreme Duty Open Gear and Chain Lube 12 Wt Oz No. 03058 | Item# 1003318 | Case# 1003317

**Product Description** A heavy-duty, extreme pressure lubricant recommended

for reducing friction & wear in harsh environments. It resists heat & pressure, will not wash or wear off because

of weather, & will not break down after repeated workings.

**Applications** Open gears, chains, cables, wire ropes, guarry and mining

> equipment, fifth wheels of tractors and trucks, leaf springs, drive chains, screw threads, and flexible

couplings.

Unit Package Description 16 Ounce Aerosol

CRC Brand

Generic Description 1 Extreme Duty Open Gear & Chain Lube

Net Fill 12 Wt Oz

**UPC** Code 078254030586

**Unit Dimensions** 7.5H x 2.625W x 2.625D in

Units Per Case 12

Case Dimensions 8.75H x 8.5W x 11.5D in

Cases Per Pallet 133 Case Weight 12 lbs

I 2 of 5 Code 30078254030587

**Appearance** Black Semi-Viscous Liquid

Base Type Petroleum Oil

Flash point (F) 17.6°F -8°C Flash point (C)

Flammability Class - CPSC Flammable

0.86 Spec Gravity Concentrate Plastic Safe No Film Type Tacky

Film Thickness >1.0 Mils

**Evaporation Rate** Fast

Last revised: 2/27/2018

Page 1 of 2



oricante de Alta

educes Friction and Wear

Contains Moly and Graphite <sup>Muce la</sup> Fric**ción y el** Desgaste

<sup>iene</sup> Molibdeno y Grafito

Resistencia para Cadenas <sup>y Eng</sup>ranajes Abiertos

> Customer Care: 800-556-5074 Technical Assistance: 800-521-3168 www.crcindustries.com





## **PRODUCT DATA SHEET**

**NLGI** Grade Working Temp (F)

Working Temp (C)

Propellant

Aerosol Flammability Level

**DOT Proper Shipping Name** VOC % (Consumer Product

def)

VOC g/L (Consumer Product def)

VOC lbs/gal (Consumer

Prod def)

**VOC Category** 

Restricted from Sale In:

Removal (How To)

Not Determined

-25 to 350°F

-31.7 to 176.7°C

Hydrocarbon

Ш

Aerosols, Flammable, Limited Quantity (Marine Pollutant)

58

500.2

4.2

 $\mathsf{C}\mathsf{A}$ 

Gear, Chain or Wire Lubricant (Aerosol)

Remove with Petroleum Distillates.

Last revised: 2/27/2018

Page 2 of 2



Ubricante de Alta Resistencia para Cadenas **Fingranajes Abiertos** 

lefaces Friction and Wear Contains Moly and Graphite <sup>leduce</sup> la Fricción y el Desgaste <sup>liene</sup> Molibdeno y Grafito

of CRC Industries, Inc.

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair