

## PRODUCT DATA SHEET

Heavy Duty Clear Penetrating Grease, 13 Wt Oz No. 03056 | Item# 1003316 | Case# 1003315

**Product Description** A high tack, clear lubricating gel which provides

lubrication at temperatures from -30°F to 500°F. High adhesive strength ensures the product will resist throw off

and water wash-out.

**Applications** Gears, sprockets, hinges, chains, cable, wire rope, slides,

valves, pistons, rings, seals, bearings, sleeves, cams, and

bushings

Unit Package Description 20 Ounce Aerosol

**Brand CRC** 

Generic Description 1 Penetrating Grease

Net Fill 13 Wt Oz

**UPC** Code 078254030562

**Unit Dimensions** 9.25H x 2.63W x 2.63D in

Units Per Case 12

Case Dimensions 9.7H x 8.3W x 11.1D in

Cases Per Pallet 114 Case Weight 11 lbs

30078254030563 I 2 of 5 Code

**Appearance** Clear Liquid Base Type Petroleum Flash point (F) <20°F Flash point (C) <-7°C

Flammability Class - CPSC Extremely Flammable

Spec Gravity Concentrate 0.8 Plastic Safe No

Film Type Clear Oily

**Evaporation Rate** Fast

Dielectric Strength Not Determined **NLGI** Grade Not Determined -30 to 500°F Working Temp (F)

Last revised: 2/20/2018

Page 1 of 2



Duty Clear Penetrating

Grasa Penetrante Transparente

Grease

Contains PTFE

para Usos Pesados

gh Adhesive Strength flective from -30°F to 500°F

ene Politetrafluoretileno (PTFE) i Poder Adhesivo ctiva entre -30°F y 500°F siste la Limpieza con Agua

HARMFUL OR FATAL ED. CAUSES EYE

sists Water Wash Out



## **PRODUCT DATA SHEET**

Working Temp (C)

Propellant Hydrocarbon

NSF Category Code H2

NSF Number 145908

Aerosol Flammability Level III

DOT Proper Shipping Name Aerosols, Flammable, Limited Quantity

3.0

-34.4 to 260°C

VOC % (Consumer Product 45

def)

VOC g/L (Consumer 360

Product def)

VOC lbs/gal (Consumer

Prod def)

VOC Category Penetrant

Restricted from Sale In: CA

Removal (How To) Remove with Petroleum Distillates.

Heavy Duty Clear Penetrating Grease Grasa Penetrante Transparente para Usos Pesados Contains PTFE High Adhesive Strength Elective from -30°F to 500°F Resists Water Wash Out Combine Politetrafluoretileno (PTFE) Allo Poder Adhesivo Clectiva entre -30°F y 500°F Resiste la Limpleza con Agua

Last revised: 2/20/2018

Page 2 of 2



CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified