

JHJ-3, 3-TON HYDRAULIC BOTTLE JACK

453303

JET®JHJ Series Hydraulic Bottle Jacks have capacities from 2 to 100 tons, and are available in standard and low profile heights. The pump piston and ram are chrome plated for added corrosive resistance increasing durability. Each JHJ model functions in upright, angled or horizontal positions for increased versatility. JET JHJ Series Hydraulic Bottle Jacks comply with ANSI/ASME B30.1 and PALD-1 standards



FEATURES

- Precision machined and polished cylinders provide non-abrasive, leak-free, durable performance
- Heavy-duty bases are electrically welded providing a stable platform
- Hydraulic system is protected from damage by internal by-pass mechanism
- Chrome-plated piston and ram are corrosion resistant for use in any industrial environment
- Industrial-duty construction permits use in extreme climates
- Lifting, pushing, spreading, bending, pressing or straightening capabilities
- Upright, horizontal or angled operating positions increase versatility
- Pump handle included
- Complies with ANSI/ASME B30.1 and PALD-1 Standards



JET RED ASSURANCE 2-YEAR WARRANTY

JET warrants every product it sells. If one of our tools needs service or repair, one of our Authorized Service Centers located throughout the United States can give you quick service. In most cases, any of these JPW Industries Authorized Service Centers can authorize warranty repair, assist you in obtaining parts, or perform routine maintenance and major repair on your JET tools. For the name of an Authorized Service Center in your area call 1-800-274-6848.

STAND BEHIND YOUR WORK™



550+ SERVICE CENTERS NATIONWIDE

INDUSTRY-LEADING WARRANTIES

EXPERT TECHNICAL SERVICE

JHJ-3, 3-TON HYDRAULIC BOTTLE JACK

453303

SPECIFICATIONS

Load Capacity (Tons)	3
Piston Lift (In.)	4-1/2
Minimum Height (In.)	7-1/2
Maximum Height (In.)	14-3/8



STAND BEHIND YOUR WORK™



550+ SERVICE CENTERS NATIONWIDE

INDUSTRY-LEADING WARRANTIES

EXPERT TECHNICAL SERVICE

JHJ-3, 3-TON HYDRAULIC BOTTLE JACK

453303

FULL SERIES

STOCK NO	MODEL NO	LOAD CAPACITY (TONS)	PISTON LIFT (IN.)	MINIMUM HEIGHT (IN.)	MAXIMUM HEIGHT (IN.)
453399K	JHJ-100	100	5-23/32	12	17-11/16
453312	JHJ-12 1/2	12-1/2	5-7/8	9-1/2	18-1/2
453313K	JHJ-12 1/2L	12-1/2	3-3/4	6-36/4	13-3/8
453317	JHJ-17 1/2	17-1/2	6-1/2	10-3/8	20
453318K	JHJ-17 1/2L	17-1/2	3-1/2	6-3/4	13
453301	JHJ-2	2	4-1/2	7-1/8	13-5/8
453322	JHJ-22 1/2	22-1/2	6-1/4	10-5/8	16-7/8
453323K	JHJ-22 1/2L	22-1/2	3-3/8	7-1/8	12
453303	JHJ-3	3	4-1/2	7-1/2	14-3/8
453335K	JHJ-35	35	6-1/4	11	17-1/4
453305	JHJ-5	5	4-5/8	7-7/8	15-1/2
453360K	JHJ-60	60	6-3/4	12	8-5/8
453308	JHJ-8	8	4-5/8	7-7/8	15-1/2

STAND BEHIND YOUR WORK™



550+ SERVICE CENTERS NATIONWIDE

INDUSTRY-LEADING WARRANTIES

EXPERT TECHNICAL SERVICE