

SPECIFICATION SHEET 280-EV6131

EVOLUTION[™] DELUXE 6131 CAP STYLE HARD HAT

- Meets ANSI Z89.1-2014 Type I Class E requirements (Class C for Vented)
- Egyptian cotton core with porous PU coating for maximum sweat absorption. PH neutral, dermatologicaly tested
- HDPE strap & webbing clips with polyester webbing straps
- Custom imprinting is available
- High-Density Polyethylene (HDPE) shell
- Suspension can be removed and refitted for reverse wearing
- · Slip ratchet size adjustment for true "one size fits all"
- Universal accessory slots
- Vented versions are available to increase air circulation

APPLICATIONS

- Construction
- Oil & gas
- Mining
- Demolition
- High pressure jetting
- Energy companies
- Certain emergency services (FEMA & USAR)
 High-risk environments where high impact situations are of concern

CARE INSTRUCTIONS

The unit may be cleaned with soap and warm water and dried with a soft cloth. The helmet should not be cleaned with chemical or abrasive cleaners. The helmet should be stored out of direct sunlight, away from chemicals and not exposed to extremes of temperature.

TECHNICAL DATA

MATERIAL	Shell: High Density Polyethylene, Recyclable Suspension: HDPE strap & clips, polyester straps Sweatband: Egyptian cotton core with PU coating				
COLOR	□ White (-10) ■ Blue (-50) ■ Bright Orange (-0R) ■ Yellow (-20) ■ Red (-60) ■ Green (-30) ■ Lime Yellow (-LY)				
HAT SIZE	6 5/8 - 8 (20 7/8" - 25")				
EACH WEIGHT	13.2 oz				
PACKAGING	10 per case				
CASE	9.5" x 23" x 18" / 24.1cm x 58.4cm x 45.7cm				
CASE WEIGHT	8.4 lbs / 5.9 kg				
C00	USA				


BARCODES

ITEM	EACH	DOZEN	CASE					
280-EV6131-10	5038428136631		5038428811859					
280-EV6131-20	5038428136648		5038428811866					
280-EV6131-30	5038428136655		5038428811873					
280-EV6131-50	5038428136662		5038428811880					
280-EV6131-60	5038428136679		5038428811897					
280-EV6131-LY	5038428136709		5038428811927					
280-EV6131-OR	5038428136693		5038428811910					
VENTED HARD HATS (CLASS C)								
□ 280-EV6131V-10 5038428136792			5038428812016					
280-EV6131V-20	5038428136808		5038428812023					



DIMENSIONS (in)

	OSFA			
Α	11.5			
В	6.375			



PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

968 Albany Shaker Road | Latham, NY 12110 | 800-262-5755 | 518-861-0133 | Fax: 518-861-0144 | sales@pipusa.com | www.pipusa.com

This document and the information contained herein is the property of Protective Industrial Products. Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED.