



SPECIFICATION SHEET

280-EV6121

EVOLUTION® 6121 CAP STYLE HARD HAT

- Meets ANSI Z89.1-2014 Type I Class E requirements
- Black brushed nylon sweatband
- HDPE strap & webbing clips with polyethylene straps
- Custom imprinting is available
- High-Density Polyethylene (HDPE) shell
- Suspension can be removed and refitted for reverse wearing
- Slip ratchet for wide size range adjustment - high comfort fit
- Universal accessory slots
- Standard and short brim options

APPLICATIONS

- Construction
- Oil & gas
- Mining
- Demolition
- High pressure jetting
- Energy companies
- Certain emergency services (FEMA & USAR)
- High-risk environments where high impact situations are of concern

CARE INSTRUCTIONS

The unit may be cleaned with soap and warm water and dried with a soft cloth. The helmet should not be cleaned with chemical or abrasive cleaners. The helmet should be stored out of direct sunlight, away from chemicals and not exposed to extremes of temperature.

TECHNICAL DATA

MATERIAL	Shell: High Density Polyethylene, Recyclable Suspension: HDPE clips & straps Sweatband: Black brushed nylon
COLOR	<input type="checkbox"/> White (-10) <input type="checkbox"/> Pink (-39) <input type="checkbox"/> Lime Yellow (-LY) <input type="checkbox"/> Yellow (-20) <input type="checkbox"/> Blue (-50) <input type="checkbox"/> Bright Orange (-OR) <input type="checkbox"/> Green (-30) <input type="checkbox"/> Red (-60)
HAT SIZE	6 5/8 - 8 (20 7/8" - 25")
EACH WEIGHT	13.2 oz
PACKAGING	20 per case
CASE	19" x 23" x 18" / 48.3cm x 58.4cm x 45.7cm
CASE WEIGHT	16.75 lbs / 42.5 kg
COO	UAE

BARCODES

ITEM	EACH	DOZEN	CASE
<input type="checkbox"/> 280-EV6121-10	5038428136556	---	5038428811774
<input type="checkbox"/> 280-EV6121-20	5038428136563	---	5038428811781
<input type="checkbox"/> 280-EV6121-30	5038428136570	---	5038428811798
<input type="checkbox"/> 280-EV6121-39	5038428143653	---	5038428812368
<input type="checkbox"/> 280-EV6121-50	5038428136587	---	5038428811804
<input type="checkbox"/> 280-EV6121-60	5038428136594	---	5038428811811
<input type="checkbox"/> 280-EV6121-LY	5038428136624	---	5038428811842
<input type="checkbox"/> 280-EV6121-OR	5038428136617	---	5038428811835
SHORT BRIM HARD HATS			
<input type="checkbox"/> 280-EV6121S-10	5038428136839	---	5038428812054
<input type="checkbox"/> 280-EV6121S-20	5038428136846	---	5038428812061



DIMENSIONS (in)

	OSFA					
A	11.5					
B	6.375					

