

EVOLUTION™ DELUXE 6161

FULL BRIM HARD HAT - WHEEL RATCHET

TECHNICAL SPECIFICATION

HEAD PROTECTION

INSTRUCTIONS FOR USE

Fit hard hat on head and ensure the hard hat is adjusted to the size of the user's head. Fasten chin strap (if available) to ensure fit. The harness depth can also be adjusted on this helmet using the unique "3D Adjustment" setting for a precise fit.

SHELL:
High Density Polyethylene (HDPE)

CHAMLON™ SWEATBAND:
Egyptian cotton core with porous PU coating for maximum sweat absorption. PH neutral, dermatologically tested

WEBBING SUSPENSION:
HDPE Strap & Webbing Clips with Polyester Webbing Straps



FULL BRIM:
The full brim provides additional protection to the neck and ears against sun, glare, rain, snow and falling debris.



WHEEL RATCHET:
The Evolution Wheel Ratchet™ is the new easy to use wheel ratchet adjustment system to create a firm comfort fit with added security



CLEANING & MAINTENANCE

- The shell may be cleaned with soap and warm water and dried with a soft cloth
- The hard hat should not be cleaned with chemical or abrasive cleaners
- The hard hat should be stored out of direct sunlight
- The hard hat should be stored away from chemicals and extremes of temperature

CONFORMITY & TECH DATA

- Conforms to ANSI/ISEA Z89.1-2009 Type I Class E (Class C Vented)
- Wheel Ratchet for wide size range adjustment - High comfort fit
- Suspension can be removed and refitted for reverse wearing
- Vented and Non-Vented Options
- Compatible with Evospec® Safety Eyewear
- Custom imprinting is available
- COO/Harm Code: UAE / 6506.10.6075

TECHNICAL SPECIFICATION

HEAD PROTECTION

EVOLUTION™ DELUXE 6161

FULL BRIM HARD HAT - WHEEL RATCHET

DIMENSIONS OF OUTER PACKAGING

Quantity: 10

Weight: 10.5 lbs. (Approx.)

HEIGHT:
17.9"



LENGTH:
21.7"

WIDTH:
12.6"

DIMENSIONS OF HARD HAT

Hat Size: 6 5/8 - 8 (20 7/8" - 25")

Weight: 15.2 oz (Approx.)

HARD HAT FEATURES

STANDARDS	ANSI/ISEA Z89.1 - 2009, Type I Class E (Class C Vented)	Yes
PERFORMANCE	Lower Temp (-22° F) Reverse Donning Impact Resistance Electrical Insulation	Yes Yes Yes 54 Joules Yes: Class E 20,000V
SHELL MATERIAL	HDPE Recyclable	Yes Yes
SUSPENSION MATERIAL	HDPE Textile	Yes Yes
OPTIONS	Universal Accessories Reflective CR2 option Integrated Eyewear	Yes Yes Yes
SUSPENSION SYSTEM OPTIONS	JSP 3D Wheel Ratchet 6-Point	Yes Yes Yes
CHINSTRAP	4 pts 2 pts	Yes Yes
LOGO OPTIONS	Front Side MOQ Logo	Yes Yes 20

ITEM #	COLOR	BRIM	SHELL	UPC - EACH	UPC - CASE	CASE QTY
280-EV6161-10	White	Full	Non-Vented	5038428010986	5038428812535	10
280-EV6161-20	Yellow	Full	Non-Vented	5038428010993	5038428812542	10
280-EV6161-30	Green	Full	Non-Vented	5038428011006	5038428812559	10
280-EV6161-50	Blue	Full	Non-Vented	5038428011013	5038428812566	10
280-EV6161-60	Red	Full	Non-Vented	5038428011020	5038428812573	10
280-EV6161-LY	Bright Lime/Green	Full	Non-Vented	5038428011051	5038428812603	10
280-EV6161-OR	Bright Orange	Full	Non-Vented	5038428011044	5038428812597	10
280-EV6161V-10	White	Full	Vented	5038428011198	5038428812696	10
280-EV6161V-20	Yellow	Full	Vented	5038428011204	5038428812702	10

LIMITATIONS OF USE: Protection will only be offered if the hard hat is fitted correctly. Any hard hat subjected to severe impact should be replaced immediately. Do not apply paint, solvents or adhesive labels except in accordance with instructions from the manufacturer. The suspension, when in contact with the skin may cause allergic reactions to susceptible individuals. If this occurs leave the hazard area, remove the helmet and seek medical advice. The attention of users is also drawn to the dangers of modifying or removing any of the original component parts, other than as recommended by the manufacturer.