



**MCR
SAFETY**

**DC1 B
FR Gear
Specification Sheet**

PRODUCT DESCRIPTION:

Whether working in the rugged oil and gas industry or spending your day working near electrical hazards, stay safe and comfortable in MCR Safety's FR Gear made with Max Comfort™ fabrics. The DC1 coveralls feature a comfortable 88% cotton 12% Nylon twill material that meets the NFPA 2112-2012 Standard for Flame Resistant Garments and NFPA 70E Standard for Electrical Safety in the Workplace. All MCR Safety's FR Garments are UL Certified and have a lifetime FR guarantee.

Available in Regular and Tall Sizes, Royal Blue, Gray, Navy, Red, Tan

Sizes available: 34-66



FEATURES:

Available in Regular or Tall Sizes, Red, Gray, Navy, Royal Blue, and Tan

- NFPA 2112 UL Certified
- ASTM F1506 Electric Arc Protection
- NFPA 70E Hazard/Risk Cat HRC2
- ATPV ASTM 1959 9.3 cal/cm²
- Max Comfort™ 7 oz. 88% cotton / 12% nylon FR twill fabric
- Sewn with Nomex® Flame Resistant thread
- Three needle reinforced stitching on major seams for durability
- Heavy duty two-way YKK® brass break-away zipper with Nomex® tape
- Protective storm flap with snap closure to cover front zipper
- Two chest pockets with mitered flaps, snap closure, plus pen pocket
- Two front hip pockets on coverall pants
- Side pass through with snap closure
- Two back patch pockets – left pocket with flap and snap closure
- Bi-swing action back gussets for ease of movement and comfort
- Pen pocket on left arm
- Tool pocket on right leg
- Adjustable snap closure on cuffs of sleeves and legs
- All snaps have reinforcement strips

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2018 MCR Safety - All Rights Reserved



MCR
SAFETY

DC1B
FR Gear
Specification Sheet

APPLICATIONS:

Oil and Gas Industry, Electronic Assembly, Fracking, Mining,
Utilities

TECHNICAL DATA FOR: DC1B60

Series	Max Comfort	Front Closure	YKK 2-Way Zipper & Triple
Category	FR Gear		Snap
Color	Royal Blue	NFPA 2112 Cert.	Yes
Material	Flame Resistant, 88% Cotton / 12% Nylon - Max Comf	NFPA 70E Cert.	Yes
Material Weight	7.0 oz.	ASTM 1930 Cert.	Yes
Components	1 pc Coverall	ASTM F1506 Cert.	Yes
Flame Resistant	Flame Resistant	Hazard Risk Category	HRC2

Item No:	Chest	Sleeve	Back Length	Waist	Inseam	Color	Case Weight
DC1B36T	36	N/A	N/A	N/A	32	Royal Blue	25.700
DC1B38	38	N/A	N/A	N/A	30	Royal Blue	25.800
DC1B38T	38	N/A	N/A	N/A	32	Royal Blue	25.700
DC1B40T	40	N/A	N/A	N/A	32	Royal Blue	25.700
DC1B40	40	N/A	N/A	N/A	30	Royal Blue	24.160
DC1B42T	42	N/A	N/A	N/A	32	Royal Blue	25.800
DC1B44	44	N/A	N/A	N/A	30	Royal Blue	25.700
DC1B44T	44	N/A	N/A	N/A	32	Royal Blue	26.700
DC1B46T	46	N/A	N/A	N/A	32	Royal Blue	23.250
DC1B46	46	N/A	N/A	N/A	30	Royal Blue	25.700
DC1B48	48	N/A	N/A	N/A	30	Royal Blue	25.700
DC1B48T	48	N/A	N/A	N/A	32	Royal Blue	25.700
DC1B50	50	N/A	N/A	N/A	30	Royal Blue	25.700
DC1B50T	50	N/A	N/A	N/A	32	Royal Blue	25.700
DC1B52	52	N/A	N/A	N/A	30	Royal Blue	25.700
DC1B52T	52	N/A	N/A	N/A	32	Royal Blue	25.700
DC1B54T	54	N/A	N/A	N/A	32	Royal Blue	25.700
DC1B54	54	N/A	N/A	N/A	30	Royal Blue	25.700
DC1B56	56	N/A	N/A	N/A	30	Royal Blue	25.700
DC1B56T	56	N/A	N/A	N/A	32	Royal Blue	25.700
DC1B58T	58	N/A	N/A	N/A	32	Royal Blue	25.700
DC1B58	58	N/A	N/A	N/A	30	Royal Blue	25.700
DC1B60T	60	N/A	N/A	N/A	32	Royal Blue	25.700

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2018 MCR Safety - All Rights Reserved



MCR
SAFETY

DC1B FR Gear

Specification Sheet

Item No:	Chest	Sleeve	Back Length	Waist	Inseam	Color	Case Weight
DC1B60	60	N/A	N/A	N/A	30	Royal Blue	25.700
DC1B62T	62	N/A	N/A	N/A	32	Royal Blue	25.700
DC1B64T	64	N/A	N/A	N/A	32	Royal Blue	25.700
DC1B66T	66	N/A	N/A	N/A	32	Royal Blue	25.700

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2018 MCR Safety - All Rights Reserved