

DC 1 G FR Gear

Specification Sheet

PRODUCT DESCRIPTION:

Whether working in the rugged oil and gas industry or spending your day working near electrical hazards, stay safe and comfortable in MCR Safety's FR Gear made with Max Comfort™ fabrics. The DC1 coveralls feature a comfortable 88% cotton 12% Nylon twill material that meets the NFPA 2112-2012 Standard for Flame Resistant Garments and NFPA 70E Standard for Electrical Safety in the Workplace. All MCR Safety's FR Garments are UL Certified and have a lifetime FR guarantee.

Available in Regular or Tall Sizes, Red, Gray, Navy, Royal Blue, & Tan

Sizes available: 34-66

FEATURES:

- Available in Regular or Tall Sizes, Red, Gray, Navy, Royal Blue, & Tan
- NFPA 2112 UL Certified
- ASTM F1506 Electric Arc Protection
- NFPA 70E Hazard/Risk Cat HRC2 / ATPV 9.3 cal/cm²
- Max Comfort™ 7 oz. 88% cotton / 12% nylon FR twill fabric
- Sewn with Nomex® Flame Resistant thread
- Three needle reinforced stitching on major seams for durability
- Heavy duty two-way YKK® brass break-away zipper with Nomex® tape
- Protective storm flap with snap closure to cover front zipper
- Two chest pockets with mitered flaps, snap closure, plus pen pocket
- Two front hip pockets on coverall pants
- Side pass through with snap closure
- Two back patch pockets left pocket with flap and snap closure
- Bi-swing action back gussets for ease of movement and comfort
- Pen pocket on left arm
- Tool pocket on right leg





DC I G FR Gear

Specification Sheet

- Adjustable snap closure on cuffs of sleeves and legs
- All snaps have reinforcement strips

APPLICATIONS:

Oil and Gas Industry, Electronic Assembly, Fracking, Mining, Utilities

TECHNICAL DATA FOR: DC1G38T

SeriesMax ComfortCategoryFR GearColorGray

Material Flame Resistant, 88% Cotton /

12% Nylon - Max Comf

Material Weight7.0 oz.Components1 pc CoverallFlame ResistantFlame Resistant

Front Closure YKK 2-Way Zipper & Triple

NFPA 2112 Cert. Yes
NFPA 70E Cert. Yes

ASTM 1930 Cert. Yes
ASTM F1506 Cert. Yes
Hazard Risk Category HRC2

| Item No: | Chest | Sleeve | Back Length | Waist | Inseam | Color | Case Weight |
|----------|-------|--------|-------------|-------|--------|-------|-------------|
| | | | | | | | |
| DC1G34 | 34 | N/A | N/A | N/A | 30 | Gray | 25.700 |
| DC1G36 | 36 | N/A | N/A | N/A | 30 | Gray | 25.700 |
| DC1G36T | 36 | N/A | N/A | N/A | 32 | Gray | 25.700 |
| DC1G38T | 38 | N/A | N/A | N/A | 32 | Gray | 25.700 |
| DC1G42 | 42 | N/A | N/A | N/A | 30 | Gray | 25.700 |
| DC1G42T | 42 | N/A | N/A | N/A | 32 | Gray | 21.680 |
| DC1G44 | 44 | N/A | N/A | N/A | 30 | Gray | 25.700 |
| DC1G44T | 44 | N/A | N/A | N/A | 32 | Gray | 25.700 |
| DC1G46 | 46 | N/A | N/A | N/A | 30 | Gray | 25.700 |
| DC1G46T | 46 | N/A | N/A | N/A | 32 | Gray | 22.740 |
| DC1G48 | 48 | N/A | N/A | N/A | 30 | Gray | 25.700 |
| DC1G48T | 48 | N/A | N/A | N/A | 32 | Gray | 23.170 |
| DC1G50 | 50 | N/A | N/A | N/A | 30 | Gray | 25.700 |
| DC1G50T | 50 | N/A | N/A | N/A | 32 | Gray | 25.700 |
| DC1G52T | 52 | N/A | N/A | N/A | 32 | Gray | 25.700 |
| DC1G52 | 52 | N/A | N/A | N/A | 30 | Gray | 23.320 |
| DC1G54 | 54 | N/A | N/A | N/A | 30 | Gray | 25.700 |
| DC1G54T | 54 | N/A | N/A | N/A | 32 | Gray | 25.190 |
| DC1G56 | 56 | N/A | N/A | N/A | 30 | Gray | 25.700 |

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrsafety.com



DC I G FR Gear

Specification Sheet

| Item No: | Chest | Sleeve | Back Length | Waist | Inseam | Color | Case Weight |
|----------|-------|--------|-------------|-------|--------|-------|-------------|
| DC1G56T | 56 | N/A | N/A | N/A | 32 | Gray | 25.700 |
| DC1G58 | 58 | N/A | N/A | N/A | 30 | Gray | 25.700 |
| DC1G58T | 58 | N/A | N/A | N/A | 32 | Gray | 26.280 |
| DC1G60T | 60 | N/A | N/A | N/A | 32 | Gray | 25.700 |
| DC1G60 | 60 | N/A | N/A | N/A | 30 | Gray | 25.700 |
| DC1G62T | 62 | N/A | N/A | N/A | 32 | Gray | 25.700 |
| DC1G64T | 64 | N/A | N/A | N/A | 32 | Gray | 28.270 |
| DC1G66T | 66 | N/A | N/A | N/A | 32 | Gray | 25.700 |