

### DC 1 G FR Gear

**Specification Sheet** 

#### **PRODUCT DESCRIPTION:**

Whether working in the rugged oil and gas industry or spending your day working near electrical hazards, stay safe and comfortable in MCR Safety's FR Gear made with Max Comfort™ fabrics. The DC1 coveralls feature a comfortable 88% cotton 12% Nylon twill material that meets the NFPA 2112-2012 Standard for Flame Resistant Garments and NFPA 70E Standard for Electrical Safety in the Workplace. All MCR Safety's FR Garments are UL Certified and have a lifetime FR guarantee.

Available in Regular or Tall Sizes, Red, Gray, Navy, Royal Blue, & Tan

Sizes available: 34-66

### **FEATURES:**

- Available in Regular or Tall Sizes, Red, Gray, Navy, Royal Blue, & Tan
- NFPA 2112 UL Certified
- ASTM F1506 Electric Arc Protection
- NFPA 70E Hazard/Risk Cat HRC2 / ATPV 9.3 cal/cm<sup>2</sup>
- Max Comfort™ 7 oz. 88% cotton / 12% nylon FR twill fabric
- Sewn with Nomex® Flame Resistant thread
- Three needle reinforced stitching on major seams for durability
- Heavy duty two-way YKK® brass break-away zipper with Nomex® tape
- Protective storm flap with snap closure to cover front zipper
- Two chest pockets with mitered flaps, snap closure, plus pen pocket
- Two front hip pockets on coverall pants
- Side pass through with snap closure
- Two back patch pockets left pocket with flap and snap closure
- Bi-swing action back gussets for ease of movement and comfort
- Pen pocket on left arm
- Tool pocket on right leg





# DC I G FR Gear

**Specification Sheet** 

- Adjustable snap closure on cuffs of sleeves and legs
- All snaps have reinforcement strips

### **APPLICATIONS:**

Oil and Gas Industry, Electronic Assembly, Fracking, Mining, Utilities

### **TECHNICAL DATA FOR:** DC1G52

Series Max Comfort
Category FR Gear
Color Gray

Material Flame Resistant, 88% Cotton /

12% Nylon - Max Comf

Material Weight7.0 oz.Components1 pc CoverallFlame ResistantFlame Resistant

Front Closure YKK 2-Way Zipper & Triple

 Snap

 NFPA 2112 Cert.
 Yes

 NFPA 70E Cert.
 Yes

 ASTM 1930 Cert.
 Yes

ASTM 1930 Cert. Yes
ASTM F1506 Cert. Yes
Hazard Risk Category HRC2

Itama Na	Obset	Oleane	Dooled on the	\M_=:=4		O a la n	Ones Waterly
Item No:	Chest	Sleeve	Back Length	Waist	Inseam	Color	Case Weight
DC1G34	34	N/A	N/A	N/A	30	Gray	25.700
DC1G36	36	N/A	N/A	N/A	30	Gray	25.700
DC1G36T	36	N/A	N/A	N/A	32	Gray	25.700
DC1G38T	38	N/A	N/A	N/A	32	Gray	25.700
DC1G42	42	N/A	N/A	N/A	30	Gray	25.700
DC1G42T	42	N/A	N/A	N/A	32	Gray	21.680
DC1G44	44	N/A	N/A	N/A	30	Gray	25.700
DC1G44T	44	N/A	N/A	N/A	32	Gray	25.700
DC1G46	46	N/A	N/A	N/A	30	Gray	25.700
DC1G46T	46	N/A	N/A	N/A	32	Gray	22.740
DC1G48	48	N/A	N/A	N/A	30	Gray	25.700
DC1G48T	48	N/A	N/A	N/A	32	Gray	23.170
DC1G50	50	N/A	N/A	N/A	30	Gray	25.700
DC1G50T	50	N/A	N/A	N/A	32	Gray	25.700
DC1G52T	52	N/A	N/A	N/A	32	Gray	25.700
DC1G52	52	N/A	N/A	N/A	30	Gray	23.320
DC1G54	54	N/A	N/A	N/A	30	Gray	25.700
DC1G54T	54	N/A	N/A	N/A	32	Gray	25.190
DC1G56	56	N/A	N/A	N/A	30	Gray	25.700

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrsafety.com



## DC I G FR Gear

**Specification Sheet** 

Item No:	Chest	Sleeve	Back Length	Waist	Inseam	Color	Case Weight
DC1G56T	56	N/A	N/A	N/A	32	Gray	25.700
DC1G58	58	N/A	N/A	N/A	30	Gray	25.700
DC1G58T	58	N/A	N/A	N/A	32	Gray	26.280
DC1G60T	60	N/A	N/A	N/A	32	Gray	25.700
DC1G60	60	N/A	N/A	N/A	30	Gray	25.700
DC1G62T	62	N/A	N/A	N/A	32	Gray	25.700
DC1G64T	64	N/A	N/A	N/A	32	Gray	28.270
DC1G66T	66	N/A	N/A	N/A	32	Gray	25.700