

## DCIR FR Gear

**Specification Sheet** 

#### **PRODUCT DESCRIPTION:**

Whether working in the rugged oil and gas industry or spending your day working near electrical hazards, stay safe and comfortable in MCR Safety's FR Gear made with Max Comfort™ fabrics. The DC1 coveralls feature a comfortable 88% cotton 12% Nylon twill material that meets the NFPA 2112-2012 Standard for Flame Resistant Garments and NFPA 70E Standard for Electrical Safety in the Workplace. All MCR Safety's FR Garments are UL Certified and have a lifetime FR guarantee.

Available in Regular or Tall Sizes, Red, Gray, Navy, Royal Blue, & Tan

Sizes available: 34-66

### **FEATURES:**

- Available in Regular or Tall Sizes, Red, Gray, Navy, Royal Blue, & Tan
- NFPA 2112 UL Certified
- ASTM F1506 Electric Arc Protection
- NFPA 70E Hazard/Risk Cat HRC2 / ATPV 9.3 cal/cm<sup>2</sup>
- Max Comfort™ 7 oz. 88% cotton / 12% nylon FR twill fabric
- Sewn with Nomex® Flame Resistant thread
- Three needle reinforced stitching on major seams for durability
- Heavy duty two-way YKK® brass break-away zipper with Nomex® tape
- Protective storm flap with snap closure to cover front zipper
- Two chest pockets with mitered flaps, snap closure, plus pen pocket
- Two front hip pockets on coverall pants
- Side pass through with snap closure
- Two back patch pockets left pocket with flap and snap closure
- Bi-swing action back gussets for ease of movement and comfort
- Pen pocket on left arm
- Tool pocket on right leg





## DCIR FR Gear

**Specification Sheet** 

- Adjustable snap closure on cuffs of sleeves and legs
- All snaps have reinforcement strips

#### **APPLICATIONS:**

Oil and Gas Industry, Electronic Assembly, Fracking, Mining, Utilities

### **TECHNICAL DATA FOR: DC1R50**

SeriesMax ComfortCategoryFR Gear

Color Red

Material Flame Resistant, 88% Cotton /

12% Nylon - Max Comf

Material Weight7.0 oz.Components1 pc Coverall

Flame Resistant Flame Resistant

Front Closure YKK 2-Way Zipper & Triple

Snap

 NFPA 2112 Cert.
 Yes

 NFPA 70E Cert.
 Yes

 ASTM 1930 Cert.
 Yes

 ASTM F1506 Cert.
 Yes

 Hazard Risk Category
 HRC2

Item No:	Chest	Sleeve	Back Length	Waist	Inseam	Color	Case Weight
DC1R34	34	N/A	N/A	N/A	30	Red	25.700
DC1R36T	36	N/A	N/A	N/A	32	Red	25.700
DC1R36	36	N/A	N/A	N/A	30	Red	25.700
DC1R38	38	N/A	N/A	N/A	30	Red	25.700
DC1R38T	38	N/A	N/A	N/A	32	Red	25.700
DC1R40	40	N/A	N/A	N/A	30	Red	25.700
DC1R40T	40	N/A	N/A	N/A	32	Red	25.700
DC1R42	42	N/A	N/A	N/A	30	Red	25.700
DC1R42T	42	N/A	N/A	N/A	32	Red	25.700
DC1R44	44	N/A	N/A	N/A	30	Red	25.700
DC1R44T	44	N/A	N/A	N/A	32	Red	25.700
DC1R46T	46	N/A	N/A	N/A	32	Red	25.700
DC1R48T	48	N/A	N/A	N/A	32	Red	25.700
DC1R50	50	N/A	N/A	N/A	30	Red	25.700
DC1R50T	50	N/A	N/A	N/A	32	Red	25.700
DC1R52T	52	N/A	N/A	N/A	32	Red	25.700
DC1R52	52	N/A	N/A	N/A	30	Red	25.700
DC1R54	54	N/A	N/A	N/A	30	Red	25.700
DC1R54T	54	N/A	N/A	N/A	32	Red	25.700
DC1R56	56	N/A	N/A	N/A	30	Red	25.700

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrsafety.com



# DCIR FR Gear

**Specification Sheet** 

Item No:	Chest	Sleeve	Back Length	Waist	Inseam	Color	Case Weight
DC1R56T	56	N/A	N/A	N/A	32	Red	25.700
DC1R58T	58	N/A	N/A	N/A	32	Red	25.700
DC1R58	58	N/A	N/A	N/A	30	Red	26.600
DC1R60T	60	N/A	N/A	N/A	32	Red	25.700
DC1R60	60	N/A	N/A	N/A	30	Red	25.700
DC1R62T	62	N/A	N/A	N/A	32	Red	25.700
DC1R64T	64	N/A	N/A	N/A	32	Red	25.700
DC1R66T	66	N/A	N/A	N/A	32	Red	25.700