

DCIRG FR Gear Specification Sheet

PRODUCT DESCRIPTION:

Whether working in the rugged oil and gas industry or spending your day working near electrical hazards, stay safe and comfortable in MCR Safety's FR Gear made with Max Comfort[™] fabrics. The DC1 coverall features a comfortable 88% cotton 12% Nylon blend that meets the NFPA 2112-2012 Standard for Flame Resistant Garments and NFPA 70E Standard for Electrical Safety in the Workplace. All MCR Safety's FR Garments are UL Certified and have a lifetime FR guarantee.

Available in Regular or Tall Sizes, Red and Gray

Sizes available: 34-66

FEATURES:

- Available in Regular and Tall sizes, Red and Gray
- Silver reflective tape on legs, sleeves and shoulders
- NFPA 2112 UL Certified
- ASTM F1506 Electric Arc Protection
- NFPA 70E Hazard / Risk Cat HRC2 / 9.3 cal/cm²
- Max Comfort™ 7 oz. 88% cotton / 12% nylon FR twill fabric
- Sewn with Nomex® Flame Resistant thread
- Three needle reinforced stitching on major seams for durability
- Heavy duty two-way YKK® brass break-away zipper with Nomex® tape
- Protective storm flap with snap closure to cover front zipper
- Two chest pockets with mitered flaps, snap closure, plus pen pocket
- Two front hip pockets on coverall pants
- Side pass through with snap closure
- Two back patch pockets left pocket with flap and snap closure
- Bi-swing action back gussets for ease of movement and comfort
- Pen pocket on left arm
- Tool pocket on right leg
- Adjustable snap closure on cuffs of sleeves and legs
- All snaps have reinforcement strips

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrsafety.com ©2018 MCR Safety - All Rights Reserved





DCIRG FR Gear Specification Sheet

APPLICATIONS:

Oil and Gas Industry, Utilities, Electronic Assembly, Fracking, Mining

TECHNICAL DATA FOR: DC1RG50T

Series	Max Comfort	Front Closure	YKK 2-Way Zipper & Triple	
Category	FR Gear		Snap	
Color	Gray	NFPA 2112 Cert.	Yes	
Material	Flame Resistant, 88% Cotton /	NFPA 70E Cert.	Yes	
	12% Nylon - Max Comf	ASTM 1930 Cert.	Yes	
Material Weight	7.0 oz.	ASTM F1506 Cert.	Yes	
Components	1 pc Coverall	Hazard Risk Category	HRC2	
Flame Resistant	Flame Resistant			

Item No:	Chest	Sleeve	Back Length	Waist	Inseam	Color	Case Weight
DC1RG34	34	N/A	N/A	N/A	30	Gray	49.600
DC1RG36	36	N/A	N/A	N/A	30	Gray	25.630
DC1RG36T	36	N/A	N/A	N/A	32	Gray	25.700
DC1RG38	38	N/A	N/A	N/A	30	Gray	21.784
DC1RG38T	38	N/A	N/A	N/A	32	Gray	19.344
DC1RG40T	40	N/A	N/A	N/A	32	Gray	22.060
DC1RG40	40	N/A	N/A	N/A	30	Gray	22.030
DC1RG42	42	N/A	N/A	N/A	30	Gray	22.664
DC1RG42T	42	N/A	N/A	N/A	32	Gray	23.440
DC1RG44	44	N/A	N/A	N/A	30	Gray	23.224
DC1RG44T	44	N/A	N/A	N/A	32	Gray	23.560
DC1RG46T	46	N/A	N/A	N/A	32	Gray	24.840
DC1RG46	46	N/A	N/A	N/A	30	Gray	23.000
DC1RG48	48	N/A	N/A	N/A	30	Gray	24.304
DC1RG48T	48	N/A	N/A	N/A	32	Gray	23.952
DC1RG50	50	N/A	N/A	N/A	30	Gray	25.424
DC1RG50T	50	N/A	N/A	N/A	32	Gray	25.720
DC1RG52	52	N/A	N/A	N/A	30	Gray	25.824
DC1RG52T	52	N/A	N/A	N/A	32	Gray	25.210
DC1RG54T	54	N/A	N/A	N/A	32	Gray	24.160
DC1RG54	54	N/A	N/A	N/A	30	Gray	26.584
DC1RG56	56	N/A	N/A	N/A	30	Gray	45.640

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrsafety.com

©2018 MCR Safety - All Rights Reserved



DCIRG FR Gear

Specification Sheet

Item No:	Chest	Sleeve	Back Length	Waist	Inseam	Color	Case Weight
DC1RG56T	56	N/A	N/A	N/A	32	Gray	26.710
DC1RG58	58	N/A	N/A	N/A	30	Gray	25.384
DC1RG58T	58	N/A	N/A	N/A	32	Gray	29.520
DC1RG60T	60	N/A	N/A	N/A	32	Gray	25.700
DC1RG60	60	N/A	N/A	N/A	30	Gray	27.960
DC1RG62T	62	N/A	N/A	N/A	32	Gray	29.984
DC1RG64T	64	N/A	N/A	N/A	32	Gray	25.700
DC1RG66T	66	N/A	N/A	N/A	32	Gray	25.700