



**MCR
SAFETY**

**DC1RR
FR Gear**

Specification Sheet

PRODUCT DESCRIPTION:

Whether working in the rugged oil and gas industry or spending your day working near electrical hazards, stay safe and comfortable in MCR Safety's FR Gear made with Max Comfort™ fabrics. The DC1 coverall features a comfortable 88% cotton 12% Nylon blend that meets the NFPA 2112-2012 Standard for Flame Resistant Garments and NFPA 70E Standard for Electrical Safety in the Workplace. All MCR Safety's FR Garments are UL Certified and have a lifetime FR guarantee.

Available in Regular or Tall Sizes, Red and Gray

Sizes available: 34-66



FEATURES:

- **Available in Regular or Tall Sizes, Red and Gray**
- Silver reflective tape on legs, sleeves and shoulders
- NFPA 2112 UL Certified
- ASTM F1506 Electric Arc Protection
- NFPA 70E Hazard / Risk Cat HRC2 / 9.3 cal/cm²
- Max Comfort™ 7 oz. 88% cotton / 12% nylon FR twill fabric
- Sewn with Nomex® Flame Resistant thread
- Three needle reinforced stitching on major seams for durability
- Heavy duty two-way YKK® brass break-away zipper with Nomex® tape
- Protective storm flap with snap closure to cover front zipper
- Two chest pockets with mitered flaps, snap closure, plus pen pocket
- Two front hip pockets on coverall pants
- Side pass through with snap closure
- Two back patch pockets – left pocket with flap and snap closure
- Bi-swing action back gussets for ease of movement and comfort
- Pen pocket on left arm
- Tool pocket on right leg
- Adjustable snap closure on cuffs of sleeves and legs
- All snaps have reinforcement strips

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2018 MCR Safety - All Rights Reserved



MCR
SAFETY

DC1RR FR Gear

Specification Sheet

APPLICATIONS:

Oil and Gas Industry, Utilities, Electronic Assembly, Fracking,
Mining

TECHNICAL DATA FOR: DC1RR54T

Series	Max Comfort	Front Closure	YKK 2-Way Zipper & Triple Snap
Category	FR Gear	NFPA 2112 Cert.	Yes
Color	Red	NFPA 70E Cert.	Yes
Material	Flame Resistant, 88% Cotton / 12% Nylon - Max Comf	ASTM 1930 Cert.	Yes
Material Weight	7.0 oz.	ASTM F1506 Cert.	Yes
Components	1 pc Coverall	Hazard Risk Category	HRC2
Flame Resistant	Flame Resistant		

Item No:	Chest	Sleeve	Back Length	Waist	Inseam	Color	Case Weight
DC1RR34	34	N/A	N/A	N/A	30	Red	25.700
DC1RR36T	36	N/A	N/A	N/A	32	Red	25.700
DC1RR36	36	N/A	N/A	N/A	30	Red	21.448
DC1RR38	38	N/A	N/A	N/A	30	Red	22.192
DC1RR38T	38	N/A	N/A	N/A	32	Red	22.624
DC1RR40	40	N/A	N/A	N/A	30	Red	22.984
DC1RR40T	40	N/A	N/A	N/A	32	Red	25.700
DC1RR42	42	N/A	N/A	N/A	30	Red	23.064
DC1RR42T	42	N/A	N/A	N/A	32	Red	23.848
DC1RR44T	44	N/A	N/A	N/A	32	Red	24.160
DC1RR44	44	N/A	N/A	N/A	30	Red	23.792
DC1RR46T	46	N/A	N/A	N/A	32	Red	24.976
DC1RR46	46	N/A	N/A	N/A	30	Red	24.392
DC1RR48	48	N/A	N/A	N/A	30	Red	25.008
DC1RR48T	48	N/A	N/A	N/A	32	Red	25.592
DC1RR50T	50	N/A	N/A	N/A	32	Red	25.700
DC1RR50	50	N/A	N/A	N/A	30	Red	25.712
DC1RR52T	52	N/A	N/A	N/A	32	Red	26.968
DC1RR52	52	N/A	N/A	N/A	30	Red	26.000
DC1RR54T	54	N/A	N/A	N/A	32	Red	25.700
DC1RR54	54	N/A	N/A	N/A	30	Red	26.560
DC1RR56T	56	N/A	N/A	N/A	32	Red	25.700

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2018 MCR Safety - All Rights Reserved



MCR
SAFETY

DC1RR FR Gear

Specification Sheet

Item No:	Chest	Sleeve	Back Length	Waist	Inseam	Color	Case Weight
DC1RR56	56	N/A	N/A	N/A	30	Red	26.700
DC1RR58T	58	N/A	N/A	N/A	32	Red	25.700
DC1RR58	58	N/A	N/A	N/A	30	Red	27.850
DC1RR60	60	N/A	N/A	N/A	30	Red	28.620
DC1RR60T	60	N/A	N/A	N/A	32	Red	25.100
DC1RR62T	62	N/A	N/A	N/A	32	Red	25.700
DC1RR64T	64	N/A	N/A	N/A	32	Red	25.800
DC1RR66T	66	N/A	N/A	N/A	32	Red	25.700

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2018 MCR Safety - All Rights Reserved