



**MCR
SAFETY**

**SIG
FR Gear
Specification Sheet**

PRODUCT DESCRIPTION:

Whether working in the rugged oil and gas industry or spending your day working near electrical hazards, stay safe and comfortable in MCR Safety's FR Gear made with Max Comfort™ fabrics. The S1 work shirt features a comfortable 88% cotton 12% Nylon blend that meets the NFPA 2112-2012 Standard for Flame Resistant Garments and NFPA 70E Standard for Electrical Safety in the Workplace. All MCR Safety's FR Garments are UL Certified and have a lifetime FR guarantee.

FEATURES:

Available in Regular and Tall Sizes, Navy Blue, Gray and Tan

- NFPA 2112 UL Certified
- ASTM F1506 Electric Arc Protection
- ATPV ASTM 1959 9.5 cal/cm²
- NFPA 70E Hazard/Risk Cat HRC2
- Max Comfort™ 6.5 oz. 88% cotton/12% nylon FR sateen fabric
- Sewn with Nomex® Flame Resistant thread
- Two needle top stitching on major seams
- Extended back tail to stay tucked in



APPLICATIONS:

Oil and Gas Industry, Utilities, Electronic Assembly, Fracking, Mining

TECHNICAL DATA FOR: S1GMT

Series	Max Comfort	Front Closure	Button
Category	FR Gear	NFPA 2112 Cert.	Yes
Color	Gray	NFPA 70E Cert.	Yes
Size	Medium	ASTM 1930 Cert.	Yes
Material	Flame Resistant, 88% Cotton / 12% Nylon - Max Comf	ASTM F1506 Cert.	Yes
Material Weight	6.5 oz.	Hazard Risk Category	HRC2
Components	Shirt		

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2018 MCR Safety - All Rights Reserved



MCR
SAFETY

SIG
FR Gear
Specification Sheet

Flame Resistant

Flame Resistant

Item No:	Chest	Sleeve	Back Length	Waist	Inseam	Color	Case Weight
S1GMT	38-40	32.5-34	38.38	N/A	N/A	Gray	30.900
S1GM	38-40	32.5-33	35.75	N/A	N/A	Gray	30.900
S1GLT	42-44	33.5-35	38.25	N/A	N/A	Gray	30.900
S1GL	42-44	33.5-34	36.25	N/A	N/A	Gray	30.900
S1GXL	46-48	34.5-35	37	N/A	N/A	Gray	49.896
S1GXLT	46-48	34.5-35	38.25	N/A	N/A	Gray	30.900
S1GX2T	50-52	35.5-36	39.63	N/A	N/A	Gray	30.900
S1GX2	50-52	35.5-36	37.63	N/A	N/A	Gray	52.452
S1GX3	54-56	36.5-37	38	N/A	N/A	Gray	55.440
S1GX3T	54-56	36.5-37	40	N/A	N/A	Gray	30.900
S1GX4	58-60	37.5-38	38.38	N/A	N/A	Gray	30.900
S1GX4T	58-60	37.5-38	40.38	N/A	N/A	Gray	30.900

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2018 MCR Safety - All Rights Reserved