



**MCR
SAFETY**

**SIG
FR Gear
Specification Sheet**

PRODUCT DESCRIPTION:

Whether working in the rugged oil and gas industry or spending your day working near electrical hazards, stay safe and comfortable in MCR Safety's FR Gear made with Max Comfort™ fabrics. The S1 work shirt features a comfortable 88% cotton 12% Nylon blend that meets the NFPA 2112-2012 Standard for Flame Resistant Garments and NFPA 70E Standard for Electrical Safety in the Workplace. All MCR Safety's FR Garments are UL Certified and have a lifetime FR guarantee.

FEATURES:

Available in Regular and Tall Sizes, Navy Blue, Gray and Tan

- NFPA 2112 UL Certified
- ASTM F1506 Electric Arc Protection
- ATPV ASTM 1959 9.5 cal/cm²
- NFPA 70E Hazard/Risk Cat HRC2
- Max Comfort™ 6.5 oz. 88% cotton/12% nylon FR sateen fabric
- Sewn with Nomex® Flame Resistant thread
- Two needle top stitching on major seams
- Extended back tail to stay tucked in



APPLICATIONS:

Oil and Gas Industry, Utilities, Electronic Assembly, Fracking, Mining

TECHNICAL DATA FOR: S1GX3T

| | | | |
|------------------------|---|-----------------------------|--------|
| Series | Max Comfort | Front Closure | Button |
| Category | FR Gear | NFPA 2112 Cert. | Yes |
| Color | Gray | NFPA 70E Cert. | Yes |
| Size | X3 | ASTM 1930 Cert. | Yes |
| Material | Flame Resistant, 88% Cotton / 12% Nylon - Max Comf | ASTM F1506 Cert. | Yes |
| Material Weight | 6.5 oz. | Hazard Risk Category | HRC2 |
| Components | Shirt | | |

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2018 MCR Safety - All Rights Reserved



MCR
SAFETY

SIG
FR Gear
Specification Sheet

Flame Resistant

Flame Resistant

| Item No: | Chest | Sleeve | Back Length | Waist | Inseam | Color | Case Weight |
|----------|-------|---------|-------------|-------|--------|-------|-------------|
| S1GMT | 38-40 | 32.5-34 | 38.38 | N/A | N/A | Gray | 30.900 |
| S1GM | 38-40 | 32.5-33 | 35.75 | N/A | N/A | Gray | 30.900 |
| S1GLT | 42-44 | 33.5-35 | 38.25 | N/A | N/A | Gray | 30.900 |
| S1GL | 42-44 | 33.5-34 | 36.25 | N/A | N/A | Gray | 30.900 |
| S1GXL | 46-48 | 34.5-35 | 37 | N/A | N/A | Gray | 49.896 |
| S1GXLT | 46-48 | 34.5-35 | 38.25 | N/A | N/A | Gray | 30.900 |
| S1GX2T | 50-52 | 35.5-36 | 39.63 | N/A | N/A | Gray | 30.900 |
| S1GX2 | 50-52 | 35.5-36 | 37.63 | N/A | N/A | Gray | 52.452 |
| S1GX3 | 54-56 | 36.5-37 | 38 | N/A | N/A | Gray | 55.440 |
| S1GX3T | 54-56 | 36.5-37 | 40 | N/A | N/A | Gray | 30.900 |
| S1GX4 | 58-60 | 37.5-38 | 38.38 | N/A | N/A | Gray | 30.900 |
| S1GX4T | 58-60 | 37.5-38 | 40.38 | N/A | N/A | Gray | 30.900 |

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2018 MCR Safety - All Rights Reserved