



**MCR  
SAFETY**

# SIT FR Gear

## Specification Sheet

### PRODUCT DESCRIPTION:

Whether working in the rugged oil and gas industry or spending your day working near electrical hazards, stay safe and comfortable in MCR Safety's FR Gear made with Max Comfort™ fabrics. The S1 work shirt features a comfortable 88% cotton 12% Nylon blend that meets the NFPA 2112-2012 Standard for Flame Resistant Garments and NFPA 70E Standard for Electrical Safety in the Workplace. All MCR Safety's FR Garments are UL Certified and have a lifetime FR guarantee. **Available in Regular and Tall Sizes, Navy Blue, Gray, and Tan.**

### FEATURES:

**Available in Regular and Tall Sizes, Navy Blue, Gray and Tan**

- NFPA 2112 UL Certified
- ASTM F1506 Electric Arc Protection
- ATPV ASTM 1959 9.5 cal/cm<sup>2</sup>
- NFPA 70E Hazard/Risk Cat HRC2
- Max Comfort™ 6.5 oz. 88% cotton/12% nylon FR sateen fabric
- Sewn with Nomex® Flame Resistant thread
- Two needle top stitching on major seams
- Extended back tail to stay tucked in



### APPLICATIONS:

Oil and Gas Industry, Utilities, Electronic Assembly, Fracking, Mining

### TECHNICAL DATA FOR: S1TLT

<b>Series</b>	Max Comfort	<b>Front Closure</b>	Button
<b>Category</b>	FR Gear	<b>NFPA 2112 Cert.</b>	Yes
<b>Color</b>	Tan	<b>NFPA 70E Cert.</b>	Yes
<b>Size</b>	Large	<b>ASTM 1930 Cert.</b>	Yes
<b>Material</b>	Flame Resistant, 88% Cotton / 12% Nylon - Max Comf	<b>ASTM F1506 Cert.</b>	Yes
		<b>Hazard Risk Category</b>	HRC2

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: [www.mcrcsafety.com](http://www.mcrcsafety.com)

©2018 MCR Safety - All Rights Reserved



**MCR**  
SAFETY

**SIT**  
**FR Gear**  
Specification Sheet

**Material Weight** 6.5 oz.  
**Components** Shirt  
**Flame Resistant** Flame Resistant

Item No:	Chest	Sleeve	Back Length	Waist	Inseam	Color	Case Weight
S1TMT	38-40	32.5-33	N/A	N/A	N/A	Tan	30.900
S1TM	38-40	32.5-33	35.75	N/A	N/A	Tan	46.044
S1TLT	42-44	33.5-34	38.25	N/A	N/A	Tan	30.900
S1TL	42-44	33.5-34	36.25	N/A	N/A	Tan	48.024
S1TXLT	46-48	34.5-35	38.25	N/A	N/A	Tan	30.900
S1TXL	46-48	34.5-35	37	N/A	N/A	Tan	48.708
S1TX2	50-52	35.5-36	37.63	N/A	N/A	Tan	52.812
S1TX2T	50-52	35.5-36	39.63	N/A	N/A	Tan	30.900
S1TX3T	54-56	36.5-37	40	N/A	N/A	Tan	30.900
S1TX3	54-56	36.5-37	38	N/A	N/A	Tan	30.900
S1TX4	58-60	37.5-38	38.38	N/A	N/A	Tan	30.900
S1TX4T	58-60	37.5-38	40.38	N/A	N/A	Tan	30.900