

PRO-LINE® Fine Line, Microline PAINT MARKERS, PRO-MAX™ PAINT MARKER – Black, White

Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 29/07/2015

Revision date:

Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Article
 Product name : PRO-LINE® Fine Line, Microline PAINT MARKERS, PRO-MAX™ PAINT MARKER – Black, White
 Synonyms : PRO-LINE® Fine Line PAINT MARKER Black, White
 PRO-LINE® Microline PAINT MARKER Black, White
 PRO-MAX™ PAINT MARKER Black, White

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Marking.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

LA-CO Industries Europe S.A.S.
 Parc Industriel de la Plaine de
 l'Ain - Allée des Combes.
 01150.BLYES.France.
 Phone: +33 (0)4 74 46 23 23
 Fax: +33 (0)4 74 46 23 29
 E-mail: info@eu.laco.com
 Web: http://www.markal.com



1.4. Emergency telephone number

Emergency number : 24-hour emergency: CHEMTREC- U.S. : 1-800-424-9300 International: +1-703-527-3887

EU Member State	Officieel adviesorgaan	Adres	Noodnummer
AUSTRIA	Vergiftungsinformationszentrale (Poisons Information Centre)	Allgemeines Krankenhaus Waehringer Geurtel 18-20 1090 Wien	+43 1 406 43 43
BELARUS	The Belarus Republican Poisons Centre	Kizhevatova str. 58 220115 Minsk	+375 (0)17 201 9158
BELGIUM	Centre Anti-Poisons/Antigifocentrum c/o Hôpital Central de la Base - Reine Astrid	Rue Bruyn 1 B -1120 Bruxelles/Brussel	+32 70 245 245
BULGARIA	Национален токсикологичен информационен център National Clinical Toxicology Centre, Emergency Medical Institute "Pirogov"	21 Toteben Boulevard 1606 SOFIA	+359 2 9154 409
CROATIA	Poisons Control Centre Institute of Medical Research & Occupational Health	Ksaverska Cesta 2 P.O. Box 291 HR-10000 Zagreb	+385 1 234 8342
CZECH REPUBLIC	Toxikologické informační středisko Clinic For Occupational Medicine, 1st Medical Faculty, Charles University	Na Bojišti 1 120 00 Praha 2	+42 2 2491 9293 +42 2 2491 5402
DENMARK	Giftlinjen Bispebjerg Hospital	Bispebjerg Bakke 23, 60, 1 DK-2400 København NV	+45 82 12 12 12 +45 35 31 55 55
ESTONIA	Mürgistusteabekeskus	Gonsiori 29 15027 Tallinn	+372 626 93 90
FINLAND	Myrkytystietokeskus	P.O.B 340 (Haartmaninkatu 4) HUS SF - 00029 Helsinki	+358 9 471 977
FRANCE	ORFILA		+33 1 45 42 59 59
GERMANY	Berliner Betrieb für Zentrale Gesundheitliche Aufgaben	Oranienburger Strasse 285 13437 Berlin	+49 30 19240
GERMANY	Informations und Beratungszentrum für Vergiftungsfälle	Kirrberger Straße, Gebäude 9 D-66421 Homburg/Saar	+49 6841 19240
GERMANY	Beratungstelle bei Vergiftungen, Klinische Toxikologie und Beratungsstelle bei Vergiftungen	Langenbeckstrasse 1 55131 Mainz	+49 6131 19240
GREECE	Poisons Information Centre	11527 Athens	+30 10 779 3777

PRO-LINE® Fine Line, Microline PAINT MARKERS, PRO-MAX™ PAINT MARKER – Black, White

Safety Data Sheet

according to Regulation (EU) 2015/830

HUNGARY	Országos Kémiai Biztonsági Intézet (National Institute of Chemical Safety) Egészségügyi Toxikológiai Tájékoztató Szolgálat (Health Toxicological Information Service)	1437 Budapest PO Box 839 1097 Budapest, Nagyvárad tér 2	+36 80 20 11 99
ICELAND	Eitrunarmiðstöðin	Eitrunarmiðstöðin 108 Reykjavik	+354 543 22 22
IRELAND	National Poisons Information Centre	Beaumont Hospital PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2166
LATVIA	Valsts Toksikoloģijas centra Saindēšanās un zāļu informācijas centrs	2 Hipocrate Street LV 1038 Riga	+371 67 04 24 73
LITHUANIA	Apsinuodijimų kontrolės ir informacijos biuras	Siitnamiu 29 2043 Vilnius	+370 5 236 20 52/+370 687 53 378
MALTA	Medicines & Poisons Info Office	Mater Dei Hospital, Msida MSD 2090 Malta	25450000
NETHERLANDS	Nationaal Vergiftigingen Informatie Centrum National Institute for Public Health and the Environment, NB this service is only available to health professionals	Huispostnummer B.00.118, PO Box 85500 3508 GA Utrecht	+31 30 274 88 88
PORTUGAL	Centro de Informação Antivenenos Instituto Nacional de Emergência Médica (INEM)	Rua Almirante Barroso, 36 1000-013 Lisboa	808 250 143 (for use only in Portugal), +351 21 330 3284
ROMANIA	Biroul pentru Regulamentul Sanitar International si Informare Toxicologica	Str. Dr. Leonte Anastasievici Nr.1-3, Sector 5 50463 Bucuresti	+40 21 318 36 06
SLOVAKIA	Národné toxikologické informačné centrum University Hospital Bratislava	Limbová 5 833 05 Bratislava	+421 2 54 77 4 166
SPAIN	Servicio de Información Toxicológica Instituto Nacional de Toxicología, Departamento de Madrid	Calle Luis Cabrera 9 E-28002 Madrid	+34 91 562 04 20
SWEDEN	Giftinformationscentralen Swedish Poisons Information Centre, Karolinska Hospital	Box 60 500 SE-171 76 Stockholm	+46 8 33 12 31 (International) 112 (National)
SWITZERLAND	Centre Suisse d'Information Toxicologique	Freiestrasse 16 Postfach CH-8028 Zurich	+41 44 251 51 51 (International) 145 (National)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH210 - Safety data sheet available on request

2.3. Other hazards

PBT: not yet assessed

vPvB: not yet assessed

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
1-Methoxy-2-propanol	(CAS No) 107-98-2 (EC no) 203-539-1 (EC index no) 603-064-00-3	10 - 50	Flam. Liq. 3, H226 STOT SE 3, H336
ethanol	(CAS No) 64-17-5 (EC no) 200-578-6 (EC index no) 603-002-00-5	25 - 50	Flam. Liq. 2, H225

Full text of R- and H-statements: see section 16

PRO-LINE® Fine Line, Microline PAINT MARKERS, PRO-MAX™ PAINT MARKER – Black, White

Safety Data Sheet

according to Regulation (EU) 2015/830

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.
- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
- First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.
- First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water.
- First-aid measures after ingestion : Do NOT induce vomiting. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause drowsiness or dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Carbon dioxide. Dry chemical. Inert gas. Foam. Water spray. Water fog.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Highly flammable liquid and vapour.
- Explosion hazard : May form flammable/explosive vapour-air mixture.
- Hazardous decomposition products in case of fire : Carbon oxides (CO, CO₂). Hydrocarbon.

5.3. Advice for firefighters

- Firefighting instructions : Exercise caution when fighting any chemical fire. Do not allow run-off from fire fighting to enter drains or water courses. Eliminate all ignition sources if safe to do so.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Use self-contained breathing apparatus. EN469.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Avoid all eye and skin contact and do not breathe vapour and mist. Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

6.1.1. For non-emergency personnel

- Protective equipment : Chemical goggles or safety glasses. Wear suitable gloves.
- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Chemical goggles or safety glasses. Wear suitable gloves.
- Emergency procedures : Stop leak if safe to do so. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Eliminate all ignition sources. Stop the flow of material, if this is without risk.
- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Take up in non-combustible absorbent material and shove into container for disposal.

6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling. Section 8: personal protective equipment.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.
- Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapour and mist. No open flames. No smoking. Use only non-sparking tools. Use only outdoors or in a well-ventilated area.
- Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

PRO-LINE® Fine Line, Microline PAINT MARKERS, PRO-MAX™ PAINT MARKER – Black, White

Safety Data Sheet

according to Regulation (EU) 2015/830

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Use only non-sparking tools. Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/... equipment.
Storage conditions	: Keep container tightly closed. Keep away from open flames, hot surfaces and sources of ignition. Keep in fireproof place.
Incompatible products	: Strong oxidizers.
Incompatible materials	: Heat sources.
Heat and ignition sources	: Keep away from heat, sparks and flame.
Prohibitions on mixed storage	: Keep away from incompatible materials.
Storage area	: Store in dry, cool, well-ventilated area.

7.3. Specific end use(s)

Marking.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

1-Methoxy-2-propanol (107-98-2)		
EU	IOELV TWA (mg/m ³)	375 mg/m ³
EU	IOELV TWA (ppm)	100 ppm
EU	IOELV STEL (mg/m ³)	568 mg/m ³
EU	IOELV STEL (ppm)	150 ppm
EU	Notes	Skin
Austria	MAK (mg/m ³)	187 mg/m ³
Austria	MAK (ppm)	50 ppm
Austria	MAK Short time value (mg/m ³)	187 mg/m ³
Austria	MAK Short time value (ppm)	50 ppm
Austria	Remark (AT)	(gemessen als Momentanwert), (H)
Belgium	Limit value (mg/m ³)	375 mg/m ³
Belgium	Limit value (ppm)	100 ppm
Belgium	Short time value (mg/m ³)	568 mg/m ³
Belgium	Short time value (ppm)	150 ppm
Belgium	Remark (BE)	D
Czech Republic	Expoziční limity (PEL) (mg/m ³)	270 mg/m ³
Czech Republic	Expoziční limity (PEL) (ppm)	73.17 ppm
Czech Republic	Expoziční limity (NPK-P) (mg/m ³)	550 mg/m ³
Czech Republic	Expoziční limity (NPK-P) (ppm)	149.05 ppm
Czech Republic	Remark (CZ)	D
Denmark	Grænseværdie (langvarig) (mg/m ³)	185 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	50 ppm
Denmark	Grænseværdie (kortvarig) (mg/m ³)	370 mg/m ³
Denmark	Grænseværdie (kortvarig) (ppm)	100 ppm
Finland	HTP-arvo (8h) (mg/m ³)	370 mg/m ³
Finland	HTP-arvo (8h) (ppm)	100 ppm
Finland	HTP-arvo (15 min)	560 mg/m ³
Finland	HTP-arvo (15 min) (ppm)	150 ppm
Finland	Huomautus (FI)	iho
France	VME (mg/m ³)	188 mg/m ³
France	VME (ppm)	50 ppm
France	VLE (mg/m ³)	375 mg/m ³
France	VLE (ppm)	100 ppm
France	Note (FR)	Peau
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	370 mg/m ³
Germany	TRGS 900 Occupational exposure limit value (ppm)	100 ppm
Germany	TRGS 900 Limitation of exposure peaks (mg/m ³)	740 mg/m ³
Germany	TRGS 900 Limitation of exposure peaks (ppm)	200 ppm

PRO-LINE® Fine Line, Microline PAINT MARKERS, PRO-MAX™ PAINT MARKER – Black, White

Safety Data Sheet

according to Regulation (EU) 2015/830

1-Methoxy-2-propanol (107-98-2)		
Hungary	AK-érték	375 mg/m ³
Hungary	CK-érték	568 mg/m ³
Ireland	OEL (8 hours ref) (mg/m ³)	375 mg/m ³
Ireland	OEL (8 hours ref) (ppm)	100 ppm
Ireland	OEL (15 min ref) (mg/m ³)	568 mg/m ³
Ireland	OEL (15 min ref) (ppm)	150 ppm
Lithuania	IPRV (mg/m ³)	190 mg/m ³
Lithuania	IPRV (ppm)	50 ppm
Lithuania	TPRV (mg/m ³)	300 mg/m ³
Lithuania	TPRV (ppm)	75 ppm
Netherlands	Grenswaarde TGG 8H (mg/m ³)	375 mg/m ³
Netherlands	Grenswaarde TGG 15MIN (mg/m ³)	563 mg/m ³
Netherlands	Remark (MAC)	(H)
Poland	NDS (mg/m ³)	180 mg/m ³
Poland	NDSch (mg/m ³)	360 mg/m ³
Slovakia	NPHV (priemerná) (mg/m ³)	375 mg/m ³
Slovakia	NPHV (priemerná) (ppm)	100 ppm
Slovakia	Upozornenie (SK)	(K)
Spain	VLA-ED (mg/m ³)	375 mg/m ³
Spain	VLA-ED (ppm)	100 ppm
Spain	VLA-EC (mg/m ³)	568 mg/m ³
Spain	VLA-EC (ppm)	150 ppm
Spain	Notes	via dérmica, VLI
Sweden	nivågränsvärde (NVG) (mg/m ³)	190 mg/m ³
Sweden	nivågränsvärde (NVG) (ppm)	50 ppm
Sweden	kortidsvärde (KTV) (mg/m ³)	300 mg/m ³
Sweden	kortidsvärde (KTV) (ppm)	75 ppm
Sweden	Anmärkning (SE)	H
United Kingdom	WEL TWA (mg/m ³)	375 mg/m ³
United Kingdom	WEL TWA (ppm)	100 ppm
United Kingdom	WEL STEL (mg/m ³)	560 mg/m ³
United Kingdom	WEL STEL (ppm)	150 ppm
Norway	Grenseverdier (AN) (mg/m ³)	180 mg/m ³
Norway	Grenseverdier (AN) (ppm)	50 ppm
Norway	Merknader (NO)	H
Switzerland	VME (mg/m ³)	360 mg/m ³
Switzerland	VME (ppm)	100 ppm 20 ppm (urina; fine dell'esposizione / del turno)
Switzerland	VLE (mg/m ³)	720 mg/m ³
Switzerland	VLE (ppm)	200 ppm
ethanol (64-17-5)		
Denmark	Grænseværdie (kortvarig) (mg/m ³)	3800 mg/m ³
Denmark	Grænseværdie (kortvarig) (ppm)	2000 ppm
Slovakia	NPHV (priemerná) (mg/m ³)	960 mg/m ³
Slovakia	NPHV (priemerná) (ppm)	500 ppm
Spain	VLA-ED (mg/m ³)	1910 mg/m ³
Spain	VLA-ED (ppm)	1000 ppm
Spain	Notes	s,

8.2. Exposure controls

Appropriate engineering controls

: Provide local exhaust ventilation of closed transfer systems to minimize exposures.

PRO-LINE® Fine Line, Microline PAINT MARKERS, PRO-MAX™ PAINT MARKER – Black, White

Safety Data Sheet

according to Regulation (EU) 2015/830

Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: None under normal use. It is a good industrial hygiene practice to minimize skin contact. Wear suitable gloves. rubber. EN 374.
Eye protection	: Eye protection should only be necessary where liquid could be splashed or sprayed. EN 166.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. Use an approved respirator equipped with oil/mist cartridges. EN 12083.
Other information	: Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Solid marker containing liquid colored paint.
Colour	: Variable.
Odour	: Ether.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 78 °C
Flash point	: 13 °C
Auto-ignition temperature	: 287 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapour
Vapour pressure	: 12 mbar @ 20 °C
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1.1 g/cm ³ @ 20 °C
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 25 mPa.s
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content	: 53.4 %
-------------	----------

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Highly flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Open flame. Direct sunlight.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
----------------	------------------

PRO-LINE® Fine Line, Microline PAINT MARKERS, PRO-MAX™ PAINT MARKER – Black, White

Safety Data Sheet

according to Regulation (EU) 2015/830

1-Methoxy-2-propanol (107-98-2)	
LD50 oral rat	4016 mg/kg bodyweight
LD50 dermal rat	> 2000 mg/kg bodyweight
LC50 inhalation rat (ppm)	> 7000 ppm 6 hr
ATE CLP (oral)	4016.000 mg/kg bodyweight

ethanol (64-17-5)	
LD50 oral rat	10470 mg/kg
LD50 dermal rabbit	> 20000 mg/kg
LC50 inhalation rat (mg/l)	133.8 mg/l/4h
ATE CLP (oral)	10470.000 mg/kg bodyweight
ATE CLP (vapours)	133.800 mg/l/4h
ATE CLP (dust,mist)	133.800 mg/l/4h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

1-Methoxy-2-propanol (107-98-2)	
LC50 fish 1	20800 mg/l
EC50 Daphnia 1	23300 mg/l
ErC50 (algae)	> 1000 mg/l

ethanol (64-17-5)	
LC50 fish 1	14200 mg/l
EC50 Daphnia 1	5012 mg/l

12.2. Persistence and degradability

1-Methoxy-2-propanol (107-98-2)	
Persistence and degradability	Readily biodegradable.
Biodegradation	96 % 28 d

ethanol (64-17-5)	
Biodegradation	> 96 % 28 d

12.3. Bioaccumulative potential

1-Methoxy-2-propanol (107-98-2)	
Bioaccumulative potential	Not expected to bioaccumulate.

ethanol (64-17-5)	
Bioaccumulative potential	Not expected to bioaccumulate.

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

PRO-LINE® Fine Line, Microline PAINT MARKERS, PRO-MAX™ PAINT MARKER – Black, White	
PBT: not yet assessed	
vPvB: not yet assessed	

12.6. Other adverse effects

No additional information available

PRO-LINE® Fine Line, Microline PAINT MARKERS, PRO-MAX™ PAINT MARKER – Black, White

Safety Data Sheet

according to Regulation (EU) 2015/830

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations	: Do not dispose of waste into sewer.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Additional information	: Handle empty containers with care because residual vapours are flammable.
Ecology - waste materials	: Avoid release to the environment.
European List of Waste (LoW) code	: For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used. 08 00 00 - WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS 08 01 00 - wastes from MFSU and removal of paint and varnish 20 01 27* - paint, inks, adhesives and resins containing dangerous substances 08 01 11* - waste paint and varnish containing organic solvents or other dangerous substances
H code	: H4 - 'Irritant': non-corrosive substances and preparations which, through immediate, prolonged or repeated contact with the skin or mucous membrane, can cause inflammation. H3-A - 'Highly flammable' : — liquid substances and preparations having a flash point below 21 °C (including extremely flammable liquids), or — substances and preparations which may become hot and finally catch fire in contact with air at ambient temperature without any application of energy, or — solid substances and preparations which may readily catch fire after brief contact with a source of ignition and which continue to burn or to be consumed after removal of the source of ignition, or — gaseous substances and preparations which are flammable in air at normal pressure, or — substances and preparations which, in contact with water or damp air, evolve highly flammable gases in dangerous quantities.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR)	: 1263
UN-No. (IATA)	: 1263
UN-No. (IMDG)	: 1263
UN-No. (ADN)	: 1263

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: Paint
Proper Shipping Name (IATA)	: Paint
Proper Shipping Name (IMDG)	: PAINT
Proper Shipping Name (ADN)	: PAINT
Transport document description (ADR)	: UN 1263 PAINT, 3, II, (D/E)

14.3. Transport hazard class(es)

Class (ADR)	: 3
Classification code (ADR)	: F1
Class (IATA)	: 3
Class (IMDG)	: 3
Class (ADN)	: 3
Classification code (ADN)	: F1

14.4. Packing group

Packing group (ADR)	: II
Packing group (IATA)	: II
Packing group (IMDG)	: II
Packing group (ADN)	: II

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

14.6.1. Overland transport

Hazard identification number (Kemler No.)	: 33
Classification code (ADR)	: F1

PRO-LINE® Fine Line, Microline PAINT MARKERS, PRO-MAX™ PAINT MARKER – Black, White

Safety Data Sheet

according to Regulation (EU) 2015/830

Orange plates



Tunnel restriction code (ADR)

: D/E

EAC code

: •3YE

14.6.2. Transport by sea

EmS-No. (Fire)

: F-E

EmS-No. (Spillage)

: S-E

Stowage category (IMDG)

: B

14.6.3. Inland waterway transport

Carriage prohibited (ADN)

: No

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no substance on the REACH candidate list

VOC content : 53.4 %

15.1.2. National regulations

Germany

Water hazard class (WGK)

: 1 - low hazard to waters

WGK remark

: Classification based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

according to Regulation (EU) 2015/830

Indication of changes:

Original Document.

Abbreviations and acronyms:

	ATE: Acute Toxicity Estimate
	CAS (Chemical Abstracts Service) number
	CLP: Classification, Labelling, Packaging.
	EC50: Environmental Concentration associated with a response by 50% of the test population.
	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
	LD50: Lethal Dose for 50% of the test population
	OSHA: Occupational Safety & Health Administration
	PBT: Persistent, Bioaccumulative, Toxic
	TWA: Time Weight Average
	TSCA: Toxic Substances Control Act

PRO-LINE® Fine Line, Microline PAINT MARKERS, PRO-MAX™ PAINT MARKER – Black, White

Safety Data Sheet

according to Regulation (EU) 2015/830

Data sources : ESIS (European chemical Substances Information System; accessed at: <http://esis.jrc.ec.europa.eu/index.php?PGM=cla>.
European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>.
Kristen Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition.
National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition.
REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of R-, H- and EUH-statements:

Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H336	May cause drowsiness or dizziness
EUH210	Safety data sheet available on request
R10	Flammable
R11	Highly flammable
R67	Vapours may cause drowsiness and dizziness
F	Highly flammable

LA-CO EU CLP SDS

SDS Prepared by: The Redstone Group, LLC
6077 Frantz Rd.
Suite 206
Dublin, OH USA 43016
T 614-923-7472
www.redstonegrp.com

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product