

SAFETY DATA SHEET

1. Identification

Product identifier CoolPAK™ L3375
Other means of identification None.
Recommended use Metal Working Fluids.
Recommended restrictions Applicable for industrial settings only. No other uses are advised.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company Name Master Fluid Solutions
Address 501 West Boundary Street
 Perrysburg, Ohio 43551-1200
 United States
Telephone 419-874-7902
Website www.masterfluidsolutions.com
E-mail info@masterchemical.com
Emergency phone number CHEMTREC 1-800-424-9300

2. Hazard(s) identification

Physical hazards Not classified.
Health hazards Aspiration hazard Category 1
Environmental hazards Not classified.
OSHA defined hazards Not classified.

Label elements



Signal word Danger
Hazard statement May be fatal if swallowed and enters airways.
Precautionary statement
Prevention Observe good industrial hygiene practices.
Response IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.
Storage Store locked up.
Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC) None known.
Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
SEVERELY HYDROTREATED PETROLEUM OIL		64742-55-8	50 - < 60
DISTILLATES, HYDROTREATED HEAVY PARAFFINIC		64742-54-7	30 - < 40
Other components below reportable levels			10 - < 20

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air.
Skin contact	Wash affected area with mild soap and water.
Eye contact	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses.
Ingestion	In the unlikely event of swallowing contact a physician or poison control center. Do not induce vomiting.
Most important symptoms/effects, acute and delayed	None known.
General information	Get medical attention, if needed.

5. Fire-fighting measures

Suitable extinguishing media	Dry chemical, CO2, water spray or alcohol resistant foam. Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media	Do not use a solid water stream as it may scatter and spread fire.
Specific hazards arising from the chemical	No unusual fire or explosion hazards noted.
Special protective equipment and precautions for firefighters	Wear suitable protective equipment. Use standard firefighting procedures and consider the hazards of other involved materials.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Use personal protective equipment as required. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Soak up with inert absorbent material. Clean up in accordance with all applicable regulations.

7. Handling and storage

Precautions for safe handling	Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Wash thoroughly after handling. Do not taste or swallow.
Conditions for safe storage, including any incompatibilities	The product is stable and non-reactive under normal conditions of use, storage and transport. Store in a dry place. Store in a closed container.

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
DISTILLATES, HYDROTREATED HEAVY PARAFFINIC (CAS 64742-54-7)	PEL	5 mg/m3	Mist.
SEVERELY HYDROTREATED PETROLEUM OIL (CAS 64742-55-8)	PEL	5 mg/m3	Mist.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
DISTILLATES, HYDROTREATED HEAVY PARAFFINIC (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.
SEVERELY HYDROTREATED PETROLEUM OIL (CAS 64742-55-8)	TWA	5 mg/m3	Inhalable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
DISTILLATES, HYDROTREATED HEAVY PARAFFINIC (CAS 64742-54-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
SEVERELY HYDROTREATED PETROLEUM OIL (CAS 64742-55-8)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

Appropriate engineering controls Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

Eye/face protection Safety glasses.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Physical state Liquid.

Color Brown

Odor Mild oily

Odor threshold Not available.

pH Not available.

Melting point/freezing point 44.49 °F (6.94 °C)

Initial boiling point and boiling range 280.4 °F (138 °C)

Flash point 305.6 °F (152.0 °C)

Evaporation rate < 1 BuAc

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) Not available.

Flammability limit - upper (%) Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Insoluble

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Flash point class	ASTM D93-08
Kinematic viscosity	20.3 cSt
Kinematic viscosity temperature	104 °F (40 °C)
Specific gravity	0.87 - 0.896

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Stable at normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	None known.
Incompatible materials	Strong oxidizing agents. Strong acids. Strong alkalis. Water.
Hazardous decomposition products	To avoid thermal decomposition, do not overheat.

11. Toxicological information

Information on likely routes of exposure

Inhalation	No adverse effects due to inhalation are expected.
Skin contact	Not classified.
Eye contact	Not classified.
Ingestion	May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics	None known.
--	-------------

Information on toxicological effects

Acute toxicity	Not classified.
----------------	-----------------

Product	Species	Test Results
CoolPAK™ L3375		
<u>Acute</u>		
Oral		
LD50	Rat	> 5000 mg/kg

Skin corrosion/irritation	Not classified.
---------------------------	-----------------

Serious eye damage/eye irritation	Not classified.
-----------------------------------	-----------------

Respiratory or skin sensitization

Respiratory sensitization	Not classified.
Skin sensitization	This product is not expected to cause skin sensitization.

Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
------------------------	--

Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
-----------------	---

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
-----------------------	--

Specific target organ toxicity - single exposure	Not classified.
--	-----------------

Specific target organ toxicity - repeated exposure	Not classified.
--	-----------------

Aspiration hazard	May be fatal if swallowed and enters airways.
-------------------	---

Chronic effects	None known.
-----------------	-------------

12. Ecological information

Ecotoxicity	Not available.
-------------	----------------

Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available.
Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations.
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Follow precautions for safe handling described in this safety data sheet.

14. Transport information

DOT

Not regulated as dangerous goods.


IATA

Not regulated as dangerous goods.


IMDG

UN number	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ALKANES, C14-16, CHLORO)
Transport hazard class(es)	
Class	9
Subsidiary risk	-
Packing group	III
Environmental hazards	
Marine pollutant	YES
EmS	F-A, S-F
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IMDG



Marine pollutant



15. Regulatory information

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

US state regulations

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 2016 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 10-13-2017

Revision date 10-10-2018

Version # 02

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Master Fluid Solutions cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.

Revision information Fire-fighting measures: Special protective equipment and precautions for firefighters
Stability and reactivity: Incompatible materials
Toxicological Information: Toxicological Data
Toxicological information: Respiratory sensitization
Toxicological information: Specific target organ toxicity - repeated exposure
Toxicological information: Specific target organ toxicity - single exposure
Regulatory information: California Proposition 65
HazReg Data: International Inventories