



# Master STAGES™ RPO 12

## Long-term Corrosion Inhibitor

### GENERAL DESCRIPTION

Master STAGES™ RPO 12 is a long-term, indoor rust preventative with a soft waxy film. RPO 12 is compatible with all metals and can be applied by dip, spray, or brush-on methods. The film thickness will be approximately eight microns.

### ADVANTAGES

- Nonstaining
- Humidity Cabinet Test: No rust @ 1400 hours (ASTM D1748)
- Salt Spray Test: No rust @ 168 hr. (ASTM B117)

### HEALTH AND SAFETY

See the most recent SDS at [2trim.us/s/?i=1126-en-US-US](http://2trim.us/s/?i=1126-en-US-US).



### NOTES

- COMBUSTIBLE: Keep away from open flames and sparks
- Available in: 1-gallon jug, 5-gallon pail, 54-gallon drum
- Europe/Asia – 20-litre pail, 204-litre drum
- For additional product applications information including performance optimization, please contact your Master Chemical Authorized Distributor at [2trim.us/distributors.php](http://2trim.us/distributors.php), your District Sales Manager, the Tech Line at 1-800-537-3365, or visit our web site at [www.master-stages.com](http://www.master-stages.com).

### PHYSICAL PROPERTIES (TYPICAL DATA)

Form .....	Liquid	Flash Point .....	111°F (44°C) (ASTM D93)
Color .....	Dark brown	Viscosity .....	N/A
Specific Gravity (H <sub>2</sub> O=1) .....	0.840-0.841	Film Type .....	Waxy
Odor .....	Kerosene	Film Thickness .....	8-11 Micron

The information herein is given in good faith and believed current as of the date of this Data & Information sheet and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation, or warranty expressed or implied is made. Consult Master Chemical Corporation for further information. For the most recent version of this document, please go to this URL: [2trim.us/di/?i=55](http://2trim.us/di/?i=55).

Master STAGES™ is a trademark of Master Chemical Corporation  
© 2007-2015 Master Chemical Corporation Revised October 29, 2015