

4952 Welder Specification Sheet

PRODUCT DESCRIPTION:

Only the finest top grain leather go into our MIG/TIG welding options. Sewn with Kevlar® thread to resist sparks and sharp metals which can unravel most gloves, you will find these gloves a great long-term value. Low heat welding often requires optimal dexterity which affords great attention to detail. You'll find features on the 4952 include Select grade cream grain cow leather, 4.5" russet split gauntlet cuff, Wing thumb and Kevlar® stitching.

FEATURES:

- Select Grade Grain Cowhide
- Wing Thumb
- Sewn with super-strong, heat-resistant DuPont(tm) Kevlar® thread
- 4 1/2"" Split Cowhide Gauntlet Cuff

APPLICATIONS:

Ship building, Concrete, Foundry, Iron work , Metal fabrication, Mig/Tig, Steel Work, Welding

TECHNICAL DATA FOR: 4952L

Material Group	Leather	ANSI Contact Heat	Level 2 (Applications less than
Product Type	Welder		284 degrees F)
Glove Size	Large		
Material	Leather		
Leather Cut	Split Shoulder		
Leather Type	Cow Skin		
Grade	Select Grade		
Features	Sewn With KEVLAR		
Lining	Unlined		
Pattern	Gunn		
Thumb Style	Wing		
Thickness	0.8 - 1.3 mm		
Made In	China		


MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrsafety.com

©2018 MCR Safety - All Rights Reserved









ltem No:	Size:	A:	B:	C:	Case Weight	UOM Weight
4952XL	X - Large	12.630	4.88	4.500	30.846 lb.	5.141
4952L	Large	12.370	4.750	4.500	28.992 lb.	4.832
4952M	Medium	12.130	4.63	4.500	25.560 lb.	4.260