

9680 Flex Tuff Dipped Specification Sheet

PRODUCT DESCRIPTION:

Our top selling FlexTuff® styles are manufactured on seamless knit liners that are flat dipped to reproduce the natural curved shape of the hand. As a result, workers benefit from less hand fatigue and greater productivity while performing detailed tasks to heavy duty jobs. The FlexTuff®'s strong 50% cotton/50% polyester shell and crinkle finish blue latex coating provides excellent protection in many applications.

FEATURES:

- Improves grip
- Natural rubber provides abrasion resistance
- Excellent comfort and fit
- Textured palm dip for extra grip and durability

APPLICATIONS:

Automotive Assembly, Farming, Landscaping, Material Handling



TECHNICAL DATA FOR: 9680S

Series	
Material Group	
Product Type	
Glove Size	
Gauge	
Material	

Made In

Flex Tuff Strings Dipped Small 10 Gauge Cotton Polyester Blend

Sri Lanka


EN 388 : CE Score - Abrasion	3
EN 388 : CE Score - Cut	1
EN 388 : CE Score - Tear	4
EN 388 : CE Score - Puncture	3

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrsafety.com

©2018 MCR Safety - All Rights Reserved



9680 Flex Tuff Dipped Specification Sheet



Item No:	Size:	A:	В:	C :	Case Weight	UOM Weight
9680M	Medium	9.45	3.94	3.15	28.128 lb.	2.344
9680S	Small	8.66	3.74	2.95	30.600 lb.	2.550
9680XL	X - Large	10.62	4.33	3.54	42.288 lb.	3.524
9680L	Large	10.04	4.13	3.62	31.680 lb.	2.640