



**MCR
SAFETY**

**9694
UltraTech
Dipped
Specification Sheet**

PRODUCT DESCRIPTION:

UltraTech® provides Ultra comfort, Ultra fit, and Ultra protection! The seamless nylon shell offers outstanding breathability and comfort while the Polyurethane palm and finger coating provides grip, puncture resistance, abrasion resistance and dexterity. Great for small parts handling. The 9694 features a 15 gauge white nylon shell and gray gray air infused nitrile coating on the palm and fingertips.

FEATURES:

- Great tactile sensitivity
- Excellent comfort and fit
- Excellent grip
- Greater dexterity
- Abrasion resistance

APPLICATIONS:

Airport , Manufacturing, Material Handling, Janitorial , Assembly
Line Production, Automotive Assembly, Landscaping,
Electronic Assembly, Semiconductor assembly



TECHNICAL DATA FOR: 9694XL

Series	UltraTech	EN 388 : CE Score - Abrasion	3
Material Group	Strings	EN 388 : CE Score - Cut	1
Product Type	Dipped	EN 388 : CE Score - Tear	3
Glove Size	X - Large	EN 388 : CE Score - Puncture	2
Gauge	15 Gauge		
Material	Nylon		
Made In	Pakistan		

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2018 MCR Safety - All Rights Reserved



MCR
SAFETY

9694
UltraTech
Dipped
Specification Sheet



Item No:	Size:	A:	B:	C:	Case Weight	UOM Weight
9694L	Large	9.85	3.94	2.76	19.008 lb.	1.584
9694XS	X - Small	8.27	3.35	2.36	13.980 lb.	1.165
9694XL	X - Large	10.43	4.33	2.95	20.760 lb.	1.730
9694S	Small	8.86	3.43	2.56	15.216 lb.	1.268
9694M	Medium	9.05	3.54	2.83	15.516 lb.	1.293

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2018 MCR Safety - All Rights Reserved