



**MCR
SAFETY**

**9699
UltraTech
Dipped
Specification Sheet**

PRODUCT DESCRIPTION:

UltraTech® provides Ultra comfort, Ultra fit, and Ultra protection! The seamless nylon shell offers outstanding breathability and comfort while the HPT palm and finger coating provides grip, puncture resistance, abrasion resistance and dexterity.

FEATURES:

- Great tactile sensitivity
- Excellent comfort and fit
- Excellent grip
- Great dexterity
- CE SCORE 4131

APPLICATIONS:

Automotive Assembly, Farming, Landscaping, Material Handling, Assembly Line Production, Construction, Manufacturing, Plumbing



TECHNICAL DATA FOR: 9699XS

| | | | |
|-----------------------|-----------|-------------------------------------|---|
| Series | UltraTech | EN 388 : CE Score - Abrasion | 4 |
| Material Group | Strings | EN 388 : CE Score - Cut | 1 |
| Product Type | Dipped | EN 388 : CE Score - Tear | 3 |
| Glove Size | X - Small | EN 388 : CE Score - Puncture | 1 |
| Gauge | 15 Gauge | | |
| Material | Nylon | | |
| Made In | Pakistan | | |

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2018 MCR Safety - All Rights Reserved



MCR
SAFETY

9699
UltraTech
Dipped
Specification Sheet



| Item No: | Size: | A: | B: | C: | Case Weight | UOM Weight |
|----------|------------|-------|------|-----|-------------|------------|
| 9699M | Medium | 10.04 | 3.78 | N/A | 15.420 lb. | 1.285 |
| 9699XXL | XX - Large | 11.22 | 4.37 | N/A | 24.096 lb. | 2.008 |
| 9699S | Small | 9.64 | 3.62 | N/A | 18.372 lb. | 1.531 |
| 9699XL | X - Large | 10.82 | 4.17 | N/A | 18.348 lb. | 1.529 |
| 9699XS | X - Small | 9.25 | 3.43 | N/A | 16.644 lb. | 1.387 |
| 9699L | Large | 10.44 | 3.98 | N/A | 21.168 lb. | 1.764 |

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2018 MCR Safety - All Rights Reserved