



MCR
SAFETY

9792

Predaflex

Supported / Dipped gloves
Specification Sheet

PRODUCT DESCRIPTION:

00013

FEATURES:

- Premium flexible nitrile
- Brushed interlock liner
- Treated with actifresh to combat odor and bacteria
- Rough finish enhances grip

APPLICATIONS:

Agriculture, Carpentry, Construction, Janitorial, Material Handling, Petrochemical industries, Oil and Gas Industry, Food



TECHNICAL DATA FOR: 9792L

Series	Predaflex	Overall Length	12 in.
Material Group	Supported	EN 388 : CE Score - Abrasion	4
Product Type	Supported / Dipped gloves	EN 388 : CE Score - Cut	1
Glove Size	Large	EN 388 : CE Score - Tear	2
Material	Nitrile	EN 388 : CE Score - Puncture	1
Grade	Industrial Grade		
Lining	Interlock		
Thumb Style	Straight		
Made In	Pakistan		

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2018 MCR Safety - All Rights Reserved



MCR
SAFETY

9792

Predaflex

Supported / Dipped gloves

Specification Sheet



Item No:	Size:	A:	B:	C:	Case Weight	UOM Weight
9792L	Large	11.811	5.160	N/A	49.812 lb.	4.151
9792XL	X - Large	0	0	N/A	53.676 lb.	4.473
9792M	Medium	0	0	N/A	50.064 lb.	4.172

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2018 MCR Safety - All Rights Reserved