



MCR
SAFETY

N9690TC

Ninja

Cut Protection Specification Sheet

PRODUCT DESCRIPTION:

00002

FEATURES:

- Dyneema and Synthetic fibers for cut protection
- Excellent abrasion resistance
- Durable Bi-polymer coating
- CE Score 4543, CPPT score 3 at 1376 grams
- Insulated with Acrylic Terry inner lining

APPLICATIONS:

Automotive Assembly, Farming, Landscaping, Agriculture, Bottling, Carpentry, Construction, Demolition, Cold storage applications, Glass handling



TECHNICAL DATA FOR: N9690TCL

Series	Ninja	EN 388 : CE Score - Abrasion	4
Material Group	Strings	EN 388 : CE Score - Cut	5
Product Type	Cut Protection	EN 388 : CE Score - Tear	4
Glove Size	Large	EN 388 : CE Score - Puncture	3
Gauge	13 / 7 Gauge	ANSI Cut	ANSI Cut A5
Material	Dyneema / Acrylic	ANSI Puncture	ANSI Puncture 4
Insulated	Insulated	ANSI Abrasion	ANSI Abrasion 4
Lining	Acrylic		
Made In	Pakistan		

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2018 MCR Safety - All Rights Reserved



MCR
SAFETY

N9690TC

Ninja

**Cut Protection
Specification Sheet**



Item No:	Size:	A:	B:	C:	Case Weight	UOM Weight
N9690TCS	Small	9.448	3.937	N/A	27.576 lb.	0.383
N9690TCXXL	XX - Large	11.417	4.764	N/A	37.728 lb.	0.524
N9690TCXL	X - Large	11.024	4.528	N/A	36.144 lb.	0.502
N9690TCM	Medium	9.843	4.134	N/A	31.464 lb.	0.437
N9690TCL	Large	10.228	4.331	N/A	33.192 lb.	0.461

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrcsafety.com

©2018 MCR Safety - All Rights Reserved