

▲ LONG CUFF NITRILE EXAM GLOVES



TEAL
NITRILE
NON-STERILE
AMBIDEXTROUS
FULLY TEXTURED
BEADED CUFF
FOR SINGLE USE ONLY
NON-LATEX

The long cuff and increased thickness provides an additional level of hand protection for the user. Nitrile offers superior puncture resistance. A textured finish allows for a good grip.

• Longer length and thicker for added protection





PRODUCT CODE				
S	N891			
М	N892			
L	N893			
XL	N894			

PACKAGING				
50	Gloves/Box			
10	Boxes/Case			

GLOVE PROFILE		ASTM D 6319	N89
Length	mm (inches)	min. 220 (8.7)	300 (11.8)
Cuff Thickness	mm (mils)	n/a	0.10 (3.9)
Palm Thickness	mm (mils)	min. 0.05 (2.0)	0.15 (5.9)
Finger Thickness	mm (mils)	min. 0.05 (2.0)	0.18 (7.1)
Tensile Strength	Before Aging After Aging	min. 14 min. 14	27 14
Elasticity/Elongation	Before Aging After Aging	min. 500 min. 400	500 400
Pinhole Defect Rate*	(AQL)	max. 2.5	1.5

^{*} Pinhole Defect Rate is FDA minimum requirement.









RECOMMENDED INDUSTRIES

