

Disposable neoprene gloves, offering chemical splash protection with enhanced grip

- **Superior chemical splash protection:** Provides chemical splash protection against a broad array of chemicals
- **Strong grip:** These PPE gloves' neoprene formulation and textured fingertips offer advanced grip performance in wet and dry conditions
- **Specialized healthcare protection:** They have also been tested against cytotoxic/chemotherapy drugs*, thereby ensuring personal protection for healthcare workers in high-risk environments
- **Easy donning:** A polymer coating makes these gloves easy to don
- **Enhanced features:** These neoprene work gloves' beaded cuff design further improves workplace safety by limiting hazardous liquid roll-off



*see product packaging for details

Industries

- Life Sciences
- Chemical
- Healthcare
- Automotive

Recommended For

- Loading centrifuges and chromatography columns
- Assembly of parts
- Sample taking and processing
- Blending, compounding solids and liquids
- Administering drugs
- Testing
- Maintenance
- Tested for use with chemotherapy drugs
- Enhanced grip in wet environments
- Damp donning
- Higher-risk clinical applications
- Protection from Type I latex allergy in HCW's or patients

TECHNICAL DATA SHEET

	Product Information
External Glove Surface	Textured Fingers
Audit Standards	EN ISO 13485:2012
Packaging Overview	100 gloves per dispenser 10 dispensers per case 1000 gloves per case
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	Indonesia
Product Segmentation	Robust
Antistatic	Yes

PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	245 / 9.6		ASTM D3767,EN 420
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151,EN 455-1
Palm Thickness (mm/mils)	0.13 / 5.1		ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.17 / 6.7		ASTM D3767,EN 420
	BEFORE AGING	AFTER AGING	
Ultimate Tensile Strength (MPa)	≥ 24	≥ 18	ASTM D412 & D573
Elongation at Break (%)	≥ 650	≥ 400	ASTM D412
Force at break (N)	≥ 9	≥ 9	ASTM D6977

ORDERING INFORMATION

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)
Product Code	NPG-888-XS	NPG-888-S	NPG-888-M	NPG-888-L	NPG-888-XL

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region
Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

Asia Pacific Region
MY: +603 8310 6688
apac.medical@ansell.com
CN: +86 21 38275000
infochina@ansell.com
JP: +813 5549 8151
info.medical.jp@ansell.com

North America Region
Ansell Healthcare Products LLC
T: +1 800 800 0444
F: +1 800 800 0445

Latin America & Caribbean Region
BR: +55 (11) 3356-3100
latam.medical@ansell.com
MX: +52 442 296 2050
latam.medical@ansell.com
CO: +57 1 288 3247
latam.medical@ansell.com

Australia
Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578

Russia
Ansell PYC
Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending; www.ansell.com/patentmarking © 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

