




Product Family
Grip N® Kevlar® - Hot Mill - 52/7457

Seamless knit, glove-within-a-glove design, Kevlar® and cotton outer shell and cotton/poly inner shell allows for thermal protection up to 400° F. The Nitrile "N" coating on both sides of glove for added grip on wet or dry objects.



Product Numbers & Ordering Information

	Product Numbers	Details
	52/7457	52/7457 Grip N® Kevlar® Hot Mill glove

Packaging Information

12 pair per pack, 72 pair per case

Overview

Key Features

- Provides protection against intermittent heat up to 400° F
- Nitrile palm coating provides excellent grip and longer life
- Knit design allows hands to breathe, unlike cut/sewn hot mill gloves
- Two glove design has outer glove made of Kevlar and cotton for cut and slash protection, and an inner glove of cotton/polyester for insulation

Recommended Industries/Use

- Construction
- Forestry
- Manufacturing
- Steel and Metals

Hazards

- Abrasion
- Cut / Puncture
- Thermal

Regulations

- ANSI/ISEA 105 - ASTM D3389-05 Abrasion Test
- ANSI/ISEA 105 cut test - Level 3 cut resistance
- EN388 - Level 5 cut-resistance
- EN420 - General Requirements - This standard defines the general requirements for protective gloves in terms of construction, fitness of purpose and safety.
- OSHA Standard -29 CFR 1915.157 - The employer shall ensure that each affected employee uses appropriate hand

protection and other protective clothing where there is exposure to hazards such as skin absorption of harmful substances, severe cuts or lacerations, severe abrasions, punctures, chemical burns, thermal burns, harmful temperature extremes, and sharp objects.

Warranty Information

LIMITED WARRANTY. Except for any warranty for a particular product or part specifically stated in our product literature, we warrant all goods sold under this agreement against defects in materials and workmanship for one year from shipment. In the event of such defects, we will, at our sole option and as your exclusive remedy, repair or replace the defective product without charge, or refund the price you have paid. In order for this warranty to be effective, you must notify us within 15 days of discovery of the defect. you must return the defective product to us within the warranty period, properly packaged and with insurance and transportation costs prepaid. We will reship the product to you at our expense in the United States. Products will conform to Honeywell published specifications if properly used and maintained and will be free from defects in materials and/or workmanship. no changes to Honeywell published specifications will be valid without Honeywell written consent. This warranty does not cover defects which we determine are because of accident, alteration, modification, negligence, misuse, abuse failure to perform adequate maintenance, or normal wear and tear.

Specifications

Ambidextrous or Hand Specific

- Ambidextrous

Coating

- Nitrile

Coating Color

- Rust

Coating Pattern

- N pattern

Construction

- Seamless knit, Glove-within-a-glove

Cuff

- Knit

Gauge / mil

- 10 gauge

Glove Type

- Cut-resistant

Length

- NA

Liner

- NA

Material

- Kevlar®/cotton outer glove and cotton/poly inner glove

Material Color

- Yellow/white

Overedge

- NA

Supported or Unsupported

- NA

Surface Finish

- NA

Additional Information

Applications:

Automotive assembly, Construction work, Cutting operations

Technical Support

Technical Support is available Monday through Friday, 8:00 AM to 7:00 PM EST. 1.800.873.5242
hsptechsupport@honeywell.com

© Honeywell International Inc.