

# Technical Data Sheet

# NORTH

**Product: Durabil Combos' FPDCOMBO Series**



The Durabil Contractors' line was derived from the existing Fall Protection line with the exception of all the bells and whistles. We have eliminated these features in order to produce a simple, easy-to-use harness and lanyard combination that is cost effective, without sacrificing quality.

## **Harness**

**Size:** Universal Fit +XL

## **Lanyard**

**Length:** 4 and 6 ft (1.2 and 1.8 m)

**Usage:** Full Body Harness with integrally connected decelerator lanyard for Fall Arrest

**Colour:** Yellow

## **Harness Webbing**

Polyester 1-3/4 inches (45 mm) wide  
Minimum tensile strength 5,000 lbs (22.2 kN)

**Hardware:** Quick Connect Buckles: Sheet – alloy steel  
Minimum breaking strength 4,000 lbs (17.8 kN)  
All hardware meets or exceeds ANSI Z-359.1 and CSA Z259.12-00 requirements

## **Lanyard Webbing**

**Outer Jacket:** Polyester 1-1/8 inches (29 mm) wide, minimum tensile strength 5,000 lbs (22.2 kN)

**Inner Energy**

**Absorbing Core:** Polyester 3/4 inches (18 mm) wide

**Hardware:** Snap Hook opening 3/4 in (20mm) (Combo1)  
Rebar Hook opening 1-3/4 in (44mm) (Combo2)  
Minimum breaking strength 5,000 lbs (22 kN)  
Snap Hooks 100% proof loaded to 3,600 lbs (16 kN) certified to ANSI Z359.1 and CSA Z259.12

**Maximum Deployment Distance:** 42 in (1070mm)

**Maximum Arresting Load:** 900 lbs (4 kN)

**Weight:** Approx. 15.6 to 18.1 lbs (7.07 to 8.25 kg) – will vary by size and hardware

**Capacity:** 310 lbs (140 kg) (combined weight of person, tools, clothing, etc)

**Number of Workers:** 1

**Operating Temperature:** -35 °C to +35 °C (-31°F to 95°F)

## **STANDARDS**

**Certified:** CAN/CSA Z259.11 –M92

**Compliance:** ANSI Z359.1 and A10.14-1991 OSHA 1910.66 App. C.

**Component Compatibility:** North full body harnesses energy absorbing lanyard combinations are designed for use with North approved components or subsystems (lifelines, lanyards, anchorage connectors and rope grabs) or as recommended by a Qualified Person.

**Warnings:** See Operating and Maintenance Instruction Manual for details.

**Storage:** Store in a cool dry place away from chemicals, water, corrosive environments, and sources of heat or spark.