



SPECIFICATION SHEET

155-1-14



NOVAX RUBBER INSULATING GLOVES

- Meet ANSI/ASTM D120 standard and NFPA 70E for use around electrical hazards and arc flash protection.
- Contoured shape reduces hand fatigue.
- Natural rubber construction offers the required dielectric properties combined with flexibility, strength and durability.
- Silicone free.

APPLICATIONS

Used exclusively for electrical purposes, such as power generation, electrical contractors, hybrid automotive repair/service, hybrid automobile manufacturing, industrial plant maintenance, utilities.

MAX USE VOLTAGE

	SC V rms	DC V
CLASS 1	7,500	11,250

10

NOVAX™ by G.B. INDUSTRIES
ANSI / ASTM CLASS 1 **MADE IN MALAYSIA** **D120 TYPE I**
MAX USE VOLT 7500V AC



TECHNICAL DATA

SHELL	Natural Rubber
COLOR	Black/Orange
CUFF STYLE	Rolled
SIZES	8-11
PACKAGING	1 pair per bag/box, 12 pair per case
CASE	16.9" x 16.9" x 19.8"
CASE WEIGHT	17.6 lbs / 8.0 kg
COO	Malaysia

BARCODES

ITEM	DOZEN	CASE
155-1-14/8	01616314058638	02616314058637
155-1-14/9	01616314058683	02616314058682
155-1-14/10	01616314058690	02616314058699
155-1-14/11	01616314058591	02616314058590

DIMENSIONS (in/cm)

	8	9	10	11
A	14.0 / 36.0	14.0 / 36.0	14.0 / 36.0	14.0 / 36.0
B	3.9 / 10.0	4.1 / 10.5	4.7 / 12.0	5.3 / 13.5

Max Thickness: 1.52mm*

