



# SPECIFICATION SHEET

## 155-4-18



### NOVAX RUBBER INSULATING GLOVES: CLASS 4

- Meet ANSI/ASTM D120 standard and NFPA 70E for use around electrical hazards and arc flash protection.
- Contoured shape reduces hand fatigue.
- Natural rubber construction offers the required dielectric properties combined with flexibility, strength and durability.
- Silicone free.

### APPLICATIONS

Used exclusively for electrical purposes, such as utilities and electrical contractors.

### MAX USE VOLTAGE

	SC V rms	DC V
CLASS 4	36,000	54,000

10

**NOVAX™ by G.B. INDUSTRIES**

ANSI / ASTM CLASS 4    MADE IN MALAYSIA    D120 TYPE I

**MAX USE VOLT 36000V AC**



### TECHNICAL DATA

SHELL	Natural Rubber
COLOR	Black/Orange
CUFF STYLE	Rolled
SIZES	8-12 (150); 9-12 (155)
PACKAGING	1 pair per bag/box, 12 pair per case
CASE	21.1" x 18.1" x 11.9"
CASE WEIGHT	35.3 lbs / 16.0 kg
COO	Malaysia

### BARCODES

ITEM	BOX	CASE
155-4-18/9	01616314063717	02616314063716
155-4-18/10	01616314063724	02616314063723
155-4-18/11	01616314063731	02616314063730
155-4-18/12	01616314063748	02616314063747

### DIMENSIONS (in/cm)

	8	9	10	11	12
<b>A</b>	18.0 / 46.0	18.0 / 46.0	18.0 / 46.0	18.0 / 46.0	18.0 / 46.0
<b>B</b>	3.9 / 10.0	4.1 / 10.5	4.7 / 12.0	5.3 / 13.5	15.0 / 5.9

Max Thickness: 3.5mm\*

