



SPECIFICATION SHEET

170-00-11

NOVAX RUBBER INSULATING GLOVES

- Meet ANSI/ASTM D120 standard and NFPA 70E for use around electrical hazards and arc flash protection.
- Contoured shape reduces hand fatigue.
- Natural rubber construction offers the required dielectric properties combined with flexibility, strength and durability.
- Silicone free.

APPLICATIONS

Used exclusively for electrical purposes, such as power generation, electrical contractors, hybrid automotive repair/service, hybrid automobile manufacturing, industrial plant maintenance, utilities.

MAX USE VOLTAGE

CLASS 00	SC V rms	DC V
	500	750

10
NOVAX™ by G.B. INDUSTRIES
 ANSI / ASTM CLASS 00 MADE IN MALAYSIA D120 TYPE I
MAX USE VOLT 500V AC



TECHNICAL DATA

SHELL	Natural Rubber
COLOR	Yellow
CUFF STYLE	Rolled
SIZES	7-12
PACKAGING	1 pair per bag/box, 12 pair per case
CASE	16.9" x 16.9" x 12.8"
CASE WEIGHT	11.0 lbs / 5.0 kg
COO	Malaysia

BARCODES

ITEM	PAIR	CASE
170-00-11/7	01616314101587	02616314101586
170-00-11/8	01616314101594	02616314101593
170-00-11/9	01616314101600	02616314101609
170-00-11/10	01616314101556	02616314101555
170-00-11/11	01616314101563	02616314101562
170-00-11/12	01616314101570	02616314101579

DIMENSIONS (in/cm)

	8	9	10	11	12
A	28.0 / 11.0	28.0 / 11.0	28.0 / 11.0	28.0 / 11.0	28.0 / 11.0
B	3.9 / 10.0	4.1 / 10.5	4.7 / 12.0	5.3 / 13.5	5.9 / 15.0

Max Thickness: .75mm*

