


# List 445

3 Flute, RHS/RHC

SPEED FEED P1261-1264 CARBIDE BR  45°

Milling Diameter Tolerance	
1/16 ≤ D ≤ 1	+0 / -0.002"



Units: Inch

EDP Number	Mill Diameter	Overall Length	Length of Cut	Shank Diameter
Bright	D	L	Lc	d
445-0625	1/16	1-1/2	3/16	1/8
445-0938	3/32	1-1/2	5/16	1/8
445-1250	1/8	1-1/2	1/2	1/8
445-1562	5/32	2	9/16	3/16
445-1875	3/16	2	5/8	3/16
445-2188	7/32	2-1/2	5/8	1/4
445-2500	1/4	2-1/2	3/4	1/4
445-2812	9/32	2-1/2	3/4	5/16
445-3125	5/16	2-1/2	13/16	5/16

EDP Number	Mill Diameter	Overall Length	Length of Cut	Shank Diameter
Bright	D	L	Lc	d
445-3750	3/8	2-1/2	1	3/8
445-4375	7/16	2-3/4	1	7/16
445-5000	1/2	3	1	1/2
445-5625	9/16	3-1/2	1-1/8	9/16
445-6250	5/8	3-1/2	1-1/4	5/8
445-6875	11/16	4	1-3/8	3/4
445-7500	3/4	4	1-1/2	3/4
445-8750	7/8	4	1-1/2	7/8
445-1000	1	4	1-1/2	1

Packed: 1 pc.  
EDP's listed above are stocked standard, other coatings available upon request.  
Specify treatment at time of order.




# List 445

3 Flute, RHS/RHC

SPEED FEED P1261-1264 CARBIDE BR  45°

Milling Diameter Tolerance	
1 ≤ D ≤ 20	+0 / -0.05mm



Units: mm

EDP Number	Mill Diameter	Overall Length	Length of Cut	Shank Diameter
Bright	D	L	Lc	d
445-0394	1.0	39	3	3
445-0591	1.5	39	5	3
445-0787	2.0	39	7	3
445-0984	2.5	39	8	3
445-1181	3.0	39	10	3
445-1378	3.5	51	12	4
445-1575	4.0	51	14	4
445-1772	4.5	51	14	5
445-1968	5.0	51	16	5
445-2362	6.0	64	19	6

EDP Number	Mill Diameter	Overall Length	Length of Cut	Shank Diameter
Bright	D	L	Lc	d
445-2756	7.0	64	19	8
445-3150	8.0	64	21	8
445-3543	9.0	70	22	10
445-3937	10.0	70	25	10
445-4331	11.0	70	25	11
445-4724	12.0	76	25	12
445-5512	14.0	89	30	14
445-6299	16.0	89	32	16
445-7087	18.0	102	35	18
445-7874	20.0	102	38	20

Packed: 1 pc.  
EDP's listed above are stocked standard, other coatings available upon request.  
Specify treatment at time of order.



## Work Material

List No.	P					M			K	N		S		H				
	Carbon Steels			Alloy Steels	Die Steels	Stainless Steels			Cast Iron	Aluminum		Nickel Alloy	Titanium	Hardened Steels				
	Low	Med.	High			300	400	17-4 PH		6061 7075	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC
445	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

good  best

