

List 455C

5 Flute, **Corner Protection**

SPEED FEED P1265-1267	CARBIDE	TiAlN	TiCN	BR		45°
--------------------------	---------	-------	------	----	---	-----

Milling Diameter Tolerance	
1/8 ≤ D ≤ 1	+0 / -0.002"



Units: Inch

EDP Number			Mill Diameter	Overall Length	Length of Cut	Shank Diameter
Bright	TiCN	TiAlN	D	L	Lc	d
455-1250	455-125008	-	1/8	1-1/2	1/2	1/8
455-1251	455-125108	455-125111	1/8	1-1/2	1/4	1/8
455-1562	455-156208	455-156211	5/32	2	9/16	3/16
455-1875	455-187508	-	3/16	2	5/8	3/16
455-1876	455-187608	455-187611	3/16	2	5/16	3/16
455-2188	-	-	7/32	2-1/2	5/8	1/4
455-2500	455-250008	-	1/4	2-1/2	3/4	1/4
455-2501	455-250108	455-250111	1/4	2	1/2	1/4
455-2502	455-250208	455-250211	1/4	4	1-1/4	1/4
455-2812	-	-	9/32	2-1/2	3/4	5/16
455-3125	-	-	5/16	2-1/2	13/16	5/16
455-3126	455-312608	455-312611	5/16	2	1/2	5/16
455-3127	455-312708	455-312711	5/16	4	1-1/4	5/16
455-3750	-	-	3/8	2-1/2	1	3/8
455-3751	455-375108	455-375111	3/8	2	5/8	3/8
455-3752	455-375208	455-375211	3/8	2-1/2	7/8	3/8
455-3753	455-375308	455-375311	3/8	4	1-1/2	3/8
455-4375	455-437508	-	7/16	2-3/4	1	7/16
455-4376	455-437608	-	7/16	2-1/2	5/8	7/16
455-4377	-	-	7/16	4	2	7/16
455-5000	-	-	1/2	3	1	1/2
455-5001	455-500108	455-500111	1/2	2-1/2	5/8	1/2
455-5002	455-500208	455-500211	1/2	3	1-1/4	1/2
455-5003	455-500308	455-500311	1/2	4-1/2	2	1/2
455-5625	-	-	9/16	3-1/2	1-1/8	9/16
455-6250	455-625008	-	5/8	3-1/2	1-1/4	5/8
455-6251	455-625108	455-625111	5/8	3	3/4	5/8
455-7500	455-750008	-	3/4	4	1-1/2	3/4
455-7501	455-750108	455-750111	3/4	3	1	3/4
455-7502	455-750208	455-750211	3/4	5	2-1/4	3/4
455-1000	-	-	1	4	1-1/2	1

Packed: 1 pc.
Corner Protection 0.005"~0.010"
EDP's listed above are stocked standard, other coatings available upon request.
Specify treatment at time of order.



List No.	Work Material																
	P					M			K	N		S		H			
	Carbon Steels			Alloy Steels	Die Steels	Stainless Steels			Cast Iron	Aluminum		Nickel Alloy	Titanium	Hardened Steels			
	Low 1010 1018	Med. 1035 1045	High 1065	4140 4340		300	400	17-4 PH		6061 7075	Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
455C	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>				<input type="checkbox"/>			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

good best

