

Carbide

Micrograin Carbide End Mills

List 461

6 Flute, RHS/RHC

SPEED FEED P1265-1267	CARBIDE	TiAlN	BR		30°
---------------------------------	----------------	--------------	-----------	--	------------

Milling Diameter Tolerance	
1/8 ≤ D ≤ 1	+0 / -0.002"



Units: Inch

EDP Number	Mill Diameter	Overall Length	Length of Cut	Shank Diameter	
					Bright
461-1250	-	1/8	1-1/2	1/2	1/8
461-1562	-	5/32	2	9/16	3/16
461-1875	461-187511	3/16	2	5/8	3/16
461-2500	461-250011	1/4	2-1/2	3/4	1/4
461-2812	-	9/32	2-1/2	3/4	5/16
461-3125	-	5/16	2-1/2	13/16	5/16
461-3750	461-375011	3/8	2-1/2	1	3/8

EDP Number	Mill Diameter	Overall Length	Length of Cut	Shank Diameter	
					Bright
461-4375	-	7/16	2-3/4	1	7/16
461-5000	-	1/2	3	1	1/2
461-5625	-	9/16	3-1/2	1-1/8	9/16
461-6250	-	5/8	3-1/2	1-1/4	5/8
461-6875	-	11/16	4	1-3/8	3/4
461-7500	-	3/4	4	1-1/2	3/4
461-1000	-	1	4	1-1/2	1

Packed: 1 pc.
EDP's listed above are stocked standard, other coatings available upon request.
Specify treatment at time of order.



List 461

6 Flute, RHS/RHC

SPEED FEED P1265-1267	CARBIDE	BR		30°
---------------------------------	----------------	-----------	--	------------

Milling Diameter Tolerance	
3 ≤ D ≤ 25	+0 / -0.05mm



Units: mm

EDP Number	Mill Diameter	Overall Length	Length of Cut	Shank Diameter
461-1181	3	39	10	3
461-1575	4	51	14	4
461-1968	5	51	16	5
461-2362	6	64	19	6
461-2756	7	64	19	7
461-3150	8	64	21	8
461-3543	9	70	22	10
461-3937	10	70	25	10

EDP Number	Mill Diameter	Overall Length	Length of Cut	Shank Diameter
461-4331	11	70	25	11
461-4724	12	76	25	12
461-5512	14	89	30	14
461-6299	16	89	32	16
461-7087	18	102	35	18
461-7874	20	102	38	20
461-8661	22	102	38	22
461-9843	25	102	38	25

Packed: 1 pc.
EDP's listed above are stocked standard, other coatings available upon request.
Specify treatment at time of order.



List No.	Work Material																		
	P					M			K	N		S		H					
	Carbon Steels			Alloy Steels	Die Steels	Stainless Steels			Cast Iron	Aluminum		Nickel Alloy	Titanium	Hardened Steels					
	Low	Med.	High	4140		300	400	17-4 PH		6061	Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC		
461	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

good best

