


List 520

2 Flute, Regular Length

SPEED FEED P1297- 1298	HSS-Co	TiN	BR	REG	30°
---------------------------------	--------	-----	----	-----	-----

Milling Diameter Tolerance	
1/8 ≤ D ≤ 2	+0.003" / -0



Units: Inch

EDP Number		Mill Diameter	Overall Length	Length of Cut	Shank Diameter
Bright	TiN	D	L	Lc	d
5200100	5200105	1/8	2-5/16	3/8	3/8
5209100	-	5/32	2-5/16	7/16	3/8
5200200	5200205	3/16	2-5/16	7/16	3/8
5209200	-	7/32	2-5/16	1/2	3/8
5200300	5200305	1/4	2-5/16	1/2	3/8
5209300	-	9/32	2-5/16	9/16	3/8
5200400	5200405	5/16	2-5/16	9/16	3/8
5209400	-	11/32	2-5/16	9/16	3/8
5200500	5200505	3/8	2-5/16	9/16	3/8
5209500	-	13/32	2-1/2	13/16	3/8
5200600	5200605	7/16	2-1/2	13/16	3/8
5209700	-	15/32	2-1/2	13/16	3/8
5200700	-	1/2	2-1/2	13/16	3/8
5201100	5201105	1/2	3	1	1/2
5201600	-	7/32	3-1/8	1-1/8	1/2
5201200	-	9/16	3-1/8	1-1/8	1/2
5201700	-	19/32	3-1/8	1-1/8	1/2
5201300	5201305	5/8	3-1/8	1-1/8	1/2
5202100	5202105	5/8	3-7/16	1-5/16	5/8
5201800	-	21/32	3-5/16	1-5/16	1/2
5201400	-	11/16	3-5/16	1-5/16	1/2
5202200	-	11/16	3-7/16	1-5/16	5/8
5201900	-	23/32	3-5/16	1-5/16	1/2
5201500	5201505	3/4	3-5/16	1-5/16	1/2
5202300	-	3/4	3-7/16	1-5/16	5/8

EDP Number		Mill Diameter	Overall Length	Length of Cut	Shank Diameter
Bright	TiN	D	L	Lc	d
5203100	5203105	3/4	3-9/16	1-5/16	3/4
5202800	-	25/32	3-5/8	1-1/2	5/8
5202400	-	13/16	3-5/8	1-1/2	5/8
5202900	-	27/32	3-5/8	1-1/2	5/8
5202500	-	7/8	3-5/8	1-1/2	5/8
5203200	5203205	7/8	3-3/4	1-1/2	3/4
5204100	5204105	7/8	3-3/4	1-1/2	7/8
5203400	-	29/32	3-3/4	1-1/2	3/4
5202600	-	15/16	3-5/8	1-1/2	5/8
5203500	-	31/32	3-3/4	1-1/2	3/4
5202700	-	1	3-5/8	1-1/2	5/8
5203300	5203305	1	3-3/4	1-1/2	3/4
5204200	-	1	3-3/4	1-1/2	7/8
5205100	5205105	1	4-1/8	1-5/8	1
5204300	-	1-1/8	3-7/8	1-5/8	7/8
5205200	-	1-1/8	4-1/8	1-5/8	1
5204400	-	1-1/4	3-7/8	1-5/8	7/8
5205300	-	1-1/4	4-1/8	1-5/8	1
5206100	-	1-1/4	4-1/8	1-5/8	1-1/4
5205400	-	1-3/8	4-1/8	1-5/8	1
5205500	-	1-1/2	4-1/8	1-5/8	1
5206200	-	1-1/2	4-1/8	1-5/8	1-1/4
5206300	-	1-3/4	4-1/8	1-5/8	1-1/4
5206400	-	2	4-1/8	1-5/8	1-1/4
5207400	-	2	5-3/4	2	2

Packed: 1pc.
EDP's listed above are stocked standard, other coatings available upon request.
Specify treatment at time of order.
2" diameter shanks have combination drive.



Work Material																		
List No.	P					M			K	N		S		H				
	Carbon Steels			Alloy Steels	Die Steels	Stainless Steels			Cast Iron	Aluminum		Nickel Alloy	Titanium	Hardened Steels				
	Low	Med.	High	4140		300	400	17-4 PH		6061	Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC	
520	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

good best

