

EXOMINI VC-10

Powdered Metal High Speed Steel




List 673

TIN-CPM-M-EDL, 2 Flute, Regular Length

SPEED FEED P1297-1298	VC10	TiN	REG	30°
--------------------------	------	-----	-----	-----

Milling Diameter Tolerance	
1/32 ≤ D ≤ 11/64	+0 / -0.0011"
D = 3/16	-0.0004" / -0.0015"



Units: Inch

EDP Number	Mill Diameter	Overall Length	Length of Cut	Shank Diameter
	D	L	Lc	d
6737005	1/32	1-7/8	3/32	3/16
6737105	3/64	1-7/8	9/64	3/16
6737205	1/16	1-7/8	3/16	3/16
6737305	5/64	1-7/8	15/64	3/16
6737405	3/32	1-7/8	9/32	3/16
6737505	7/64	1-7/8	21/64	3/16

EDP Number	Mill Diameter	Overall Length	Length of Cut	Shank Diameter
	D	L	Lc	d
6737605	1/8	1-7/8	3/8	3/16
6737705	9/64	1-7/8	13/32	3/16
6737805	5/32	1-7/8	7/16	3/16
6737905	11/64	1-7/8	1/2	3/16
6738005	3/16	1-7/8	1/2	3/16

Packed: 1 pc.
Available TiN coating only.



List No.	Work Material																
	P					M			K	N		S	H				
	Carbon Steels			Alloy Steels	Die Steels	Stainless Steels			Cast Iron	Aluminum		Nickel Alloy	Titanium	Hardened Steels			
	Low	Med.	High	4140		300	400	17-4 PH		6061	Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
673	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

good best

