

SHOCK ABSORBING LANYARD - SP - SINGLE LEG - SNAP HOOKS - 2.5' (0.8 M) - 110–220 LB CAPACITY



Product # **V81036025** | Model # **SA-5200-2.5**

SP (Shock Pack) lanyards are comprised of tear webbing which is woven in a manner that allows the webbing to tear when it has a load applied to it. This tearing absorbs a significant amount of downward force under load, reducing injury. This tear webbing is folded and shrink-wrapped into a compact 1 x 2 x 6 (2.5 x 5 x 15 cm) pack that is sewn into the lanyard next to the body connector.

- Certified to CSA Z259.11-05 standards
- Made with a superior grade, heavy-duty 1" (25 mm) polyester webbing for maximum strength with tear webbing shock absorber
- PeakWorks E4 SP lanyards have a capacity range of 110–220 lbs (50–100 kg)



TECHNICAL SPECIFICATIONS

Anchor Hook Type	Snap Hook
Body Hook Type	Snap Hook
Certification	CSA Z259.11-17
Deceleration Distance	4 ft at 220 lbs
Leg Type	Single
Length (ft.)	2.5
Length (m.)	0.8
Material	Polyester Webbing
Max. Allowable Free Fall (ft.)	6
Max. Arrest Force	900 lb (4 kN), 1800 lb
Nominal Length (ft.)	2.5
Number of Hooks	2
Special Features	Tear-Webbing Shock Absorber
Style	Webbing, Shock Absorbing
Weight	110 lb to 220

Capacity lb
(lbs.)