

SHOCK ABSORBING LANYARD - SP - SINGLE LEG - SNAP HOOKS - 4' (1.2 M) - 200 - 350 LB CAPACITY



Product # **V8104704** | Model # **SA-6400-4**

SP (Shock Pack) lanyards are comprised of tear webbing which is woven in a manner that allows the webbing to tear when it has a load applied to it. This tearing absorbs a significant amount of downward force under load, reducing injury. This tear webbing is folded and shrink-wrapped into a compact 1 x 2 x 6 (2.5 x 5 x 15 cm) pack that is sewn into the lanyard next to the body connector

- Certified to CSA Z259.11-05 standards
- Made with a superior grade, heavy-duty 1" (25 mm) polyester webbing for maximum strength with tear webbing shock absorber
- A tearaway absorber limits the arrest force to a maximum of 1800 lbf (8.0 kN) and an average arrest force of less than 1350 lbf (6.0 kN)
- PeakWorks E6 SP lanyards have a capacity range of 200–350 lbs (9 –159 kg)



TECHNICAL SPECIFICATIONS

Anchor Hook Type	Snap Hook
Body Hook Type	Snap Hook
Certification	CSA Z259.11-17
Deceleration Distance	4.4 ft at 350 lbs
Hooks	2 snap hooks (1 body, 1 anchor)
Leg Type	Single
Length (ft.)	4
Length (m.)	1.2
Length/Configuration	4' (1.2 m), single leg
Material	Polyester Webbing
Max. Allowable Free Fall	6 ft
Max. Allowable Free Fall (ft.)	6
Max. Arrest Force	1800 lb, 1,300 lb (6 kN)
Nominal Length (ft.)	4
Number of Hooks	2
Special Features	Tear-Webbing Shock Absorber

Style	Shock Absorbing, Webbing
Weight (lb)	2.5 lb
Weight Capacity (lbs.)	200 lb to 350 lb